

FESTOOL®



2006



TOOLS AND ACCESSORIES

Welcome



Welcome to Festool

Festool power tools are designed and manufactured in Germany—just as they have been for the past 81 years. Long known as the professional's professional tool choice in Europe, come discover for yourself what a growing number of professional craftsmen and women already know—that Festool is like nothing else.



"Festool is the professional's 'do it right the first time' tool."
Joe Longoria
Middle Grove, NY

"You recognize a professional by his tools—Festools."
Jim Walker
CEO/Executive Director,
Certified Floorcovering Installers
Kansas City, MO



"My compliments to you on your tool line. Our fabricators love them."
Brent Nance
Montelli Industries, Inc.,
New Braunfels, TX



"There is no comparison. With Festool things that were difficult and time-consuming are no longer."
Steve Seabough
Ellisville, MO

Festool — a history of innovation

The history of Festool is the history of a vision and a consistent company philosophy focused on the needs of users. Since the company was founded in 1925, our goal has been to offer the expert tradesman tools to make daily work better and easier. This effort has led to numerous technological breakthroughs and has made Festool a leader in innovation, expertise, and quality. Every power tool Festool sells has at least one patent-ed or patent-pending feature. These features frequently change the way professionals do their jobs – allowing them to increase their efficiency and productivity. Our customers find that Festool power tools quickly pay for themselves in time and effort saved on the job.

At Festool, we've always focused on the needs of the skilled trades and we're proud of the close relationship we enjoy with our users.



Work better with Festool technology

Festool offers not just tools, but complete, portable solutions. Our products are conceived and developed to meet practical requirements both on the jobsite and off. Consider our cordless drills with the inter-changeable Fast Fix chuck system – in

an instant, the user has a right angle drill, a straight chuck drill and a drill that can drive deep in corners and right up against rails just by snapping off and on one of the patented chucks. Then take a look at our plunge cut circular saws – make splinter-free cuts with table saw precision and mitre saw versatility with our patented saw design and guide rail system. To find out more about these tools and all the special features and benefits of our entire product line, read through this catalog or visit our website at www.festoolusa.com.

Festool is in constant contact with professional users from industry and trade so that our comprehensive system of accessories meets all of your needs. Our tools form a complete system that works together to help you work better.



Festool 3-year guarantee

The Festool guarantee grants a 3-year warranty from the date of purchase on all electric tools, provided they are operated correctly. (Not applicable for wearing parts.) Not only is it one of the longest in the industry, it's also the

strongest. You don't have to send tools in for maintenance like some manufacturers require. There are no ifs, and, or buts.



30-Day Money Back Guarantee

We are so confident that you will thoroughly enjoy our tools, that we offer a 30-day money back guarantee. If you are not completely satisfied, we will refund the full purchase price, excluding all shipping charges.

Contents

What's new?		What's new? Festool – where and how to buy Package deals	pg. 4 pg. 4 pg. 5
Expertise and Attributes		Festool expertise and attributes	pg. 6
Drilling/screwdriving		Cordless drills	pg. 16
Sawing		Plunge-cut saws Pendulum jigsaws	pg. 22 pg. 28
Routing		Routers	pg. 32
Planing		Planer	pg. 50
Sanding		Rotex – dual-mode sanders Random orbital sanders Rotary sander Duplex – linear sander Direct drive orbital sanders Deltex – detail sander Air sanders	pg. 57 pg. 59 pg. 65 pg. 67 pg. 69 pg. 73 pg. 75
Dust extraction		Mobile dust extractors	pg. 76
Guide system		Guide system	pg. 86
Multifunction tables		Portable multifunction tables	pg. 89
Organizing the workspace		Systainers Sortainers, Festool gear Festool dealers Festool feature icons	pg. 91 pg. 95 pg. 97 pg. 99

What's new?



C 12

C12

Revolutionary, brushless motor and the lightest 12v drill on the market.
See page 19.



TS 55

TS 55

Splinter-free, absolutely straight, repeatable cuts right out of the box. Light weight and extremely powerful.
See page 25.



HEPA filter

HEPA filter

Now, all CT 22 and CT 33 mobile dust extractors are standard equipped with HEPA filters.
See page 80.



TS 75

Coming Soon

TS 75 Plunge-cut Saw



RO 150

Coming Soon

RO 150 FEQ 6" Dual made Random Orbital Sander



Festool dealers in your area

We have a growing network of dealers located throughout the U.S. Our factory-trained dealers will provide demonstrations, answer any questions, and take orders.

For a Festool dealer near you, check our web site at **www.festoolusa.com/dealers**

You can also refer to page 97 or call us toll-free at (888) 337-8600.

Package deals




















CT Mini




CT 22



CT 33

Tool	Dust Extractor	CT Mini		CT 22		CT 33	
		Package Order No.	Price (Savings)	Package Order No.	Price (Savings)	Package Order No.	Price (Savings)
 TS 55 EQ Circular plunge-cut saw		PM561174	\$643.50 (\$71.50)	P2561174	\$769.50 (\$85.50)	P3561174	\$828.00 (\$92.00)
 PS 300 EQ Barrel grip jigsaw		PM561097	\$508.50 (\$56.50)	P2561097	\$634.50 (\$70.50)	P3561097	\$693.00 (\$77.00)
 PSB 300 EQ D-handle jigsaw		PM561123	\$508.50 (\$56.50)	P2561123	\$634.50 (\$70.50)	P3561123	\$693.00 (\$77.00)
 OF 1010 EQ 1 1/2 hp router		PM574240	\$549.00 (\$61.00)	P2574240	\$675.00 (\$75.00)	P3574240	\$733.50 (\$81.50)
 OF 1400 EQ 2 1/4 hp router		-	-	P2574267	\$738.00 (\$82.00)	P3574267	\$796.50 (\$88.50)
 OF 2000 E 3 1/2 hp router		-	-	P2574216	\$810.00 (\$90.00)	P3574216	\$868.50 (\$96.50)
 OF 2000 Basic 3 1/2 hp router		-	-	P2574268*	\$765.00 (\$85.00)	P3574268*	\$823.50 (\$91.50)
 HL 850 E Planer		-	-	P2574539	\$769.50 (\$85.50)	P3574539	\$828.00 (\$92.00)
 Rotex RO 150 E 6" dual-mode sander		PM571494	\$643.50 (\$71.50)	P2571494	\$769.50 (\$85.50)	P3571494	\$828.00 (\$92.00)
 ETS 150/3 EQ 6" random orbital sander 3mm (1/8") stroke		PM571540	\$486.00 (\$54.00)	P2571540	\$612.00 (\$68.00)	P3571540	\$670.50 (\$74.50)
 ETS 150/5 EQ 6" random orbital sander 5mm (3/16") stroke		PM571541	\$486.00 (\$54.00)	P2571541	\$612.00 (\$68.00)	P3571541	\$670.50 (\$74.50)
 Rotex RO 125 EQ 5" dual-mode sander		PM571536	\$571.50 (\$63.50)	P2571536	\$697.50 (\$77.50)	P3571536	\$756.00 (\$84.00)
 ES 125 EQ 5" orbital sander		PM571568	\$405.00 (\$45.00)	P2571568	\$531.00 (\$59.00)	P3571568	\$589.50 (\$65.50)
 RAS 115 4.5" rotary sander		PM570738	\$522.00 (\$58.00)	P2570738	\$648.00 (\$72.00)	P3570738	\$706.50 (\$78.50)
 Duplex LS 130 EQ Linear sander		PM567777	\$517.50 (\$57.50)	P2567777	\$643.50 (\$71.50)	P3567777	\$702.00 (\$78.00)
 DS 400 EQ Orbital delta sander		PM567566	\$427.50 (\$47.50)	P2567566	\$553.50 (\$61.50)	P3567566	\$612.00 (\$68.00)
 RS 400 EQ Orbital sander		PM567567	\$427.50 (\$47.50)	P2567567	\$553.50 (\$61.50)	P3567567	\$612.00 (\$68.00)
 RS 2 E Orbital sander		PM567669	\$522.00 (\$58.00)	P2567669	\$648.00 (\$72.00)	P3567669	\$706.50 (\$78.50)
 Deltex DX 93 E Orbital delta sander		PM567738	\$490.50 (\$54.50)	P2567738	\$616.50 (\$68.50)	P3567738	\$675.00 (\$75.00)



MFT 800



MFT 1080

Saw	MFT	MFT 800		MFT 1080	
		Package Order No.	Price (Savings)	Package Order No.	Price (Savings)
 TS 55 EQ Circular plunge-cut saw		PT856174	\$675.00 (\$75.00)	PT156174	\$783.00 (\$87.00)

Festool Expertise and Attributes



Like all of our tools, the ETS 150 EQ sander is built for the rigors of day-in, day-out use.

DURABILITY – Our tools last. Depend on it.

When you're on the job, you need tools you can depend on. And with Festool, that's what you get.

A lot of manufacturers talk about how tough their tools are, but we back ours up with a 3-year warranty – one of the longest in the industry, and certainly the strongest. We don't make you send tools in for regular maintenance or fill out lengthy reports, like some manufacturers do. Instead, if a tool doesn't work right, you send it in and we fix it or replace it, period. For three years.

Our tools regularly achieve top scores in comparison testing. There are many reasons for this: low vibration, good heat dissipation, the use of top-quality materials, careful attention to quality. We build premium tools, and we don't take shortcuts.

SAFETY – Extra safety at no extra cost.

Protecting your safety is of prime importance to Festool, in the shop and on-site.

We invest substantial design effort into workplace safety. The technologies we use include Vibration-Stop, which protects your joints from stress as the idle speed is automatically lowered to load speed. And while we recommend the use of hearing protection whenever you use power tools, the fact that our tools are exceptionally quiet plays a role in protecting your hearing.

Dust extraction is a major factor in all material-removing applications, and our mobile dust extraction technology leads the industry.

This all means that with Festool, you can minimize risks and side effects which may affect your health and that of your co-workers.

SPECIALIZATION – Anybody can build a tool. But it takes a real specialist to build a special tool.

Festool thinks in terms of specific solutions to specific problems. Our detailed knowledge of specialist trades – like cabinetmaking, furniture-making, hardwood flooring, laminate flooring, solid surface fabrication, and boatbuilding – enables us to identify and address specific needs.

That means we can provide tools that let you do things no other tools can. Since we know your trade and its demands so well, we can develop and produce the appropriate solutions – tools that are like nothing else.

The result is a line of products which meet many of the most challenging day-to-day requirements of the tradesman. This includes a series of special solutions for sawing, planing, sanding, routing and drilling. Our users often tell us that they would use no other tool for their jobs, and feel as if we had designed our tools just for them. And of course, that's exactly what we did!



Festool tools are tested rigorously.



Many Festool tools are still in regular daily use after 20 years.



We don't just quality-test our tools, we also test all our accessories.



The 1+2 guarantee: Festool provides a warranty of 3 years from the date of purchase.

EFFICIENCY – You can do a lot with Festool. For example, you can make more money.

Festool makes a difference, in the shop, on the site, and also on the bottom line. Our tools are designed for efficiency. This means they offer superior workshop logistics, job times, set-up times, service life, and overall ROI.

The cost of a tool is more than just the purchase price. How fast does it get the job done? How long does it last? How versatile is it? How long does it take to change blades, bits and pads? How long do consumables last, and how well do they perform? How much material can you save due to higher precision?

When you add it all up, the high quality, efficiency and long life of our tools gives them a real edge in the real world of professional use. Festool users find that they get more done faster, and at higher quality, and that our tools keep on performing long after others have given up and quit.

INNOVATION – You can't do tomorrow's work with yesterday's tools.

Festool has been at the forefront of tool technology for over 80 years – and always with an eye on the future. We are constantly developing innovative tool technologies which help users push the envelope of working technique and quality.

Throughout our history we have produced patents, developments, technologies, and tools, all of which have moved the industry forward. But this is not enough. We are constantly assessing what we have already accomplished, in order to turn new ideas into better, more capable, more durable, more ergonomic, safer equipment that gives you even better return on investment. This is an ongoing process.

That's why our tools do things other tools can't, and do it longer than other tools can. It's why they are like no other tools out there.

ENVIRONMENT – Help save the environment... buy Festool.

Professionals understand how important it is to avoid wastage. Like our users, we are very aware of the value of natural resources, and we do our share for the environment throughout the life cycle of our products.

The long service life of Festool tools preserves material and energy resources. By outlasting lesser tools, we prevent wastage of all of the metals, plastics, packaging, and energy that go into producing a tool.

It can take many years, but even our tools wear out eventually. We take back worn out tools free of charge, strip them down, separate the components into their different materials and recycle or reclaim them, or dispose of them in an environmentally sound manner. This naturally includes the batteries.

SYSTEM DESIGN – The best tools, the best accessories, the best results... it all fits together.

At Festool, we see each tool as an element in a greater system. You can benefit greatly from using our tools individually, and you stand to benefit even more from our comprehensive approach to efficient solutions.

This is because we offer integrated tool systems with a comprehensive range of well thought-out accessories. Developed from the ground up for specific Festool tools, they provide optimum interaction and prolonged service life. They also mean less work for you, with better results.

The system concept runs through all Festool products, encompassing special-purpose tools, general-purpose tools, our dust extraction system, accessories, and consumables.

Used as intended, the system concept makes just about any job easier and more efficient, whether it be sawing, routing, planing, drilling, sanding, or polishing.

ERGONOMICS – The tool should fit the person, not the other way around.

Since the whole idea of a tool is to make things easier, we give this careful attention in designing our tools.

That's why our tools conform so well to the human hand and the way it moves. And that's why a Festool is so easy to control for precision work – and so untiring to use – even towards the end of a long working day.



The extremely compact, ergonomic design with an integrated dust extraction port makes working a pleasure.



Sometimes the most ergonomic solution means inventing a new type of tool, like the C12 drill with interchangeable chucks.

The Festool System for Woodworking

Festool gives woodworkers a host of solutions that make their work go easier and faster. We can only show a few of them here.

CHALLENGE: Doing Extended Routing Jobs Without Strain ▶

SOLUTION: Festool OF 2000 Router

This powerful 2000 W tool makes routing a comfortable, easily handled procedure. The tilted handles let you work standing straight up, without bending your wrists. Over the course of a day, this makes a big difference in control.

Like all Festool tools, the OF 2000 has top-grade bearings with very low tolerance. There are two bearings, to keep the spindle running true for the life of the tool. This prevents chatter, for overall smoother running. It also gives very clean routing edges, so you have less refinishing effort.



The OF 2000 router lets you work in a natural position.

WOODWORKING WITH FESTOOL

- Long, straight, precise cuts quickly and easily
- Very precise jigsaw cuts
- High-precision routing
- Very efficient sanding
- Low vibration, ergonomic tools that minimize fatigue
- Efficient, quiet, mobile dust extraction

CHALLENGE: Straight Cuts Quickly and Easily

SOLUTION: Festool Plunge-cut Saw and Guide Rail

The TS 55 Plunge-cut Saw and Guide Rail let you make straight cuts almost anywhere. Just lay the Guide Rail along the line you want to cut, place the saw on it, and cut. No measuring, clamping or taping, and no need for a home-made jig. The Guide Rail stays put and lets you focus on the cut, while a splinter guard keeps the cut edge clean. It's simple, fast and effective, whether for trimming a door or cutting large sheet goods to size.



The TS 55 and Guide Rail make precise straight cuts easy.



The OF 1010 router is incredibly controllable.



CHALLENGE: Routing Final Details in a Piece You Can't Afford to Mess Up

SOLUTION: Festool OF 1010 Router

This exceptionally smooth-running, easy-handling router is among the lightest in its class. It's designed so that you can switch it on, lower the spindle, adjust the speed, raise the spindle, and switch it off without lifting off. Fast depth setting with a zero function eliminates guesswork. A low center of gravity and carefully designed handles add very good ergonomics. The resulting controllability makes this an ideal tool for precision jobs.



The Trion jigsaw makes clean perpendicular cuts.

CHALLENGE: Clean Cutouts in Thick Workpieces

SOLUTION: Festool Jigsaw

This saw solves the problem that has plagued all jigsaws before it - blade sway-out. Three-way blade guidance keeps the blade perpendicular, even in curves, even in tough materials. A splinter guard keeps the cut edge from splintering and chipping. The result is a perpendicular cut with a clean edge that follows the scribe line. This raises the bar on jigsawing, turning it from rough carpentry to finish work.



The CT 33 is quiet, efficient, and tool-triggered.



The ES 125 sander is light and smooth.

CHALLENGE: Sanding Smoothly in Odd Positions

SOLUTION: Festool Random Orbital Sanders

Most random orbital sanders shudder and jump as they work, requiring you to apply significant pressure just to keep them where you want them. Not so with Festool. Our attention to detail throughout the engineering and construction of our sanders makes them perform very smoothly. It's difficult to show just how smooth in a picture, but the difference is remarkable. You can sand with less effort and better results. The 2.4 lb ES 125 shown here is designed for one-hand use, making it perfect for touch-ups and all kinds of jobs around the shop.

CHALLENGE: Keeping a Clean Shop
SOLUTION: Festool Dust Extractor

Every shop needs a dust extractor. Our mobile CT Dust Extractors are unusually efficient. They're tool-triggered with most of our tools so they're only on when the tool is, and even then they're remarkably quiet.

ERGONOMICS

Every Festool is ergonomically designed for untiring day-long use.



CONSUMABLES

Festool has a full line of superior saw blades, router bits and abrasives.



JETSTREAM

Patented Jetstream pad design gives improved dust removal for up to 30% longer abrasive life.



LOW VIBRATION

Festool's low vibration helps you work better with less strain.



ELECTRONIC SPEED CONTROL

For constant speed under load.



SYSTAINER

Our unique Systainer tool cases are tough and stackable. They latch together for carrying convenience.



FESTOOL'S EXCLUSIVE GUARANTEES

With Festool, you get a 3-year warranty – the strongest in the industry – and a 30-day money back guarantee.

The Festool System for Flooring

Festool gives flooring installers more than just superior tools. We give you an entire system that solves the challenges of flooring installation, so you can work better, finish faster, and make more profit. It's like nothing else.

CHALLENGE: Keeping the Customer's House Clean

SOLUTION: Festool Dust Extractor

Efficient dust extraction is a must when you're working in someone's home. All of our flooring tools fit our portable CT Dust Extractor. The CT is tool-triggered, so it's only on when the tool is. In operation it's remarkably quiet but extremely efficient. You leave a clean job, and a satisfied customer.

CHALLENGE: Accurate, Repeatable Crosscutting at the Site

SOLUTION: Festool MFT and Plunge-cut Saw

Need 10 or 100 pieces exactly the same? Precise angle cutoffs? Our Multi-function Table folds up so you can take it on the job. With its adjustable angle fence and perforated top, it turns our Plunge-cut Saw into a chop, miter and radial arm sawing system. The job goes quicker – and when you're done, fold it up and take it home.



Festool Rotex – the solution for fast sanding in tight spaces

CHALLENGE: Long Straight Cuts Without Complications

SOLUTION: Festool Plunge-cut Saw and Guide Rail

With our TS 55 Plunge-cut Saw and Guide Rail you can make absolutely precise cuts anywhere, without clamping. This is a convenience on straight installations and a must for border work and inlays. Installers also appreciate the way the splinter guard protects the brittle wear layer from chipping, even on laminates.

The Guide Rail lets you saw with shop accuracy at the site, and makes quick work of chores like trimming ends. It doesn't need taping or clamping to the surface, so it leaves no marks and lets you work at any point on the floor.



Festool Multi-function Table & Plunge-cut Saw – the solution for precision crosscutting on-site

CHALLENGE: Fast Sanding in Tight Spaces

SOLUTION: Festool Rotex

Need to sand fast in small places, without scratch marks? How about in a closet, on stairs, or the perimeter of a room? Our Rotex RO 150 E Dual-Mode Sander is the way to go. The shape makes it easy to sand close to walls, and it switches from rotary to random-orbital motion to give you fast material removal and fine sanding in a single tool.

FLOORING WITH FESTOOL

- Long, straight, accurate cuts, quickly and easily
- Non-destructive cuts even on brittle laminates
- Routing to precise depths for painless, uncomplicated installs
- Highly efficient portable dust extraction to leave a clean site
- Fast, high-end installs with fewer callbacks and higher profit



Festool Plunge-cut Saw and Guide Rail – the solution for straight splinter-free cuts

CHALLENGE: Precision Regrooving ►
SOLUTION: Festool Router

Our OF 1010 EQ Router is an indispensable tool for regrooving. The ability to fine-tune the depth adjustment eliminates height variations from one board to the next, even in difficult products like laminate and pre-finished flooring. The router is also invaluable for precise inlay and medallion work. Dust extraction cleans as you go so you don't have to stop, get up, and clean up before moving on.



Festool Router – the solution for precision regrooving



Festool Jigsaw – the solution for clean scribing cuts

◀ **CHALLENGE: Clean Scribing Cuts**
SOLUTION: Festool Jigsaw

Finally, a powerful jigsaw that does what you always wished one could do. Our Trion Jigsaw has a blade support for true vertical cuts, and a splinter guard that prevents chipping even in brittle materials. You can scribe to cutouts and similar features quickly and cleanly. And the non-scarring base plate on the Trion won't damage pre-finished products.

ERGONOMICS

Every Festool is ergonomically designed for untiring day-long use.



CONSUMABLES

Festool has a full line of superior saw blades, router bits and abrasives.



JETSTREAM

Patented Jetstream pad design gives improved dust removal for up to 30% longer abrasive life.



LOW VIBRATION

Festool's low vibration helps you work better with less strain.



ELECTRONIC SPEED CONTROL

For constant speed under load.



SYSTAINER

Our unique Systainer tool cases are tough and stackable. They latch together for carrying convenience.



FESTOOL'S EXCLUSIVE GUARANTEES

With Festool, you get a 3-year warranty – the strongest in the industry – and a 30-day money back guarantee.

SOLID SURFACES WITH FESTOOL

- *Take seams down fast with no scratch marks*
- *Fast sanding with no gouging or linear marring*
- *Highly efficient dust extraction leaves a clean site*
- *Faster installs with fewer callbacks and more profit*

The Festool System for Solid Surface

Solid surface work is in a category of its own. Customers demand a perfect finish, and you can't afford to mar a workpiece. Festool gives solid surface fabricators the right tools, and more: we give you an entire system that solves installation and repair challenges, so you can work better, finish faster, and make more profit. It's like nothing else.

CHALLENGE: Keeping the Customer's House Clean

SOLUTION: Festool Dust Extractor

Efficient dust extraction is a must when you're working in someone's home. All of our solid surface tools fit our portable CT Dust Extractor.

The CT is tool-triggered, so it's only on when the tool is. It's remarkably quiet but extremely efficient. You leave a clean job, and a satisfied customer.

CHALLENGE: Fast Repairs
SOLUTION: Festool Rotex Dual-Mode Sander

The better you can sand, the better you can work. Our Rotex RO 150 E Sander makes quick work of repairs. It removes stock quickly to level out plugs on repair jobs. Then you can switch modes for intermediate sanding and fine polishing with the same sander. Unlike a belt sander, it won't gouge the surface or leave linear scratches, so it's safer and saves time and effort on finishing.

Festool Plunge-cut Saw and Guide Rail



CHALLENGE: Flawless Straight Cuts

SOLUTION: Festool Plunge-cut Saw

The TS 55 Plunge-cut Saw is the tool of choice for quick, easy panel-saw quality cuts. Ideal for trimming sheets to size, cutting buildup strips in the shop and trimming a countertop to fit during installation. It fits our Guide Rail to cut absolutely straight.

Festool Rotex



CHALLENGE: Stock Removal and Polishing

SOLUTION: Festool Rotex

The Festool Rotex RO 150 E is the premium sander for the solid surface fabricator. Used in rotary orbital mode, it removes stock quickly and is excellent at grinding down seams without linear scratching, for fewer steps to final finish. With a flip of a switch it converts to random orbital motion for intermediate sanding and fine polishing. You can do almost all of your sanding and finishing with this one tool.



Festool Rotex and Dust Extractor – the solution for quick repair sanding

Festool Router



CHALLENGE: High-Precision Routing

SOLUTION: Festool Router

A small but powerful router, the Festool OF 1010 EQ Router is capable of precise, vibration-free routing coupled with very effective dust collection. It features extremely accurate depth adjustment for exacting work.

Festool Linear Sander



CHALLENGE: Fast Contour Sanding

SOLUTION: Festool Linear Sander

Tired of tedious hand sanding? The LS 130 EQ Linear Sander is a world first – it sands edges and rebates 3 times faster than by hand. Convex and concave pads are available for cove and bullnose sanding. A special kit lets you configure a pad to your exact contour. Now you can power through jobs that used to take forever.

ERGONOMICS

Every Festool is ergonomically designed for untiring day-long use.



CONSUMABLES

Festool has a full line of superior saw blades, router bits and abrasives.



JETSTREAM

Patented Jetstream pad design gives improved dust removal for up to 30% longer abrasive life.



LOW VIBRATION

Festool's low vibration helps you work better with less strain.



ELECTRONIC SPEED CONTROL

For constant speed under load.



SYSTAINER

Our unique Systainer tool cases are tough and stackable. They latch together for carrying convenience.



FESTOOL'S EXCLUSIVE GUARANTEES

With Festool, you get a 3-year warranty – the strongest in the industry – and a 30-day money back guarantee.

The Festool System for Boating and Marine Work

Boat work generally has to take place where the boat is, so tools have to be easily transportable. When they're at the site, they have to work dust-free. These are areas where the Festool system approach shines.

CHALLENGE: Efficient Hull Sanding ► **SOLUTION:** Festool Rotex RO 150 E Dual-Mode Sander

The 6" Rotex 150 E lets you do rough sanding in rotary random mode and then switch instantly to random orbital mode for finish sanding. You get the whole job done with just one sander. The sander design makes it easy to hold on vertical surfaces like hulls. Jetstream pad design makes dust extraction very efficient by preventing build-up on the abrasive, and also extends abrasive life by up to 30%. The dust hose connection is at the end of the tool where it belongs, out of your way.

CHALLENGE: Efficient Dust Extraction Anywhere **SOLUTION:** Festool Mobile Dust Extractors

Dust extraction is a requirement for boat work. Our extremely efficient mobile dust extractors make it easy. Their large wheels give them good yard mobility, and their low profile makes them stable - an asset when working on decks and scaffolding. Our CT Mini is ideal for taking up on deck, at just 21 lbs. All of our extractors are tool-triggered so you can focus on the work, instead of on the dust extractor.



Festool dust extractors go with you to where the work is.



The Rotex 150 E gives you rough and fine sanding from the same sander.



The RS 400 EQ delta sander takes care of the details.

▲ **CHALLENGE:** Palm and Detail Sanding in a Single Tool **SOLUTION:** Festool Delta Orbital Sander

This handy tool is a great asset for detail work. It operates very efficiently as both a palm sander and detail sander, so that with a single tool you can handle all the tight corners in and on a boat.

BOAT WORK WITH FESTOOL

- *Highly efficient, quiet, mobile dust extraction*
- *Easily transportable tools that do shop-quality work*
- *Very efficient sanding*
- *Multifunctional tools reduce the number of tools to carry*
- *Systainer cases latch together to reduce trips to and from boats*



The Trion jigsaw handles thick work pieces with ease.

▲ CHALLENGE: Accurate Scribing Cuts Without a Bandsaw

SOLUTION: Festool Jigsaw

This saw solves the problem that has plagued all jigsaws before it – blade swayout. Three-way blade guidance keeps the blade perpendicular, even in curves, even in tough laminates. A splinter guard keeps the cut edge from splintering and chipping. The result is a perpendicular cut with a clean edge that follows the scribe line. In most cases this eliminates the need for a heavy bandsaw.



Each Festool comes in a Systainer, which latches to other Systainers for easy carrying.



The MFT table folds up for transport and folds out to give you table-saw functions at the job.

▲ CHALLENGE : Portable Table-Saw Functionality
SOLUTION: Festool MFT Table and Plunge Saw with Guide Rail

This setup gives you the repeatable precision of a table saw, yet it packs small enough to fit in any van. That means you can take it where the work is. You can even set it up on deck. There is no need to search for a flat sawing surface. Festool's unique Guide Rail even lets you do long cuts in sheet goods that would be difficult to do on a regular table saw.

◀ CHALLENGE: Getting Tools On and Off Boats
SOLUTION: Festool Systainers

The Systainers form a storage and transport system unlike any other. They stack and latch together, so you can carry multiple tools to the boat and up the ladder with ease, saving on time-consuming trips. Systainers offer ample space for tools and accessories, and special systainers are available for consumables. Since you have everything with you, work goes faster and you won't be tempted to skip steps.

ERGONOMICS

Every Festool is ergonomically designed for untiring day-long use.



CONSUMABLES

Festool has a full line of superior saw blades, router bits and abrasives.



JETSTREAM

Patented Jetstream pad design gives improved dust removal for up to 30% longer abrasive life.



LOW VIBRATION

Festool's low vibration helps you work better with less strain.



ELECTRONIC SPEED CONTROL

For constant speed under load.



SYSTAINER

Our unique Systainer tool cases are tough and stackable. They latch together for carrying convenience.



FESTOOL'S EXCLUSIVE GUARANTEES

With Festool, you get a 3-year warranty – the strongest in the industry – and a 30-day money back guarantee.

Cordless drills



NEW!

The C12 drill is ideal for tight spaces and has many convenient features.



Never buy another 12v drill...

Introducing the new C12—the lightest 12v on the market and the first cordless drill with a brushless motor. Lift a pound less each time you drill or drive without sacrificing any power. That's 200 fewer pounds in a typical day. As for longevity, the C12 will drive up to one million screws before it needs to be replaced.

Clever arrangement of motor, transmission and batteries allows an extremely short design: the C12 never needs more than 6" (15 cm) space.



C12 benefits at a glance

Superb ergonomics

- Uniquely compact design with 6" drill head.
- Weight centered around the hand for easy working, weighs 1 pound less than most other 12v drills.
- Takes Centrotec quick-change chuck for snap-on, snap-off bit changes, and weighs 1/2 lb. less than regular chucks.
- Takes accessory FastFix® right-angle chuck to work around corners.
- Takes accessory FastFix® eccentric chuck to work up against inside walls.

Highly controllable

- 42 torque settings permit fast yet controlled fastener seating.
- Reduction gearing for high speed or high torque, depending on the job.
- Infinitely-variable speed.

Highly durable

- New compact 1.3 amp NiCad battery can drive about 240 screws without recharging.
- Smart charger protects batteries from overcharge, for long battery life.
- Tough construction backed by our 3-year warranty.

Cordless drills



The TDK drill driver puts power, flexibility, control, and convenience into a more compact package than other drills in its class.

A drill for all reasons

The TDK packs big power into extremely compact dimensions for tremendous all-round utility. It takes our new Centrotec chuck to make bit changes a snap – literally. The TDK also takes our FastFix® angle and eccentric chucks for added flexibility. Add exceptional controllability and great ergonomics, and you have the ultimate all-day, all-purpose drill driver.

The remarkably compact transmission gives you 21 torque settings and 2 gears, so you can work fast without damaging fasteners and materials. Sink screws to exactly the depth you want simply by setting the right torque level. The high-torque motor gives you plenty to work with! The wraparound softgrip and onboard bit stowage add all-day comfort and convenience.



Use any standard bit with the Centrotec chuck.



On-board magnetic bit stowage.



Wraparound grip for an easy hold.

TDK benefits at a glance

Flexible and convenient

- The very compact, remarkably light TDK gives all the control, torque, and features you need for demanding jobs.
- The battery pack gives you enough power for up to 550 fasteners on a single charge.
- Takes new Centrotec quick-change chuck for snap-on, snap-off bit changes, weighs 1/2 lb. less than regular chucks, and measures less than 1 1/2" in length.
- Takes accessory FastFix® right-angle chuck to work around corners and the FastFix® eccentric chuck to work up against walls.
- Magnetic on-board bit storage adds speed on multi-bit jobs.

Extremely controllable

- 21 torque settings permit fast yet controlled fastener seating.
- Reduction gearing for high speed or high torque, depending on the job.
- Infinitely-variable speed.
- Wraparound softgrip for long-term comfort.
- Ergonomic center of gravity


Highly durable

- Tough construction backed by our 3-year warranty.
- Self-cleaning battery contacts for reliability.
- Smart charger protects batteries from overcharge, for long battery life.
- Motor brushes can be changed from the outside.



The Centrotec chuck makes bit changes a snap.

Interchangeable chucks



The TDK and CDD drills all take the FastFix® and Centrotec chucks, to form a versatile drilling system.

The Centrotec Chuck

Festool inventiveness covers every aspect of power tools – even the chuck. The Centrotec is not just another quick-change accessory. It actually replaces the regular straight chuck. That means there's no extra length and no extra wobble. Since the Centrotec is so light, it also saves about half a pound over conventional chucks - that makes a big difference on a long job. The Centrotec fits all Festool drills.

Speed and ease of use

With the Centrotec there's no more twisting the chuck back and forth to clamp and unclamp a bit. Instead, you just snap bits in and out. It makes the “installer's triathlon” literally a snap – drill starter hole, drill the finish hole, set the screw. Now you can blaze through those jobs like never before.

Compactness

The Centrotec is over an inch shorter than conventional chucks, and much less bulky. That means the drill is an inch shorter so you can get into tighter spaces, since there's less bulk in the way, you can also see what you're doing better.

Lightness

The Centrotec replaces a regular straight chuck and saves 7 3/8 oz. – almost half a pound. That means that for every 21 screws you drill, you heft 10 pounds less. Think about what that can mean on overhead jobs – especially towards the end of a working day.



The Festool FastFix® Chucks

The FastFix® right angle chuck lets you work at a right angle from the axis. You can position it at any angle relative to the drill body – up, down, to the sides – at 22.50° increments.



The FastFix® eccentric chuck offsets the bit to the side of the chuck. This lets you drill and drive fasteners straight, even right up against sidewalls.



Both are keyless and snap on and off in seconds, without tools.



Driving up to the edge in tight corners.



And in tight spaces.

Typical FastFix® applications

- Drawer carriages
- Door cases
- Internal cabinet fittings
- Rails and panels
- Height adjustments to wall-mounted cabinets, etc.
- Assembly work in niches, cavities, corners, and angles

Cordless drills

C12 Cordless Drill



C12

Includes LC 45 charger; 2 NiCad batteries; FastFix® keyless chuck; Centrotec starter set; In Systainer 1
 Item No. 564178/NiCad, 1.3Ah\$345.00
 Item No. 564179/NiCad, 2.4Ah\$365.00
 Item No. 564180/NiMH, 3.0Ah\$395.00

C12 Set

As above but with both right angle and eccentric FastFix® chucks
 Item No. PC1213S/1.3Ah Set\$460.00
 Item No. PC1224S/2.4Ah Set\$480.00
 Item No. PC1230S/3.0Ah Set\$510.00

C12

The very compact, remarkably light C12 offers all the power, control, torque, and features you need for demanding jobs. It's the lightest 12v on the market and the first cordless drill with a brushless motor. Lift a pound less each time you drill or drive without sacrificing any power. That's 200 fewer pounds in a typical day. As for longevity, the C12 will drive up to one million screws

- before it needs to be replaced.
- High power batteries with smart charger for long service life
- New motor design allows short drill head for compactness
- EC-TEC motor without carbon brushes produces virtually no mechanical wear
- Stepless electronic speed control for work in any material

- Softgrip for comfort on long jobs
- Good center of gravity for long jobs
- On-board magnetic bit holder
- Takes Centrotec and FastFix chucks
- The spring contacts are cleaned automatically every time the battery pack is slotted into position

Battery voltage		12 V
Idling speed	setting 1	0 - 450 rpm
	setting 2	0 - 1500 rpm
Chuck capacity		1/2" (13 mm)
Max drill diameter	in steel	9/16" (14 mm)
	in wood	1" (25 mm)
Torque setting range		2-7 Nm/0.5-2.5 Nm
Max torque	in wood	159.3 in.lbs (18 Nm)
	In steel	265.5 in.lbs (30 Nm)
Weight/charging time	1.13 Ah NiCad	3 lbs 6.8 oz/25 minutes
	2.4 Ah NiCad	3 lbs 13.4 oz/50 minutes
	3.0 Ah NiMhd	3 lbs 13.4 oz/70 minutes

(Metric dimensions binding)

Industrial Package 1

Includes 5 C12 drills, NiCad, 1.3Ah; 5 Centrotec chucks; 5 FastFix® chuck; 8 NiCad Batteries; 3 Chargers
 Item No. PC12135\$1450.00

Industrial Package 2

Includes 3 C12 drills, NiCad, 1.3Ah; 3 Centrotec chucks; 3 FastFix® chucks; 5 Batteries; 2 Chargers
 Item No. PC12133\$900.00

TDK 15.6 and 12 CE Cordless Drill



TDK 15.6 CE

Includes LC 45 charger; 2 NiCad batteries; keyless chuck; Centrotec chuck; bit holder; In Systainer 1
 Item No. 564 139\$408.00

TDK 15.6 CE Set

As above but with both right angle and eccentric FastFix® chucks.
 Item No. PTDK15S\$515.00

TDK 15.6 CE and 12 CE

The very compact, remarkably light with all the power, control, torque, and features you need for demanding jobs.
 • High power NiCad batteries with smart charger for long service life

- Sintered planetary gears
- New motor design allows short drill head for compactness
- Ball-bearing motor shaft
- Stepless electronic speed control for work in any material

- Wraparound softgrip for comfort on long jobs
- Good center of gravity for long jobs
- On-board magnetic bit holder
- Takes Centrotec and FastFix® chucks

	TDK 15.6 CE	TDK 12 CE
Battery voltage	15.6V	12V
No-load speed	0-450 rpm (low gear)	0-430 rpm (low gear)
	0-1500 rpm (high gear)	0-1400 rpm (high gear)
Chuck clamping range	Up to 1/2" (13 mm)	Up to 1/2" (13 mm)
Max. drill dia. in steel	5/8" (16 mm)	9/16" (14 mm)
Max drill dia. in wood	1 3/8" (35 mm)	1" (25 mm)
Torque setting range	4.5-62 in. lbs. (0.5-7 Nm)	4.5-62 in. lbs. (0.5-7 Nm)
Max. torque in steel	320 in. lbs. (36 Nm)	250 in. lbs. (28 Nm)
Max. torque in wood	220 in. lbs. (25 Nm)	175 in. lbs. (20 Nm)
Weight with battery	5 lbs (2.3 kg)	4.4 lbs (2 kg)

(Metric dimensions binding)

TDK 12 CE

Includes LC 45 charger; 2 NiCad batteries; FastFix® chuck; Centrotec chuck; bit holder; In Systainer 1
 Item No. 564 136\$345.00

TDK 12 CE Set

As above but with both right angle and eccentric FastFix® chucks.
 Item No. 564 163\$460.00


Accessories for cordless drills

Battery packs and chargers




No.	Description and application	Type	Item No.	Price
1	Battery pack for CDD (NiCad) a) 12 volt, 2.0 Ah as replacement or spare battery b) 9 volt, 2.0 Ah for CDD 9.6	BPH 12 C BPH 9.6 C	488 438 488 437	95.50 75.50
2	Battery pack for TDK 12 and C12 (NiCad)	BPS 12 NiCD 2.4	492 268	95.50
3	Battery pack for TDK 15.6 (NiCad) (not shown)		492 269	116.00
4	Battery pack for TDD 12 (NiCad) (not shown)		489 003	95.50
5	Battery pack for C12 a) 12 volt, 1.3 Ah as replacement or spare battery (NiCad) b) 12 volt, 3.0 Ah as replacement or spare battery (NiMH) (not shown)		493 348 491 821	83.00 106.00
6	Charger for TDK and C12 fast charger for Festool TDK and C12 cordless drills	LC 45	492 138	119.00
7	Charger for CDD and TDD superfast charger for Festool CDD and TDD cordless drills up to 12 volt Full charge in 15 minutes, electronic charge control	MC 15	564 040	164.00

Keyless chucks



No.	Description and application	Type	Item No.	Price
	Keyless chuck for clamping drill and screwdriver bits without tools			
8	Clamping range .04" - .39" (1 - 10 mm), with 1/2" - 20 UNF thread (replacement)	BF-SSB 10	487 542	30.50
9	With starting ring for clamping range .06" - .51" (1.5 - 13 mm), with 1/2" - 20 UNF thread	BF-SSB 13 A	489 373	35.50
10	FastFix keyless chuck (replacement) (not for CDD-ES)	BF-FX 13	490 698	41.00

Interchangeable chucks



No.	Description and application	Type	Item No.	Price
	FastFix chucks			
11	FastFix eccentric chuck (not for the CDD ES)	DD-ES	490 294	88.00
12	FastFix right-angle chuck (not for the CDD ES)	DD-AS	490 293	88.00
13	Centrotec chuck	WH-CE	492 135	18.00
14	Centrotec starter set (not shown) Centrotec chuck, 4mm wood drill bit, Phillips 2 HiQ and bit holder		492 772	40.00


Drill bits and accessories



No.	Description and application	Type	Item No.	Price
15	Bit store for CDD (replacement) with space for four bits, bit holder and chuck key	BD-CDD	444 905	4.00

Accessories for cordless drills

Wood drill set




Item No.	Description	Qty	Price
492 519	Wood drill set (includes 7 bits below)	1	66.00

Drill bit




Item No.	Description	Qty	Price
492 512	Drill bit, 3 mm	1	8.50
492 513	Drill bit, 4 mm	1	8.50
492 514	Drill bit, 5 mm	1	9.50
492 515	Drill bit, 6 mm	1	9.50
492 516	Drill bit, 7 mm	1	9.50
492 517	Drill bit, 8 mm	1	11.50
492 518	Drill bit, 10 mm	1	13.50

Countersink




Item No.	Description	Qty	Price
492 520	Countersink, D2-8	1	27.50
492 521	Countersink, D5-15	1	34.50

Drill bit w/depth stop



Item No.	Description	Qty	Price
492 522	Drill bit w/depth stop	1	40.00
491 794	Replacement bit	1	15.00

Countersink w/depth stop




Item No.	Description	Qty	Price
492 523	Countersink drill bit with depth stop, 3.5 mm	1	52.50
491 795	Replacement bit	1	15.00
492 524	Countersink drill bit with depth stop, 4.5 mm	1	55.50
493 274	Replacement bit	1	15.00

Hook adapter



Item No.	Description	Qty	Price
492 526	Hook adapter	1	10.50

Bit holder BHS 65



Item No.	Description	Qty	Price
492 648	Bit holder BHS 65	1	23.00

Bit holder BH 60



Item No.	Description	Qty	Price
492 539	Bit holder BH 60	1	17.00

Bit extension



Item No.	Description	Qty	Price
492 540	Bit extension	1	22.00

Pozidrive bit



Item No.	Description	Qty	Price
492 527	Pozidrive 1-100*	2	14.50
492 528	Pozidrive 2-100*	2	14.50
492 529	Pozidrive 3-100*	2	14.50
490 471	Pozidrive 1-25 HiQ	3	7.50
490 472	Pozidrive 2-25 HiQ	3	7.50
490 473	Pozidrive 3-25 HiQ	3	7.50
490 474	Pozidrive 4-25 HiQ	3	16.00
490 481	Pozidrive 1-25	10	7.50
490 482	Pozidrive 2-25	10	7.50
490 483	Pozidrive 3-25	10	7.50
490 484	Pozidrive 4-25	5	16.00

Phillips bit




Item No.	Description	Qty	Price
492 530	Phillips 1-100*	2	14.50
492 531	Phillips 2-100*	2	14.50
492 532	Phillips 3-100*	2	14.50
490 491	Phillips 1-25 HiQ	3	7.50
490 492	Phillips 2-25 HiQ	3	7.50
490 493	Phillips 3-25 HiQ	3	7.50
490 501	Phillips 1-25	10	7.50
490 502	Phillips 2-25	10	7.50
490 503	Phillips 3-25	10	7.50

Torx bit



Item No.	Description	Qty	Price
492 533	Torx 15-100*	2	14.50
492 534	Torx 20-100*	2	14.50
492 535	Torx 25-100*	2	14.50
492 536	Torx 30-100*	2	14.50
490 494	Torx 10-25 HiQ	3	11.50
490 495	Torx 15-25 HiQ	3	11.50
490 496	Torx 20-25 HiQ	3	11.50
490 497	Torx 25-25 HiQ	3	11.50
490 498	Torx 30-25 HiQ	3	11.50
490 499	Torx 40-25 HiQ	3	11.50
490 504	Torx 10-25	10	11.50
490 505	Torx 15-25	10	11.50
490 506	Torx 20-25	10	11.50
490 507	Torx 25-25	10	11.50
490 508	Torx 30-25	10	11.50

Center bit



Item No.	Description	Qty	Price
492 525	Center bit 5 mm	1	52.50

* Centrotec bits are specially designed for the Centrotec chuck. They have a longer shaft and when used with the Centrotec chuck, they extend into the spindle offering true-running precision. All Centrotec bits can also be used with standard bit holders and chucks.

Portable plunge-cut saws



The TS 55 and TS 75 plunge-cut saws with guide rail: highest precision, simple handling.

Straighter, safer, better

Portable circular saws often react unexpectedly. They wander offline and are subject to play in the guide. It's a quick way to ruin expensive material.

But not if you use a Festool plunge saw and guide rail: the saw blade makes its cut absolutely straight and splinter-free. Perpendicular or even beveled, the choice is yours. As a plunge-cut saw, it can start and end a cut accurately anywhere on the material.

Equally important, on the TS 55 and TS 75 the saw blade and riving knife retracts into the housing, unlike on conventional pendulum-cover saws, where the cover retracts instead of the blade. This automatically means greater intrinsic safety.

Saw like a professional. Try it once and you'll never look back.



The benefits at a glance

Outstanding cuts that need little or no finishing

- Absolutely straight cuts, thanks to the included guide rail.
- Splinter-free cutting, thanks to the patented splinter guard on the guide rail and on the blade housing.
- Precise cut start and end, thanks to the plunge-cut design.
- Precise and splinter-free bevel cuts, thanks to patented swiveling segments.

Significant time saving

- Quick cut setup since the guide edge and the cut edge are aligned to the scribe mark.
- Spindle stop for quick and simple blade changes.

Low long-term tool costs

- Long service life from high-quality components and original Festool accessories.
- The smooth start-up and current/temperature controls prevent overheating.
- Extreme durability backed by our 3-year warranty.

Ergonomics

- The ergonomic hand grip guide is less tiring, for easier operation.
- Very effective chip and dust extraction help keep the site and the air cleaner and healthier.



With the extensive range of system accessories for our circular saws, many different applications are now within your grasp.

Application examples

- Solid wood and veneered sheet goods
- Plaster, plasterboard, wallboard
- Cement-bonded chipboard
- Phenol-resin-bonded panels
- Plastic
- Acrylic
- Laminates
- Construction materials
- Aluminum

Controlled precision

Wood, plastic, metal – each material requires a different cutting speed. This poses no problem for the MMC electronics, which set the optimum speed for the material and automatically keeps it constant. This really counts when it comes to costly materials such as plexiglas and powder-coated aluminum, as there is no danger of melting at the cutting edge. The high-tech heart of the saw has a total of six control and monitoring functions.

The smooth start-up prevents stress on the drive and on your wrist. Automatic speed reduction reduces the noise level when the saw is idling, and two sophisticated safety systems protect the motor and cut down on repairs.



Simple and precise depth stop setting.



Plunge action.



The right speed for a multitude of materials. Electronics keep the speed constant.

Portable plunge-cut saws



Cutting doors to size – fast, safe and easy the Festool way.

Time is the most important cost factor.



Time is money.
Saving time saves money.

Comparison of the time cost factor for cutting a door to size
Task: shortening a door by 1 inch.

Manual planing	
Placing scribe marks on both corners of the door	15 sec.
Marking the entire cutting line	6 sec.
Planing the door repeatedly	2 min, 36 sec.
Sanding the edge	35 sec.
Cleaning the area	1 min, 30 sec.
Total time taken	5 minutes, 2 seconds

ATF	
Placing scribe marks on both corners of the door	15 sec.
Aligning the rail to the scribe marks and clamping	10 sec.
Sawing the door	10 sec.
Beveling the edge	20 sec.
Cleaning the area	30 sec.
Total time taken	1 minute, 25 seconds


Time saved: approx. 3.6 minutes per door

With a total of 10 identical applications per day,
the time saved would be:

36 minutes per day

Source: Festool testing laboratory

Portable circular plunge-cut saw



TS 55 EQ

Includes:

- 1 High-quality 48-tooth carbide blade
- 55" (1400 mm) guide rail
- Chip deflector
- Splinter guard
- In Systainer 4

Item No. 561 174.....Price \$430.00

See page 5 for package savings.



TS 55 EQ


Bring the accuracy of a panel saw to any site with the Festool portable plunge saw and guide rail. Dust extraction port for cleaner air and a clear view of the workpiece. Saw close to edges, cut apertures and false joints, and cut to length. For solid wood, fine veneered panels and sheet goods of all kinds, plastic, and aluminum.

- Comfortable, precise, and safe, thanks to guided saw blade with plunge-cut principle
- Quick and easy cutting depth adjustment
- Bevel unit allows you to swivel the blade by up to 45° on the guide rail for clean cut edges even on bevel cuts
- Reliable and durable thanks to sturdy drive, bearings, and gear elements
- Chip and dust extractor port for healthier working
- Integrated guide slot supplied for guide rail
- Spindle stop for quick and easy blade change
- MMC electronics with 6 control and monitoring functions, including soft start, constant speed under load, stepless speed adjustment, temperature and current-triggered overload protection

Power consumption	1,200 watts/10 amp 120 v AC
Saw blade speed	2,000 - 5,200 rpm
Saw blade diameter	6 1/4" (160 mm)
Bevel cuts	0° - 45°
Cutting depth on guide rail	1 15/16" (50 mm) straight down and 1 7/16" (37 mm) at 45°
Cutting depth without guide rail	2 1/8" (55 mm) straight down
Arbor size	.787" (20 mm)
Weight	9.92 lbs. (4.5 kg)

(Metric dimensions binding)

Portable circular plunge-cut saw



TS 75 EQ

Includes:

- 1 High-quality 48-tooth carbide blade
- 55" (1400 mm) guide rail
- Chip deflector
- In Systainer 5
- Table extension
- Limit stop

Item No. 561 188.....Price \$550.00

Coming later in 2006

TS 75 EQ Coming later in 2006

Cut as straight as a panel saw with the versatility of a portable saw. It has a multitude of uses, from fine cabinetry to cutting spiral staircase steps; from rough timber to cutting out window frames in renovation work. The TS 75 is a larger saw with greater cut depth than the TS 55.

- Comfortable, exact, and safe thanks to guided saw blade with plunge-cut principle
- Quick and easy cutting depth adjustment
- Bevel unit allows you to swivel the blade by up to 45° on the guide rail for clean cut edges even on bevel cuts
- Reliable and durable thanks to sturdy drive, bearings, and gear elements
- Chip and dust extractor port for healthier working
- Integrated guide slot for supplied guide rail
- Spindle stop for quick and easy blade change
- MMC electronics with 6 control and monitoring functions—including soft start, constant speed under load, stepless speed adjustment, temperature and current-triggered overload protection

Power consumption	1,600 watts/13 amp 120 v AC
Saw blade speed	1,350 - 3,550 rpm
Saw blade diameter	8 1/4" (210 mm)
Bevel cuts	0° - 45°
Cutting depth on guide rail	2 3/4" (70 mm) straight down and 2 1/8" (55 mm) at 45°
Cutting depth without guide rail	2 15/16" (75 mm) straight down
Arbor size	1.101" (30 mm)
Weight	13.6 lbs. (6.2 kg)

(Metric dimensions binding)



With Festool you will always find the right blade for any material.

The right tool for the job


The shape, type, and number of teeth depend on the application and the material in question. The speed also has a significant effect on the cutting result.

Simply use the color codes and symbols shown here to find the ideal saw blade for your application.

Color code for quick selection of the correct saw blade.

Color code	Material	Speed range
		3 - 6
		3 - 5
		1 - 3
		2 - 4
		3 - 6

Saw and Dust Extractor Packages



TS 55 EQ Plunge-cut Saw with FS 1400/2 Guide Rail and CT 22 E Dust Extractor with hose. Package price \$769.50

Price \$820.00 if bought separately

Save \$85.50


Item No. P2561 174

See page 5 for more package savings.



Accessories for portable plunge-cut saws

Stops and accessories




No.	Description and application	TS 55	ATF 55	AT 65	Type	Item No.	Price
1	Parallel stop can be used with workpieces up to 8 19/32" wide	•	• ¹⁾	• ²⁾	PA-HKS	483 278 491 469	17.00 40.00
2	Stop adapter to fit parallel stop 483 278		•	•	AD-AP 55 AD-AP 65	484 583 486 314	5.50 10.50
3	Splinterguard pack of 5	•				491 473	13.50
4	Set-back stop for use with FS/2 guide rail only	•	•	•	FS-RSP	491 582	6.50
5	Chip deflector (replacement)		•	•	AW-AP 55	439 696	5.50
6	Plug-it power cord, 13' (replacement)	•			SJO 2 x 16 AWG	490 656	27.50
7	Cover plate (replacement, not shown)	•				491 750	40.00

¹⁾ Only in conjunction with adapter 484 583

²⁾ Only in conjunction with adapter 486 314

Blades for portable plunge-cut saws

Saw blades



Type	Dimensions in mm	Tooth shape	No. of teeth	Item No.	Price
1 Standard saw blade for all wood materials, building panels and soft plastics, coarse cuts	160 x 2.5 x 20 (ATF 55)	ATB	12	487 377	27.50
	190 x 2.8 x 30 (AT 65)	ATB	16	486 296	36.50
Carbide offset teeth/positive					
2 Panther saw blade for fast cutting with less force, particularly rip cutting	160 x 2.5 x 20 (ATF 55)	ATB	14	439 685	32.50
	190 x 2.8 x 30 (AT 65)	ATB	14	486 298	45.50
Panther carbide offset teeth/positive					
3 Fine tooth saw blade for clean cross cuts	160 x 2.2 x 20 (ATF 55)	ATB	48	491 952	48.50
	190 x 2.8 x 30 (AT 65)	ATB	48	486 297	63.50
Carbide offset teeth/positive					
4 Universal saw blade for all wooden materials, all construction panels, soft plastics	160 x 2.2 x 20 (ATF 55)	ATB	28	490 516	36.50
	190 x 2.8 x 30 (AT 65)	ATB	32	490 517	51.00
Carbide offset teeth/positive					
5 Special saw blade for aluminum panels and section, hard and fiber reinforced plastics	160 x 2.5 x 20 (ATF 55)	TC	56	439 686	63.50
	190 x 2.8 x 30 (AT 65)	TC	68	486 299	84.00
Carbide trapezoidal flat teeth/negative					
6 Special saw blade for laminated floors and polymer materials	160 x 2.6 x 20 (ATF 55)	TC	48	489 457	55.00
	190 x 2.6 x 30 (AT 65)	TC	54	489 458	76.50
Carbide trapezoidal flat teeth/positive					

Offset tooth saw blade Alternating top bevel (ATB)

The teeth on this saw blade cut alternately to the left and right. Offset teeth are standard for all blades for wooden materials.



Trapezoidal flat tooth saw blade Triple chip (TC)

With trapezoidal teeth the edges of the teeth are bevelled on both sides. The combination of the two different saw teeth cut alternately. This tooth shape is used to cut aluminum, hard plastics, and hard coated materials.



Pendulum jigsaws



Power and precision

Most jigsaws have a hard time staying on course. Tough workpieces and curves can easily cause the blade to sway out. The result? Time-consuming finishing work like sanding or even recutting.

The Festool Trion solves the problem. Parallel-adjustable carbide-tipped jaws provide three-way blade guidance to ensure precise perpendicularity to the table at all times, even in curves. A splinter guard protects against chipping.

The result? A clean, precise cut to the scribe mark through the entire depth of the workpiece, with little or no finishing.

The Festool Trion jigsaws are among the most powerful jigsaws in existence, with a full 720 W. They can cut 4 3/4" wooden beams, 3/4" aluminum, or 3/8" steel. All our jigsaws feature adjustable pendulum stroke for powerful forward travel.

All this power and precision is exceptionally easy to control. Our jigsaws are particularly well-balanced to allow the power of the hand to be used to its best advantage. This is a significant benefit for one-handed use and work on vertical

The benefits at a glance

Better results in a shorter time

- Patented three-way blade guide for precise perpendicular cuts.
- Splinter guard for splinter-free cuts.
- Multi-Material-Control electronics for constant cutting speed and cleaner cuts.
- 0-45° bevel adjustment for bevel and miter cuts.
- Non-scarring base plate.

Easier work

- Easy "FastFix" blade change.
- Low center of gravity and ergonomic switch placement for untiring work.
- Efficient chip and dust extraction for reduced cleanup and better working environment.

Reduced total costs

- Highly durable, sturdy long-life components.
- Backed by our 3-year warranty.

and overhead surfaces. The Trion comes in two configurations to suit the way you work.

Smooth running

Electronic Multi-Material Speed Control gives you the correct constant speed for the material you're sawing. It prevents overheating, and keeps the saw running smoothly.

Versatility

You can set a bevel to 45° on either side, and you can even start cuts in wood without a pilot hole. You can set the blade to a straight or pendulum motion, depending on the material. You even get a choice of handle styles to fit the way you work – the barrel-grip PS 300 EQ, or the PSB 300 EQ with D-handle for easier one-hand use.

Dust and Chip Extraction

Suction ports on both sides of the blade ensure efficient extraction. The Trion integrates with our quiet CT dust extractors for clean working with the convenience of tool-triggered autostart.

With Festool CP saw blade guide Without saw blade guide



Perfect guidance for precise cuts

The Trion has 3-way blade guidance – first by the pendulum rod, second by the pendulum guide roller, and third at the cutting point by two carbide plates, the patented CP (Carbide Precision) blade guide. The blade stays at exactly the pre-set angle, for precise cuts of all kinds including bevel or miter cuts, and reduced sway out in tight radius cuts. You get virtually no cutting errors, spoiled workpieces, or need for reworking.

No more splintering

The simple but effective splinter guard ensures perfect, splinter-free edges. The splinter guard is automatically cut to shape by the saw blade immediately after fitting. This gives you clean cut edges and avoids the need for laborious reworking.



Suction ports are located on both sides of the blade.

The Trion powers through thick workpieces.

Pendulum jigsaws

Barrel grip jigsaw



Trion PS 300 EQ

- High power
- 3-way blade guidance
- Splinter guard for splinter-free cuts
- Adjustable pendulum stroke for powerful forward movement
- Electronic speed control
- Non-scarring stable base plate
- Dust extraction


D-handle jigsaw



Trion PSB 300 EQ

The **Trion PSB 300 EQ** has all of the benefits of the Trion PS 300 EQ, as well as:

- Special D-handle for easy one-handed use



PS 300 EQ/PSB 300 EQ

Includes:

- 2 multipurpose wood saw blades
- 1 splinter guard • Chip deflector
- Plug it power cord • In Systainer 1

PS 300 Item No. 561 097.....Price \$280.00

PSB 300 Item No. 561 123.....Price \$280.00

See page 5 for package savings.


Trion PS 300 EQ/Trion PSB 300 EQ

Power Consumption	720 watts/6 amp 120 v AC
Stroke rate (1")	1,000 - 2,900 spm
Pendulum stroke adjustment	4 stages
Bevel adjustment	0° - 45°
Cutting depth, wood	4 3/4" (120 mm)
Cutting depth, non-ferrous metals	3/4" (20 mm)
Cutting depth, steel soft	3/8" (10 mm)
Weight	5.06 lbs. (2.3 kg)/5.29 lbs. (2.4 kg)

(Metric dimensions binding)


Accessories for pendulum jigsaw PS 300 EQ/PSB 300 EQ/PS 2 E

Guides and stops



No.	Description and application	Type	Item No.	Price
1	Parallel stop for use with material up to 7 7/8" (200 mm) wide	PA-PS	490 119	22.00
2	Circle cutter for cutting circles with diameters of 4 23/32" - 28 11/32" (120 - 720 mm)	KS-PS	490 118	21.00
3	Guide stop gives absolutely straight cuts with the FS guide system For PS 300/PSB 300 jigsaws For PS 2 jigsaw	FS-PS/PSB FS-FS/PS 2	490 031 486 721	10.50 10.50

Other accessories




No.	Description and application	Type	Item No.	Price
4	Splinter guard for top quality cut edges, prevents splintering			
4a	Pack of 5 for PS 300/PSB 300	SP-PS/PSB	490 120	4.00
	Pack of 20 for PS 300/PSB 300	SP-PS/PSB 20	490 121	11.50
4b	Pack of 5 for PS 2	PSP-PS	483 372	4.00
	Pack of 20 for PS 2	PSP-PS 20	488 662	11.50
5	Chip guard (replacement) for a clear view of the workpiece, protects against flying chips, For PS 300/PSB 300 For PS 2	SF-PS300 SF-PS 2	453 491 448 596	2.00 2.00

Blades for pendulum jigsaw PS 300 EQ/PSB 300 EQ/PS 2 E

The right saw blade for every need

Saw blades



No.	Type	Length of blade	Tooth pitch mm	Tooth type	Max. material thickness	Qty. in pack	Item No.	Price
①	S 75/4	3" (75 mm)	4		< 2 1/8" (55 mm)	5	486 546	7.50
	S 75/4	3" (75 mm)	4		< 2 1/8" (55 mm)	25	486 962	33.50
②	S 105/4	4 1/8" (105 mm)	4		< 3 3/8" (85 mm)	5	486 547	12.50
③	S 75/2.5	3" (75 mm)	2.5		< 2 1/8" (55 mm)	5	486 548	8.50
	S 75/2.5	3" (75 mm)	2.5		< 2 1/8" (55 mm)	25	486 963	38.00
④	S 75/4 FS	3" (75 mm)	4		< 2 1/8" (55 mm)	5	486 549	11.00
	S 75/4 FS	3" (75 mm)	4		< 2 1/8" (55 mm)	20	490 256	40.00
⑤	S 75/4 FSG	3" (75 mm)	4		< 2 1/8" (55 mm)	5	486 551	13.50
⑥	S 105/4 FSG	4 1/8" (105 mm)	4		< 3 3/8" (85 mm)	5	486 552	18.00
	S 105/4 FSG	4 1/8" (105 mm)	4		< 3 3/8" (85 mm)	20	488 015	69.50
	S 145/4 FSG	5 3/4" (145 mm)	4		< 4 3/4" (120 mm)	5	490 179	23.00
⑦	S 75/4 K	3" (75 mm)	4		< 2 1/8" (55 mm)	5	486 563	7.50
	S 75/4 K	3" (75 mm)	4		< 2 1/8" (55 mm)	25	486 965	37.00
⑧	S 50/1.4 K	2" (50 mm)	1.4		< 1 3/10" (30 mm)	5	486 564	7.50
⑨	HS 75/4 bi	3" (75 mm)	4		< 2 1/8" (55 mm)	5	486 553	14.00
⑩	HS 75/3 bi	3" (75 mm)	3		< 2 3/8" (60 mm)	5	486 554	14.00
	HS 75/2.5 bi	3" (75 mm)	2.5		< 2 1/8" (55 mm)	5	490 178	14.00
⑪	HS 60/1.2 bi	2 3/8" (60 mm)	1.2		< 1 3/10" (30 mm)	5	486 556	12.50
	HS 60/1.2 bi	2 3/8" (60 mm)	1.2		< 1 3/10" (30 mm)	25	488 016	54.50
⑫	HS 105/1.2 bi	4 1/8" (105 mm)	1.2		< 3 3/8" (85 mm)	5	486 558	14.50
	HS 155/1.2 bi	6" (155 mm)	1.2		< 5 1/8" (130 mm)	5	490 180	15.00
⑬	HS 60/1.4 bi VA	2 3/8" (60 mm)	1.4		< 1/16" (1.5 mm)	5	490 181	12.50
⑭	HS 60/2 bi	2 3/8" (60 mm)	2		< 3/10" (30 mm)	5	486 557	12.50
⑮	HS 105/2 bi	4 1/8" (105 mm)	2		< 3 3/8" (85 mm)	5	486 559	14.50
⑯	HM 75/4.5	3" (75 mm)	4.5		< 2" (50 mm)	1	486 561	17.00
⑰	HM105/4.5	4 1/8" (105 mm)	4.5		< 3 1/8" (80 mm)	1	486 560	21.00
⑱	R 54 G	2 1/8" (54 mm)			< 3/16" (30 mm)	1	486 562	6.50

Jigsaw blades in the handy Professional Pack:

Handy packs of 20 or 25 blades. A convenient way of ensuring that you always have enough blades on hand.

Tooth, pitch, type and material



Cross-set teeth for fast cutting



Conically ground teeth for clean cuts



HCS tool steel: the standard quality for all wood materials



HS bimetal: long service and high cutting capacity



Coarse or fine saw blade: at least 3 teeth must engage workpiece at any time.



Carbide tipped (HM): resistant to high temperatures and hard wearing




















Hard soldered carbide tipped splitter, fine



Corrugated blade, teeth milled

Features Materials

		Softwood Hardwood	Chipboard	Coated chipboard Veneered plywood	Laminated boards	Fiber-reinforced plastics	Soft plastics	Acrylic Plexiglas®	Composite materials	NF-metals	Aluminum, steel sheets and section	Sandwich materials	Stainless steel	Iron and steel	Glass, tiles, ceramics
															
		①													
		②													
		③	③			③									
		④													
		⑤													
		⑥													
		⑦				⑦									
		⑧				⑧									
		⑨													
						⑩								⑩	
										⑪					
										⑫					
												⑬			
										⑭		⑭			
										⑮					
		⑯		⑯				⑯							
		⑰		⑰				⑰							
					⑱			⑱						⑲	

Features of Festool jigsaws



Clean cuts without splintering.




Cuts at precise angles.



Precise control in curves.



Long-life design for high cutting capacity and long service life.



Super-long 6 1/8" (155 mm) blade for materials up to 5 1/8" thick.

Routers




The OF 1400 runs remarkably smoothly, thanks to Vibration Stop and innovative design.

The New Benchmark

The new OF 1400 Router gives you 2 1/4+ HP in under 10 lbs., takes 1/2", 3/8", 1/4" or 8 mm bits to handle almost any project. It sets the new benchmark for top-quality routers. **NEW RATCHETING SPINDLE.** Change bits in a flash. **NEAR-TOTAL DUST EXTRACTION.** The new chip catcher helps you work super clean when used with a dust extractor. **DEEPER REACH.** Category-beating 2 3/4" routing depth lets you rout countersinks deep into rebates.

The OF 1400 raises the bar in the medium-power router class. It gives you more power in a lighter package, easier operation, smoother running, more routing depth, and the ultimate in dust extraction. With thoroughbred performance and a host of unique features, it takes routing to a new level.



*Toolless copy ring clamping
Change copy rings fast.*

OF 1400 EQ benefits at a glance

Extremely Versatile Capabilities

- 1400 W, 2 1/4+ HP class.
- 2 3/4" routing depth.
- Double column clamping with a single knob.
- Double guide rod lock with a single knob.
- Patent-pending chip catcher for near total dust extraction.
- Full suite of accessories for all kinds of jobs.
- Takes bits up to 1/2".

Convenience and control

- Toolless copy guide bushing clamping.
- Ratcheting spindle – change bits faster than ever before.
- Extremely fast and accurate depth setting, to the nearest 1/256".
- Ergonomic handle.
- Plug-it cord.
- Stepless variable speed and electronic speed control for constant speed under load.
- One-handed operation of controls.

Top results, less refinishing

- Smoother, truer running gives top-quality routed surfaces.
- Fiber baseplate prevents marring of surfaces.
- Dust extraction port for cleaner working.

Long life

- Extreme durability backed by a 3-year warranty.
- Longlife components and sealed double bearings.
- Electronic overload protection prevents overheating.



*Ratcheting spindle
A world first. Change bits faster
than ever before.*



*Near-total dust removal
A world first. The new chip
catcher rotates 360° to adjust
for the way you rout.*



The OF 2000 E is a powerful production-grade router for 1/2" bits.

No idle chatter

Many routers work well enough to start with, but after a while they start to run out of round. The result is chatter, vibration, and sub-par results.

This won't happen with the Festool OF 2000 E. This big 3.5 HP class router features sealed double bearings that ensure true running for the life of the tool. The tool runs very smoothly, for better results with less refinishing, and it keeps on running smoothly.

This plus a host of other important benefits make the OF 2000 E the router of choice for demanding professional use. It gets the job done and leaves the chatter to others.



Smooth going in tough materials.



A dust extraction port lets you work clean.

OF 2000 E benefits at a glance

Heavy-duty capabilities

- 2000 W, 3.5 HP class.
- Highly efficient power transfer to the bit due to low vibration and top-quality materials.
- Full suite of accessories for all kinds of jobs.
- 1/2" collet.

Convenience and control

- Extremely fast and accurate depth setting, to the nearest 1/256".
- Ease of use – operate the on/off switch and lock the depth adjustment without taking your hands off the handles.
- Ergonomic angled handles.
- Remarkably low weight in its class.
- Electronic speed control for constant speed under load.

Top results, less refinishing

- Smoother, truer running gives top-quality routed surfaces – no chatter or ripples to sand out.
- Fiber baseplate prevents marring of surfaces.
- Dust extraction port for cleaner working.

Long life

- Extreme durability backed by 3-year warranty.
- Longlife components and sealed double bearings.
- Electronic overload protection prevents overheating.



Simple and precise: setting the depth stop.

Exact depth

The exact routing depth is almost always critical. You need to be able to adjust the routing depth precisely if you are working to get the results you want. All Festool routers achieve this with a depth stop which is precise to thousandths of an inch. This starts at a zero point you set at the workpiece surface level. No guesswork, no time-consuming calculations, and no going back and refinishing.



The OF 1010 EQ is not only extremely versatile, it is also very easy to maneuver.

Ease of use

The ergonomics of the OF 1010 EQ give you a host of benefits which add up to an unbeatable tool.

True one-handed operation allows you to switch on, lower the tool, rout, lift the tool and switch it off, all while your other hand is steadying the workpiece. The compact design and the efficient center of gravity make the tool extremely handy. The handles are shaped for easy working from the side or from above. The OF 1010 EQ is also the lightest router of its kind and therefore less tiring to use – a real plus on extended projects.



OF 1010 EQ benefits at a glance

Versatile capabilities

- Wide range of accessories for many applications.
- 1010 W power, takes 8 mm or 1/4" bits
- Fits Festool VS 600 jointing system for fast, precise dovetails.

Convenience and control

- Extremely fast and accurate depth setting to the nearest 1/256".
- One-handed operation of controls.
- Simple bit change with spindle stop
- Very light for its class at 6 lbs.
- Electronic speed control maintains constant speed.


Top results, less refinishing

- Smooth running for top-quality routs.
- Fiber baseplate prevents marring of surfaces.
- Dust extraction port for cleaner working.

Long life

- Extreme durability backed by 3-year warranty.
- Longlife components and sealed bearings.
- Smooth start-up and temperature control protect against overheating.

Router



OF 1010 EQ

Includes:

- 8 mm and 1/4" collets
- Chip catcher
- Edge guide
- Guide stop
- Guide bushing adaptor
- In Systainer 3

Item No. 574 240Price \$325.00

See page 5 for package savings.

OF 1010 EQ

Powerful, high-precision router. A turret stop allows fast and accurate adjustment of the height of the router without the use of special tools. Adjustable speed control produces higher surface quality and longer tool life. The router has a special base runner that leaves no scratches. Designed for one- or two-handed use. Fits Festool

guide rail for precision straight guidance.


- Fine depth adjustment accurate to 1/256" (0.1 mm) and "zero" function for quick yet precise depth setting
- Turret with three adjustable stops for simple selection of routing depths
- Dust extractor port
- Edge working accessories available

- Guide rail available as an accessory
- MMC electronics with 5 control and monitoring functions, including soft start, constant speed under load, stepless speed adjustment, temperature and current-triggered overload protection.
- 32 mm Euro-hole drilling attachment available

Power consumption	1010 watts/8.5 amp 120 v AC
Drive shaft speed	10,000 - 23,000 rpm
Quick depth adjustment range	2 3/16" (55 mm)
Fine depth adjustment range	5/16" (8 mm)
Weight	5.94 lbs. (2.7 kg)

(Metric dimensions binding)

Router



OF 1400 EQ

Includes:

- 8 mm, 1/2" and 1/4" collets
- Collet wrench
- Dust extraction hood
- Chip catcher
- Bushing ring adaptor
- In Systainer 4

Item No. 574 267Price \$395.00

See page 5 for package savings.

OF 1400 EQ

Powerful, high-precision, 2 1/4 HP class router which weighs under 10 lbs – more power in a lighter package. Unique ratcheting spindle, chip catcher, and double guide column clamping. This versatile 1/2" collet router gives you a level of speed, precision, and all-around performance that's hard to match. Adjustable speed control produces higher surface quality and longer tool life. The router has a special base runner that

leaves no scratches. Fits Festool guide rail for precision straight guidance.


- Deep, 2-3/4" category-beating routing depth
- Tool-less copy ring clamping allows for fast copy ring changes
- Fine depth adjustment accurate to 1/256" (0.1 mm) and "zero" function for quick yet precise depth setting
- Double guide rod lock – clamp both guide rods with a single knob

- Dust extractor port and hood
- Edge working accessories available
- Guide rail available as an accessory
- Guide bushing adaptor for use with standard USA bushings
- MMC electronics with 5 control and monitoring functions, including soft start, constant speed under load, stepless speed adjustment, temperature- and current-triggered overload protection.

Power consumption	1400 watts/11.7 amp 120 v AC
Drive shaft speed	10,000 - 22,500 rpm
Quick depth adjustment range	2 3/4" (70 mm)
Fine depth adjustment range	5/16" (8 mm)
Collet dia. range	1/4", 3/8", 1/2" and 8 mm
Weight	9.9 lbs. (4.5 kg)

(Metric dimensions binding)

Router



OF 2000 E

Includes:

- 8 mm and 1/2" collets
- M12 to 1/2" adapter
- Dust hood
- Edge guide
- Adjustment wrench
- In Systainer 4

Item No. 574 216.....\$475.00

See page 5 for package savings.

OF 2000 Basic*

As 574 216, except no systainer, 8 mm collet or edge guide

Item No. 574 268\$425.00

See page 5 for package savings.

*Coming in Summer 2006

OF 2000 E

Tough, 3 1/4 HP class, 1/2" collet production-grade router with double bearings for lasting precision. Fast and precise depth setting, electronic speed control. Very low vibration and ergonomic handle design make even long jobs go easy. Fiber base runner prevents surface marring.

- 2000 Watts - abundant power for any task
- Sealed double bearings for rock-steady true running over the life of the tool
- Precise 1/256" depth setting, extremely accurate plunge action
- Low vibration and ergonomic handle design, for easier use and better results. Light for its class - easy to handle


- Controlled constant speed to suit the workpiece material, even under load
- Electronic starting control keeps startup smooth and jolt-free
- Dust extraction port

Power consumption	2000 watts/16.7 amp 120 v AC
Clamping collet	1/2" (also available: 1/4" dia.)
Rotary Speed	12000-22000 rpm
Fast depth adjustment range	2 9/16" (65 mm)
Fine adjustment range	13/64" (5 mm)
Adjustment accuracy	1/256" (0.1 mm)
Weight	11.2 lbs. (5.1 kg)

(Metric dimensions binding)

Accessories for routers

Clamping collets




No.	Description and application	OF1000/ 1010	OF 1400	OF2000	Type	Item No.	Price
1	Clamping collets						
	6 mm collet with nut	•			SZ-D 6/OF 1000	488 760	25.00
	1/4" (6.35 mm) collet with nut	•			SZ-D 6.35/OF 1000	488 761	25.00
	8 mm collet with nut	•			SZ-D 8/OF 1000	488 755	25.00
	1/4" collet with nut		•	•	SZ-D6,35/OF2000	492 141	34.50
	8mm collet with nut		•	•	SZ-D8/OF2000	492 005	34.50
	3/8" collet with nut		•	•	SZ-D9,53/OF2000	492 142	34.50
	1/2" collet with nut (replacement)		•	•	SZ-D12,7/OF2000	492 143	34.50

Copying rings



No.	Description and application	OF1000/ 1010	OF 1400	OF2000	Type	Item No.	Price
2	Copying rings						
	d = 13.8 mm (.543"), dia. 11 mm (.433")	•		•	KR D 13.8/OF 1010	484 176	8.50
	d = 10.8 mm (.425"), dia. 9 mm (.354")	•		•	KR D10.8/OF 1010	486 029	8.50
	d = 17 mm (.669"), dia. 15 mm (.590")	•		•	KR D 17/OF 1010	486 030	8.50
	d = 24 mm (.944"), dia. 21 mm (.826")	•		•	KR D 24/OF 1010	486 031	8.50
	d = 27 mm (1.062"), dia. 25 mm (.984")	•		•	KR D 27/OF 1010	486 032	8.50
	d = 30 mm (1.181"), dia. 27 mm (1.062")	•		•	KR D 30/OF 1010	486 033	8.50
	d = 40 mm (1.575"), dia. 37 mm (1.457")	•		•	KR D 40/OF 1010	486 034	8.50
	d = 17 mm (.669"), dia. 15 mm (.590")	•		•	KR D 17/V5 600	490 770	10.50
	d = 24 mm (.944"), dia. 22 mm (.866")	•		•	KR D 24/V5 600	490 771	10.50
	d = 8.5 mm (.335"), dia. 6.5 mm (.255")	•		•	KR D 8.5/V5 600	490 772	10.50
3	Copying rings						
	d = 24 mm (.994")		•		KR D 24/OF 1400	492 183	14.50
	d = 27 mm (1.062")		•		KR D 27/OF 1400	492 184	14.50
	d = 30 mm (1.181")		•		KR D 30/OF 1400	492 185	14.50
	d = 40 mm (1.575")		•		KR D 40/OF 1400	492 186	14.50
	d = 8.5 mm (.335")		•		KR D 8.5/V5 600	492 179	14.50
	d = 13.8 mm (.543")		•		KR D 13.8/V5 600	492 180	14.50
	d = 17 mm (.669")		•		KR D 17/V5 600	492 181	14.50
	d = 24 mm (.994")		•		KR D 24/V5 600	492 182	14.50
4	Copying ring set (24/27/30/40 mm)			•	KRH-OF2000 Set	487 441	51.50
5	Copying rings						
	d = 24 mm (.944")			•	KR-D24/OF2000	487 019	10.50
	d = 27 mm (1.062")			•	KR-D27/OF2000	487 018	10.50
	d = 30 mm (1.181")			•	KR-D30/OF2000	487 016	10.50
	d = 40 mm (1.575")			•	KR-D40/OF2000	487 017	10.50


Edge trimming



No.	Description and application	OF1000/ 1010	OF 1400	OF2000	Type	Item No.	Price
6	Angle arm						
	Required to copy workpieces in conjunction with the copier scanning set KT-OF	•	•	•	WA-OF	486 052	28.50
7	Copier scanning set						
	Copier scanning set KT-OF and angle arm WA-OF are needed to copy workpieces	•	•	•	KT-OF	486 534	45.50
8	Edging plate						
	Angle arm WA-OF and edging plate UP-OF are needed for the flush trimming of projecting edges	•	•		UP-OF	486 058	43.00
9	Chipguard						
		•			SF-OF	486 242	18.00

Accessories for routers

Hole drilling system



No.	Description and application	OF1000/ 1010	OF 1400	OF2000	Type	Item No.	Price
1	Hole drilling set Guide plate with centering mandrel and two side stops; for drilling rows of holes in shelves and furniture fittings in a 32 mm grid pattern (Euro-holes) • bits sold separately	•	•		LR 32-Set	583 160 583 290*	162.00 162.00
2	Guide plate with centering mandrel	•	•		FP-LR 32	485 761 494 340*	82.00 82.00
3	Edge guide with stop rider for parallel alignment of guide rails	•			SA-LR 32	485 758	43.00
4	Stop rider (separate item)	•			AR-LR 32	485 759	21.00
5	Guide rails for rows of holes Length 42 1/2" (1080 mm) Length 95 13/32" (2424 mm)	•			FS 1080/2-LR 32 FS 2424/2-LR 32	491 621 491 622	63.00 205.00
6	Hole drilling set in Systainer • Guide plate • Centering mandrel • 2 side stops with stop riders • 2 linear stops • 2 clamps • Operating tool • Carbide-tipped hinge-location bit 35 mm • 2 carbide-tipped dowel drills 5 mm • In Systainer 1	•	•		LR 32-SYS	489 270 583 291*	369.00 369.00

*Coming in Summer 2006

Other accessories



No.	Description and application	OF1000/ 1010	OF 1400	OF2000	Type	Item No.	Price
7	Extension table to enlarge support area when trimming edges	•			TV-OF 1000	488 756	26.50
8	Hard fiber base runner without centering bore	•			TP-OF	489 229	12.50
9	Hard fiber base runner with small bore		•		TP-OF	492 574	25.00
10	Extractor hood for edge guide (not shown)			•	AH-SA-OF 2000	489 565	16.00
11	Routing aid Plexiglas® template for routing grooves or slots	•		•	OF-FH-Plus	492 037	228.00
12	Table widener	•	•	•	AS-OF 1010 AS-OF 1400 AS-OF 2000	493 139 493 233 493 046	80.00 90.00 95.00
13	Centering mandrels for 8 mm collets and 1/4" (6.35 mm) collets	•	•	•	ZD-OF dia. 6.35/8mm	492 187	21.00
14	Extractor hood for VS 600 jointing set/edge trimming	•	•		AH-OF 1000 AH-OF 1400	484 453 492 585	13.00 31.50
15	Dust hood (replacement, not shown)		•	•	AH-OF 1400 AH-OF 2000	492 000 444 376	14.50 9.50
16	Guide bushing adaptor (not shown)	•	•	•		469 625 493 566 469 627	20.00 20.00 20.00

Accessories for routers

Edge guides, stops and circles



No.	Description and application	OF1000/ 1010			Type	Item No.	Price
		OF 1400	OF 2000				
1	Guide stop Allows use of router with the FS guide system, complete with support	•	•	•	FS-OF 1000 FS-OF 1400 FS-OF 2000	488 752 492 601 487 010	24.00 60.00 43.00
2	Support (replacement)	•	•	•		438 608	3.00
3	Fine adjuster for guide stop	•			FE-FS/OF 1000	488 754	17.00
4	Edge guide	•	•		SA-OF 1000 SA-OF 1400	489 427 492 636	27.50 52.50
5	Parallel guide (not shown)			•		487 839	125.00
6	Chip guard (replacement) for edge guide	•				437 307	8.50
7	Chip catcher (replacement)	•	•	•	KSF-OF 1010 KSF-OF 1400 KSF-OF 2000	493 180 492 732 493 259	12.50 14.50 17.00
8	Trammel unit For cutting radii, circles and decorative curves on surfaces and edges 6" - 30" (153 - 760 mm) diameter	•			SZ-OF 1000	483 922	17.00
9	Plug-it power cord, 13' (replacement)	•	•		SJO 2 x 16 AWG	490 656	27.50

Multi-routing template



Festool MFS — Multi-routing template


The Festool MFS System is made for anybody that's ever had to create and use complex hand-made templates. All over the world, woodworkers, carpenters, solid surface workers, furniture and cabinetmakers are using the MFS and saving a lot of time. Now, in just a matter of moments, you can have an accurate, adjustable, template guide system for lines, squares, rectangles, curves or circles.

The benefits at a glance

MFS Template System

- Portable, flexible and accurate –easy to use in the shop and at the job site
- Specifically designed for Festool routers but can also be used with other routers
- Makes precise mortise and tenons and other jointery, cuts grooves, flutes, holes - even round and elliptical cut-outs quickly
- No need for time consuming template construction
- Made from anodized aluminum profile. Can be adjusted precisely from 1/32" and extended to any length
- Better than CNC routers for making small-quantity production runs and is far less expensive
- More accurate and efficient than hand-made templates

Accessories for multi-routing template



No.	Description and application	OF1000/ 1010			Type	Item No.	Price
		OF 1400	OF2000				
1	Template MFS400 15.7" x 7.8" includes 2 angle stops, tilt protection and circle routing insert	•	•	•		492 610	229.00
2	Template MFS700 27.5" x 15.7" includes 2 angle stops, tilt protection and circle routing insert	•	•	•		492 611	351.00
3	Routing slide (not shown)	•	•	•		492 728	108.00
4	Extension profile 1000 39" long Quantity: 2	•	•	•		492 725	229.00
5	Extension profile 2000 78" long Quantity: 2	•	•	•		492 726	302.00

Bits

Shank dia. 8 mm

Hinge location bits

HW



D/mm	L/mm	Item No.	Price
20	54.5	491 072	45.00
35	54.5	491 077	58.00

Straight/mortising bits

HW



D/mm	B/mm	L/mm	Item No.	Price
3	6	45	490 952 ¹⁾	26.50
4	10	45	490 953 ¹⁾	26.50
5	12	45	490 954 ¹⁾	27.50
6	14	55	490 955 ¹⁾	27.50
7	17	55	490 956 ¹⁾	28.50
8	20	55	490 957 ¹⁾	29.50
9	23	55	490 958 ¹⁾	25.00
10	20	60	490 959 ¹⁾	25.00
10	25	60	490 960 ²⁻³⁾	27.50
11	20	60	490 961 ¹⁾	28.50
12	20	60	490 962 ¹⁾	28.50
13	20	60	490 963 ¹⁾	29.50
14	20	60	490 964 ¹⁾	29.50
15	20	60	490 965 ¹⁾	32.50
16	20	70	490 966 ¹⁾	35.50
16	30	65	490 967 ¹⁾	37.00
18	20	70	490 968 ¹⁾	38.00
18	30	65	490 969 ¹⁾	38.00
19	20	70	490 970 ¹⁾	38.00
20	20	70	490 971 ¹⁾	39.00
20	30	65	490 972 ¹⁾	40.00
22	20	70	490 973 ¹⁾	41.00
24	20	60	490 974 ¹⁾	44.00
25	20	60	490 975 ¹⁾	48.50
30	20	60	490 976 ¹⁾	53.50


¹⁾ Solid carbide bit

²⁾ Bit for slotted joints with the Festool VS 600 FZ 10, with long edges and precise dimensional accuracy

³⁾ Bit with long edges and carbide-tipped cutting faces

Groove/slot cutters

HSS




D/mm	NL/mm	L/mm	Item No.	Price
3	8	45	490 941 ¹⁾	12.50
4	15	48.5	490 942 ¹⁾	9.50
5	12	50	490 943 ¹⁾	12.50

¹⁾ Single-edged bit

Dowel drills

HW



D/mm	B/mm	L/mm	Item No.	Price
3	16	55	491 065 ²⁾	29.50
5	30	53.5	491 064 ¹⁾	25.00
5	30	53.5	491 066 ²⁾	21.00
6	30	53.5	491 067 ²⁾	21.00
8	30	53.5	491 068 ²⁾	22.00
10	30	53.5	491 069 ²⁾	23.00

¹⁾ With v-shaped tip for splinter-free through holes

²⁾ With centering bit and pre-cutter. With high precision diameters for dowel joints with the VS 600 DS 32

Slot cutters without spindles

HW



D/mm	d/mm	B/mm	Item No.	Price
40	6	1.5	491 038	17.00
40	6	1.8	491 039	17.00
40	6	2	491 040	17.00
40	6	2.5	491 056	18.00
40	6	3	491 057	19.00
40	6	3.5	491 058	19.00
40	6	4	491 059	19.00
40	6	5	491 060	20.00


Cutter spindles for slot cutters

Spindle only (no bearing)	491 062	10.50
Spindle with bearing D15	491 061	17.50
Spindle with bearing D28	491 557	31.50

V-groove bits

HW

Two-edged



D/mm	B/mm	L/mm	alpha	Item No.	Price
32	16	49	90°	491 001 ¹⁾	49.50


¹⁾ Special v-groove bit with flattened tip for use with drywall.

Script bits

HSS

HW


Special single-edged script cutters



D/mm	B/mm	L/mm	alpha	Item No.	Price
11	9.5	55	60°	491 002	30.50
11	9.5	55	60°	491 003	37.00

Keyhole bit

HW



D/mm	NL/mm	L/mm	Item No.	Price
10.5	13	50	491 035	28.50

Bits

Shank dia. 8 mm

Core box bits HW



D/mm	NL/mm	L/mm	R	Item No.	Price
8	8	38	4	490 983	25.00
12.7	10	40	6.35	490 984	28.50
16	11	41	8	490 985	29.50
19.4	11	41	9.7	490 986	31.50
25.4	14	44	12.7	490 987	39.00

Cove bits w/bearing guide HW



D/mm	NL/mm	L/mm	R	Item No.	Price
25.5	12.7	54	6.35	491 018	40.00
28.8	14	56	8	491 019	43.00
31.7	14.3	56	9.5	491 020	45.00
38.1	16	57	12.7	491 021	51.50

Ogee bit w/bearing guide HW



D/mm	NL/mm	L/mm	R1/R2	Item No.	Price
36.7	21	61	6/6	491 031	58.00

Beading bits HW



D/mm	NL/mm	L/mm	R	Item No.	Price
17	10	40	3	491 004	41.00
19	11	41	4	491 005	42.00
21	12	42	5	491 006	44.00
23	13	43	6	491 007	46.00
27	15	45	8	491 008	48.50

Ogee bit w/bearing guide HW



D/mm	NL/mm	L/mm	R1/R2	Item No.	Price
31.7	13	53	4/4	491 029	51.50
38.1	19	59	6.35/6.35	491 030	58.00

Classical bit HW



D/mm	NL/mm	L/mm	R1/R2	Item No.	Price
19	12.5	54	5/4	491 032	46.00

Roundover bits w/bearing guide HW



D/mm	NL/mm	L/mm	R	Item No.	Price
16.7	9	49	2	491 009	44.00
18.7	10	50	3	491 010	44.00
20.7	11	51	4	491 011	45.00
22.7	12	52	5	491 012	46.00
25.5	13.5	54	6.35	491 013	46.00
28.7	15	55	8	491 014	49.50
31.7	16.5	56.5	9.5	491 015	51.50
38.1	19	59	12.7	491 016	56.50
42.7	22	62	15	491 017	60.00

Edge trimming bit w/bearing guide HW



D/mm	NL/mm	L/mm	Item No.	Price
12.7	25	65	491 027	42.00
19	25		491 028	45.00

(like above but with top bearing)

Hand hole bit HW



D/mm	NL/mm	R	Item No.	Price
19	26	16	491 033	68.50

Bits

Shank dia. 8 mm

Stile bit

HW



D/mm	B/mm	NL/mm	Item No.	Price
43	5	21	491 129	88.00

Rail bit

HW



D/mm	B/mm	NL/mm	Item No.	Price
43	5	21	491 130	91.50

Panel raising bit without bearing

HW



D/mm	NL/mm	L/mm	R	Item No.	Price
42.7	13	50	6	491 138	61.00

Reversible stile and rail bit


HW



D/mm	B/mm	NL/mm	R	Item No.	Price
46	4	20	22	490 645	174.00

Reversible stile and rail bit

HW



D/mm	B/mm	NL/mm	R	Item No.	Price
46	4	20	22	490 643	174.00

Roundover bit

HW



D/mm	NL/mm	L/mm	R	Item No.	Price
42	14	54	6	491 131	65.00

Profile bit


HW



D/mm	NL/mm	L/mm	R1/R2	Item No.	Price
42	13	50	6/12	491 137	62.00

Bullnose bit


HW



D/mm	NL/mm	L/mm	R	Item No.	Price
27	28	70	12	491 139	65.00

Fingergrip bit

HW



D/mm	NL/mm	L/mm	R	Item No.	Price
22	16	50	2.56	491 140	64.00

Chamfer bits w/bearing guide

HW



D/mm	NL/mm	L/mm	F°	Item No.	Price
24	10	50	30°	491 024	35.50
24	11.5	53	45°	491 025	42.00

Roundover bits w/angled bearing

HW



D/mm	NL/mm	L/mm	R	F°	Item No.	Price
17.5	19	61.5	6	15°	491 134	57.00
23.1	19	60.5	6	30°	491 135	58.50
31.4	18.5	60.5	6	45°	491 136	60.50
491 403	Angled bearing (repl.) for 491 134					24.00
491 404	Angled bearing (repl.) for 491 135					24.00
491 405	Angled bearing (repl.) for 491 136					26.00

Chamfer bits w/bearing


HW



D/mm	NL/mm	L/mm	F°	Item No.	Price
25.7	25.1	70	15°	491 132	45.00
38.5	23	64.5	30°	491 133	53.50

Bits

Shank dia. 8 mm


Aluminum bit				HSS
				
D/mm	B/mm	L/mm	Item No.	Price

5	23	65	491 036	12.50
---	----	----	---------	-------

Chamfer/Edge trimming bits

HW

with ball bearing guide, dia. 18 mm



					
D/mm	B/mm	L/mm	α	Item No.	Price

24	11	54	45°	491 026	32.50
----	----	----	-----	---------	-------

Tongue and groove bit

HW

for glued joints in wood up to 1.10" (28 mm) thick


					
					
D/mm	B/mm	L/mm	T/mm	Item No.	Price

34	32	62	6	491 034	73.50
----	----	----	---	---------	-------

Rebating cutter

HW

with reversible carbide tips

				
D/mm	B/mm	L/mm	Item No.	Price


38	12	53.7	491 085	95.50
----	----	------	---------	-------

491 391	4 Reversible cutters (repl.) for 491 085				34.00
---------	--	--	--	--	-------

Rabbit bits

HW

With ball bearing guide, dia. 12.7 mm

				
D/mm	B/mm	L/mm	Item No.	Price


31.7	12.7	54	491 022	41.00
------	------	----	---------	-------

491 406	Bearing set (repl.) for 491 022	46.50
1 ea. 9.5 mm, 12.7 mm, 16 mm, 19 mm, 22 mm		

Spiral bits

HSS

HW



Model	D/mm	B/mm	L/mm	Item No.	Price
-------	------	------	------	----------	-------


HW	4	10	45	490 977	41.00
HSS	6	16	50	490 944 ¹⁾	21.00
HW	6	16	50	490 978 ¹⁾	44.00
HSS	8	19	50	490 945	16.00
HW	8	25	55	490 979	46.00
HSS	10	30	60	490 946 ²⁾	23.00
HW	10	30	60	490 980 ²⁾	53.50
HSS	12	20	52	490 947	20.00
HSS	14	20	52	490 948	22.00
HSS	16	20	52	490 949	24.00
HSS	18	25	57	490 950	28.50
HSS	20	25	57	490 951	29.50

¹⁾ for use with VS 600 FZ 6

²⁾ for use with VS 600 FZ 10

Laminate slot cutter



HW

				
D/mm	B/mm	L/mm	Item No.	Price

40	2.8	47.5	491 063	59.00
----	-----	------	---------	-------

Dovetail bits

HW

					
					
D/mm	B/mm	L/mm	α	Item No.	Price

14.3	13.5	46	15°	490 990	28.00
------	------	----	-----	---------	-------

14.3	13.5	46	15°	490 992 ¹⁾	25.00
------	------	----	-----	-----------------------	-------

14.3	16	50	10°	491 164 ²⁾	27.00
------	----	----	-----	-----------------------	-------

20	17	46	15°	490 996 ³⁾	30.00
----	----	----	-----	-----------------------	-------

20	26	58	10°	491 165 ⁴⁾	38.00
----	----	----	-----	-----------------------	-------

¹⁾ for use with VS 600 SZ 14



²⁾ for use with VS 600 SZO 14

³⁾ for use with VS 600 SZ 20

⁴⁾ for use with VS 600 SZO 20

Dovetail bits

HSS

					
					
D/mm	B/mm	L/mm	α	Item No.	Price

14.3	13.5	46	15°	490 988 ¹⁾	21.00
------	------	----	-----	-----------------------	-------

14.3	13.5	46	15°	490 991 ¹⁾	17.00
------	------	----	-----	-----------------------	-------


20	17	49	15°	490 995 ²⁾	25.00
----	----	----	-----	-----------------------	-------

¹⁾ for use with VS 600 SZ 14

²⁾ for use with VS 600 SZ 20

Panel cutter bit

HW

				
D/mm	B/mm	L/mm	Item No.	Price

8	19	65	491 037	22.00
---	----	----	---------	-------

HW Duro-Form reversible cutters

Shank bits, shank dia. 8 mm

Extra-long service life and ultra-high precision

HW Duro-Form groove and edge-trimming bits with reversible carbide bits are ideal when you need long service life, high economy and consistent precision.

The difference between carbide-tipped Duro-Form tools and conventional carbide-tipped bits is as follows:


- Re-sharpening the blunt blades of conventional bits not only costs time and money but also reduces the diameter of the bit. This is not a problem with carbide-tipped Duro-Form bits.
- Fast replacement of bits means sharp tools are readily available at all times.
- Guaranteed constant bit diameter, thanks to replaceable bits.
- Lower costs after purchase. One reversible bit lasts as long as two to four conventional bits and is thus extremely economical.
- The very hard-wearing reversible bits are exceptionally efficient, which means less cutting pressure is required and work is easier.



Straight bits

HW

single-edged Z 1



Type	D/mm	B/mm	L/mm	Item No.	Price
------	------	------	------	----------	-------

① HW D 8/20 WP Z1	8	20	50	491 078	98.50
② HW D10/25 WP Z1 ¹⁾	10	25	55	491 079	101.00
③ HW D12/30 WP Z1	12	30	61	491 080	104.00


For grooving, jointing, and rebating in panel materials, wood sandwich boards, and solid wood.

¹⁾ Ideal for use with the Festool jointing system VS 600 FZ 10 for slotted joints.

Straight plunge bit

HW

with peripheral and base cutters; Z 1 + 1



Type	D/mm	B/mm	L/mm	Item No.	Price
------	------	------	------	----------	-------


④ HW D16/30 WP Z1+1	16	30	65	491 081	85.00
---------------------	----	----	----	---------	-------

For plunge cutting, grooving, and jointing in rough, veneered or plastic laminated materials, wood sandwich boards and solid wood.

Flush trim bit

HW

with peripheral and base cutters; Z 1 + 1




Type	D/mm	NL/mm	L/mm	Item No.	Price
------	------	-------	------	----------	-------

⑤ HW D19/20 WM Z2K2	19	20	64	491 082	82.00
---------------------	----	----	----	---------	-------

Edge-trimming bit

HW

double cutter face Z 2



Type	D/mm	L/mm	α	Item No.	Price
------	------	------	---	----------	-------

⑥ HW D30.5/45 GR WP Z2	30.5	62	45°	491 084 ¹⁾	87.00
------------------------	------	----	-----	-----------------------	-------

For edging laminated wood materials without copying pin or stop.

Accessories for carbide-tipped Duro-Form reversible bits


Description	For bits No.	Qty.	Type/dimensions mm	Item No.	Price
Reversible cutters for bits	①	4	HW-WP 20 x 4.1 x 1.1	491 386	41.00
	②	4	HW-WP 25 x 5.5 x 1.1	491 387	44.00
	③	4	HW-WP 30 x 5.5 x 1.1	491 388	46.00
	④ G	4	HW-WP 7.5 x 12 x 1.5	491 390	39.00
	④ U	4	HW-WP 30 x 12 x 1.5	491 393	48.50
	⑤	4	HW-WP 20 x 12 x 1.5	491 392	35.50
	⑥	4	HW-WP 12 x 12 x 1.5	491 391	35.50
		G = Base cutter U = Peripheral cutter			
Ball bearing guide	⑤	2	D19	491 385	13.00
	⑥	2	15.88 x 6.35 x 5	491 384	15.00

Bits

Shank dia. 1/2 in

Solid TC spiral groove bits[®] Roughing and finishing


HW



Ø D/mm	NL/mm	L/mm	R	Fα	Item No.	Price
12.7	42	87			492660	120.00

Edge trimming bit with ball bearing, top


HW



Ø D/mm	NL/mm	L/mm	R	Fα	Item No.	Price
28	25	80			492 706	82.00
Spare ball bearing			dia. 28		493 063	19.00

Edge trimming bit and transition cutter with ball bearing


HW



Ø D/mm	NL/mm	L/mm	R	Fα	Item No.	Price
19	25	74		(11°)	492 662	82.00
Spare ball bearing			dia. 19		493 055	14.50
Spare ball bearing			dia. 22/11°		493 056	17.00

Chamfer bit with cutting edge


HW



Ø D/mm	NL/mm	L/mm	R	Fα	Item No.	Price
23	25	66		15°	492 664	82.00

Chamfer bit with ball bearing, top


HW



Ø D/mm	NL/mm	L/mm	R	Fα	Item No.	Price
28	25	80		15°	492 704	87.00
Spare ball bearing			dia. 28		493 063	19.00

Chamfer bit with ball bearing

HW



Ø D/mm	NL/mm	L/mm	R	Fα	Item No.	Price
33.5	25	66		15°	492 666	84.00
Spare ball bearing			dia. 20/15°		493 057	17.00

Chamfer bit undercut with ball bearing

HW



Ø D/mm	NL/mm	L/mm	R	Fα	Item No.	Price
66.5	28	82		30°	492 668	127.00
Spare ball bearing			dia. 28		493 063	19.00

n max.
16,000

Rounding chamfer router with ball bearing

HW



Ø D/mm	NL/mm	L/mm	R	Fα	Item No.	Price
39.5	23.5	74	6.35	30°	492 708	106.00
Spare ball bearing			dia. 39.5		493 064	20.00

Facing bit

HW



Ø D/mm	NL/mm	L/mm	R	Fα	Item No.	Price
52	7.3	60	1.5	3	492 702	79.00

Bits

Shank dia. 1/2 in


Basin bit with ball bearing HW



Ø D/mm	NL/mm	L/mm	R	Fα	Item No.	Price
53	25	81.7	6.35	18°	492 672	125.00
49	25	81.7	6.35	12°	492 673	116.00
45	25	81.7	6.35	6°	492 674	107.00
63	25	81.7	12.7	18°	492 678	166.00
59	25	81.7	12.7	12°	492 679	146.00
56	25	80	12.7	6°	492 680	135.00

Spare ball bearing	dia. 18°	493 059	17.00
Spare ball bearing	dia. 12°	493 060	17.00
Spare ball bearing	dia. 6°	493 061	17.00
n max.	22,000		

Edge-rounding router with ball bearing HW



Ø D/mm	NL/mm	L/mm	R	Fα	Item No.	Price
22	10	59.3	3		492 688	67.00
26	12	61	5		492 689	77.50
28.8	13.4	62	6.35		492 690	72.50
32	15	63	8		492 691	75.50
41.4	19	69	12.7		492 692	80.00
54	25	75	19		492 693	95.50
66.8	31.4	81	25.4		492 694	120.00

Spare ball bearing	dia. 16°	493062	14.50
n max.	22,000		

Chamfer bit undercut with ball bearing HW



Ø D/mm	NL/mm	L/mm	R	Fα	Item No.	Price
44.7	6.35	80	6.35		492 698	92.50
57.4	12.7	80	12.7		492 699	118.00
70	19	80	19		492 700	138.00

Spare ball bearing	dia. 28	493 063	19.00
n max.	22,000		



The superb quality of our routers teams up with the extremely close tolerances of our bits to give you exceptionally smooth results.



VS 600 jointing system and the OF 1010 EQ router – an unbeatable team for producing wooden joints.



Why just hope, when you can know – no problem with the folding template.

The benefits at a glance

Outstanding results

- Versatility, thanks to seven different joint types and a working width of up to 24 1/4" (615 mm).
- Absolute precision, thanks to a matched system of router, template, copying ring, and bit.

No finishing work required

- Results can be checked at any time, thanks to the folding template (patent pending).
- Dowels can be inserted in bases and sides with one setting, thanks to a completely new process.
- Secure and reproducible positioning of the workpiece and the template with a simple clamping system and eccentric memory disk, that allows accurate and repeatable setting.

Significant time savings

- Quick and simple template change.
- Rapid production of carcase joints by simultaneous parallel clamping on the right and left.
- Simple change between joint types by changing the template and setting the new joint type.

Low machine costs and long service life

- The VS 600 and templates are available separately – you buy only what you need, not an entire set.
- Extreme durability backed by our 3-year warranty.

Works with OF 1010 and OF 1400 routers.

Jointing system



Festool has designed a very special system which allows you to process both workpieces in one setting.

Fits first time, every time

Dovetail joints are the hallmark of fine woodworking, but every woodworker knows just how time-consuming it is to get dovetails right. It involves careful calculating and lots of manual chiseling. And even “simple” butted joints with dowels can present challenges. If the edges of the finished piece are going to come out flush, then the dowel on both workpieces must be painstakingly accurate.

All this work can either be done laboriously by hand, expensively on industrial machinery, or quickly and easily using the VS 600. All you need to do is clamp the template in the jig, place the workpiece against the swivel stop, clamp it, fine-adjust with the eccentric memory ring, and route. It’s unbelievably fast, and unbelievably accurate – joint after perfectly-fitting joint. You can make dowel joints and high-value dovetail and box joints in a fraction of the time.



The swiveling segment of the VS 600 jointing system.



Seven templates, four different joint types, one system – the VS 600 with the OF 1010 EQ router.

The whole is greater than the sum of the parts

At Festool, we always think in terms of systems. The idea is to do as many applications as possible using as few components as possible, to save overall tool costs and use shop resources most efficiently. Each component must be superior on its own terms, and together they must offer advantages you can get nowhere else.


The VS 600 jointing system used with our router and dust extractor offers exactly this benefit – the OF 1010 EQ is one of the best routers available anywhere, and you can use our quiet and effective CT dust extractors throughout the shop and off-site. Add the VS 600 jointing system, and you have a fast, efficient, and clean-working machine for turning out high-quality joints. Your overall output is higher, and your shop can make more money.



VS 600 jointing system

For exact joints. For use with OF 1010/OF 1000/OF 1400

Jointing systems



No.	Description and application	Type	Item No.	Price
1	VS 600 jointing system for professional joints in hard and softwood. • bits and templates sold separately Extra knob for VS 600	VS 600 GE	488 876	299.00
			490 560	11.50
2	SZ 14 dovetail joint unit for half-blind dovetail joints, slot size 9/16" (14 mm) workpiece thickness: 5/8" - 25/32" (16 - 20 mm) Includes copy ring d 17 mm for OF 1010 Copy ring for OF 1400 sold separately • bits sold separately Dovetail bit HSS Dovetail bit HW	VS 600 SZ 14	488 877	61.00
		HS D14.3/13.5/46/15°	490 991	17.00
		HW D14.3/13.5/46/15°	490 992	25.00
3	SZ 20 dovetail joint unit for half-blind dovetail joints, slot size 25/32" (20 mm) workpiece thickness: 26/32" - 1 3/32" (21 - 28 mm) Includes copy ring d 24 mm for OF 1010 Copy ring for OF 1400 sold separately • bits sold separately Dovetail bit HSS Dovetail bit HW	VS 600 SZ 20	488 878	61.00
		HS D20/17/49/15°	490 995	25.00
		HW D20/17/49/15°	490 996	30.00
4	FZ 6 box joint unit for box joints, slot size 1/4" (6 mm) workpiece thickness: 1/4" - 3/8" (6 - 10 mm) Includes copy ring d 8.5 mm for OF 1010 Copy ring for OF 1400 sold separately • bits sold separately Spiral groove bit HSS Spiral groove bit HW	VS 600 FZ 6	488 879	61.00
		HS SPI D6/16/50	490 944	21.00
		HW SPI D6/16/50	490 978	44.00
5	FZ 10 box joint unit for box joints, slot size 3/8" (10 mm) workpiece thickness: 3/8" - 1 3/32" (10 - 28 mm) Includes copy ring d 13.8 mm for OF 1010 Copy ring for OF 1400 sold separately • bits sold separately Spiral groove bit HSS Spiral groove bit HW	VS 600 FZ 10	488 880	61.00
		HS SPI D10/30/60	490 946	23.00
		HW SPI D10/30/60	490 980	53.50
6	DS 32 dowel joint unit for dowel joints in a 32 mm grid (Euro-hole) Includes copy ring d 13.8 mm for OF 1010 Copy ring for OF 1400 sold separately • bits sold separately	VS 600 DS 32	488 881	61.00
7	Template kit SZO 14 (Includes 2 templates) for through dovetail joints, slot size 17/32" (14 mm) workpiece thickness: 15/32" - 21/32" (12 - 17 mm) Includes copy ring d 17 mm for OF 1010 Copy ring for OF 1400 sold separately • bits sold separately, both bits listed below needed Dovetail bit HW Spiral groove bit HW	VS 600 SZO 14	491 152	109.00
		HW D14.3/16/50/10°	491 164	27.00
		HW D6/16/50	490 978	44.00
8	Template kit SZO 20 (Includes 2 templates) for through dovetail joints, slot size 25/32" (20 mm) workpiece thickness: 21/32" - 1" (17 - 25 mm) Includes copy ring d 24 mm for OF 1010 Copy ring for OF 1400 sold separately • bits sold separately, both bits listed below needed Dovetail bit HW Spiral groove bit HW	VS 600 SZO 20	491 153	109.00
		HW D20/26/10°	491 165	38.00
		HW D10/30/60	490 980	53.50



There's no longer any need for tiresome finishing work, because the HL 850 E doesn't leave a lip.

Breathe life into dead spots

Using an electric planer right up to the edge or on rebates often produces unsatisfactory results, as the machine leaves a lip that has to be removed by hand – unless you have the Festool HL 850 E planer.

The HL 850 E lets you work in dead spots because it can plane across the entire width of the rebate.

The one-sided head support makes this possible. It means that the planer head is flush with the other side of the planer casing.

It's also safe. The side guard swings up as the rebate depth increases. Planing up to the edge in deep rebates is no longer a problem.



The benefits at a glance

Outstanding results

- High surface quality, thanks to the unique spiral blade with a drawing cut.
- Texturing and finishing using the special planer heads.

No finishing work required

- No limit to the depth of rebates, and planing up to the edge, thanks to the planer head mounted on one side.
- Precise material removal, thanks to infinitely adjustable cutting depth of up to 9/64" (3.5 mm).
- Planing is matched to the material by the MMC electronics, which keep the cutting speed constant.

Significant time savings

- Fast and easy head replacement, thanks to the unique patented head support.
- Faster and simpler changing of the spiral blade.
- No need to clean up afterwards, thanks to the chip extraction port, which can be placed on the left or right.

Health

- Massive noise reduction, thanks to the true-running spiral blade which makes a drawing cut.

Long service life

- The smooth start-up and speed control protect the motor.
- Extreme durability backed by our 3-year warranty.

Planer HL 850 E



3 15/64" (82 mm) planing width, unlimited rebate depth. Only with the Festool HL 850 E.

Smooth going

The HL 850 E planer is equipped with the unique spiral blade. Because the blade is drawn across the workpiece at an angle and cuts more gently into the workpiece, it produces less noise and an absolutely smooth surface.

Since the planer head has only one blade, blade changing is faster – it takes less than a minute. No blade adjustment is necessary.

With many planers, the chip ejection unit is on the wrong side and in the way 50% of the time. Luckily, Festool engineers understand the problems of day-to-day work, and come up with solutions. The chip ejection unit and the chip extraction port switch between left and right to suit the job at hand. There's no longer any need to lose time cleaning up afterwards.



All the main functions are available to you without having to change the position of the handle or your hands.

Easy control


The 90° V-shaped groove in the sole-plate of the HL 850 E planer prevents the planer from slipping or running out when chamfering boards and beams. For reliable and precisely contoured chamfering, simply set the planer on the workpiece and away you go.

The infinitely adjustable cutting depth is another instance of Festool's careful design. You can correct the cutting depth from 0" to 9/64" while planing, without lifting the planer off the workpiece, and without taking your hands off the handle.

Add some texture

Different textures can bring life and beauty to surfaces. All you have to do is change the planer head. Our three "rustic" planer heads are perfect for giving wood a rough-hewn look.

Planer



HL 850 E
Includes:
• Parallel guide
• Rebate depth guide
• In Systainer 3
Item No. 574 539Price \$430.00
See page 5 for package savings.

HL 850 E

- A unique planer, very quiet and very fast. Change cutting depth with the planer running. Always a clear view of the rebate edge. Create distressed or rough-hewn effects with accessory heads, or convert into a bench-mounted planer with optional bench unit.
- Planer head is mounted on one side for unlimited rebate depth and planing up to the edge
 - Single spiral carbide blade requires no adjustment of cutting circle diameter and planer head
 - The fastest blade change – takes only 60 seconds!
 - Long plate at front and rear
 - Lockable planing depth adjuster
- V-groove in shoe for corner beveling
 - Pivoted chip deflector and dust extraction port mounts on left or right side
 - Smooth run-up and constant cutting speed even at maximum cutting depth thanks to electronics with controlled smooth start-up and constant speed under load


Power consumption	850 watts/7 amp 120 volts AC
Drive shaft speed	10,000 rpm
Cutting depth	0 - 9/64" (0 - 3.5 mm)
Rebating depth	unlimited
Head width	3 15/64" (82 mm)
Noise level at idle	79 dB(A)
Weight	8.6 lbs. (3.9 kg)

(Metric dimensions binding)

Accessories for planer HL 850 E

Planer heads and blades – super-fast changing

Planer heads and blades




No.	Description	Type	Item No.	Price
Planer heads for HL 850 E				
1	Standard (smooth) with carbide-tipped spiral blade HM 82 SD	HK 82 SD	484 520	102.00
2	Rustic, fine with HSS spiral blade HS 82 RF	HK 82 RF	484 521	114.00
3	Rustic, coarse with HSS spiral blade HS 82 RG	HK 82 RG	484 522	114.00
4	Rustic, undulating with HSS spiral blade HS 82 RW	HK 82 RW	485 331	114.00
Spiral blades for quick and easy changing				
5	Carbide-tipped design for planer head HK 82 SD	HW 82 SD	484 515	22.00
6	HSS Rustic, fine for planer head HK 82 RF	HS 82 RF	484 518	24.00
7	HSS Rustic, coarse for planer head HK 82 RG	HS 82 RG	484 519	24.00
8	HSS Rustic, undulating for planer head HK 82 RW	HS 82 RW	485 332	25.00

Rustic effects with the HL 850 E planer

Unique flexibility for all kinds of finishes
When you want to produce not smooth surfaces but distressed or rough-hewn effects, simply replace the standard planer head with a “rustic” head. This offers many ways of decorating surfaces with different textures.


- a Rustic fine
- b Rustic coarse
- c Rustic undulating



Accessories for planer HL 850 E

Bench unit for extra safety

Bench unit



No.	Description	Type	Item No.	Price
1	Bench unit (without planer) for bench-mounted truing and rebating, pivoted protective cover, profile plate with non-slip covering including scale for cutting depth setting	SE-HL	485 017	75.50
2	Clamps – all-steel to secure bench-mounted device. Clamping width 4 1/4" (120 mm) Pack of 2	FSZ 120/2	489 570	31.50
3	Angle stop for HL 850 E for planing at angles of 0° - 45° Stop area 13 3/4" x 3" (350 x 75 mm)	WA-HL	485 018	71.50


Using the bench unit with the HL 850 E planer

If you work frequently with smaller workpieces, it is sometimes easier to use the planer as a stationary planer. This frees up both of your hands for guiding the workpiece. The HL 850 E is easy to convert – simply secure the planer in the SE-HL stationary unit and away you go.

You can also attach the WA-HL angle stop to the stationary unit to give you a valuable tool for creating precise chamfers of any angle from 45° to 90°. The large support helps you guide workpieces securely.



Other accessories



No.	Description	Type	Item No.	Price
4	Parallel stop for side guidance, adjustable from 0 - 3 15/64" (0 - 82 mm) (replacement part)	PA-HL	484 513	13.50
5	Rebate depth stop for rebate depths of 0 - 1 3/16" (0 - 30 mm) (replacement part)	FA-HL	484 512	7.50
6	Chip collection bag with suction adapter	SB-HL	484 509	41.00
7	Suction adapter for SB-HL (not shown) for chip collecting bag and suction hose with bushing recommended D36 hose, item no. 452 882 or 452 881 (replacement part)	AD-HL	484 507	10.50

Sanders



We supply the software as well as the hardware

There are two main factors involved in getting perfect sanding results. First, the tool and the abrasive must meet the highest standards in terms of quality and reliability. Second, they must be compatible. This is why you should reach for Festool abrasives as well as a Festool sander.



Festool sanders for sanding without limits

Festool offers professionals the perfect sanding technology for all situations. For sanding profiles, corners, edges, and surfaces. For careful, light, surface sanding. For the rapid stripping of old coatings. For coarse and fine sanding. For the best surface quality. And of course, Festool provides the optimum abrasives and accessories for all situations too. Festool provides professionals with solutions that give top results with low effort, perfect handling, and a long service life.

For decades we have been developing and producing sanders which set the standard and give professionals' work the perfect finishing touch. Our most recent development is the Duplex LS 130 EQ. The Duplex is the world's first professional-grade linear sander. It lets you sand profiles and rebates cleanly, easily, quickly, and economically.

Festool sanders set an example when it comes to results, and also where handling and ergonomics are concerned. One thing that sets Festool sanders apart is their extremely low vibration levels. This not only increases the precision of your work and the durability of the machine components, but also helps protect your joints.

Sanders

LS 130 EQ



RO 125 FEQ and RO 150 E



ETS 150/3 EQ and ETS 150/5 EQ



ES 125 EQ



RAS 115.04 E



DS 400 EQ



RS 400 EQ



RS 2 E



DX 93 E









Festool has the right sander for just about any need.

Which Festool sander should you use?

Your goal	Our solution	Features
Sanding profiles, corners, edges and rebates	The linear sander for all profiles. The Duplex is a totally new innovation for applications which require a reciprocating sanding motion.	
	Duplex LS 130 EQ	has a linear sanding motion, and sands lengthwise only. Interchangeable pads make it ideal for edges, profiles, and rebates.
Light surface sanding	Orbital sanders for detail work. Festool's first choice for awkward objects, hard-to-reach corners, and small areas.	
	RS 400 EQ	is particularly light and fits the hand well (for true one-handed operation). It is used mainly for sanding small areas and edges, and vertical sanding.
	DS 400 EQ	is particularly compact and light and can be comfortably operated with one hand. Its pointed pad makes it ideal for small areas and corners, vertical or horizontal.
	RS 2 E	is compact, has a good grip, and is also powerful – to deal with larger areas.
Achieving the best surface quality	Festool's random orbital sanders for fine and super-fine finishing, and for prepping surfaces for painting.	
	ETS 150/3 EQ	is the professional 6" sander for fine sanding and finishing. Its small sanding stroke and low weight make it perfect for delicate sanding on veneers and similar materials.
	ETS 150/5 EQ	gives great intermediate sanding results, thanks to its large sanding stroke.
	ES 125 EQ	is particularly compact and lightweight and can be comfortably operated with one hand. Mainly used for small overhead and vertical areas, or as an all-around 5" shop sander.
Coarse and fine sanding and polishing	The flexible all-rounder. The dual-mode random orbital sander for a very high rate of stock removal, smooth surface finishing, and polishing.	
	Rotex RO 150 E	is three 6" tools in one. It is a powerful coarse sander, fine sander, and polisher.
	Rotex RO 125 FEQ	is three 5" tools in one. It is a powerful coarse sander, fine sander, and polisher.
Rapid stripping of old coatings	Festool orbital sander for coarse sanding with fast stock removal	
	Deltex DX 93 E	offers a high stock removal capacity and is suitable for corners and edges as well as for smaller areas.
	RAS 115.04 E	a 4.5" sander with high torque and optimum speed for controlled stripping and prepping of surfaces.

Festool has developed six special, high performance abrasives for specific sanding tasks and materials.

Abrasive type	Application	Abrasive type	Application	Abrasive type	Application
Brilliant 2	Special abrasives for paints and varnishes. Preliminary, intermediate and final sanding for painters, joiners, furniture makers and interior fitters.	Rubin	Special abrasives for wood materials. Preliminary and intermediate sanding for joiners, carpenters and painters in the woodworking and furniture industries.	Titan 2	Special abrasives for repair compounds, fillers, and paint. Preliminary, intermediate and final sanding in paint shops and automotive repair workshops.
					
Saphir	Special abrasives for heavy-duty use under particularly tough conditions.	Vlies	Special fleece abrasives for light sanding, roughening, cleaning, degreasing, and matting.	Platin 2	Platin abrasives are specially designed for super-finishing surfaces without damaging the surface structure.
					

Sanders

ROTEX® – Random orbital sanders that do it all




The Rotex switches from rotary to random orbital motion to cover all types of sanding.

ROTEX – three tools in one

The dual-mode Rotex gives you the choice of two sanding motions – random orbital for fine sanding, and Rotex rotary/random orbital motion for fast material removal in rough sanding or for polishing. You can switch between modes in seconds by simply turning a knob. You no longer need to change to another tool.

This saves you time and the cost of a second sander.



The benefits at a glance

Superb versatility

- Dual-mode – Random orbital and gear-driven rotary orbital motion, for rough sanding, fine sanding, and polishing, all with one sander.
- Infinitely variable speed for any application.

Better results in less time

- Simple switching from rough to fine sanding.
- Fast coverage of large surfaces, thanks to continuous untiring operation.
- Reduction gear for high torque and fast material removal.
- No unnecessary reworking – the sanding pad brake prevents scratching when placing the sander on a surface or picking it up.

Great handling

- Dust extraction port at the rear and out of the way.
- Low weight and ergonomic design for an easier hold in any position.
- Vibration-Stop balancing reduces vibration and helps you work longer without tiring.
- “StickFix” hook-and-loop abrasive mounting for fast, easy grit changes.

Lower costs

- Initial costs minimized since the Rotex represents three tools in one.
- Patented Jetstream pad design prevents dust buildup on the abrasive, for cleaner work and up to 30% longer abrasive life.
- Sealed bearings for long service life.
- Long-life MPE sanding pad.
- Extreme durability backed by our 3-year warranty.

Sanders

ROTEX® – all the performance in a smaller, lighter package



Everything Rotex has to offer in a smaller, lighter package

The new RO 125 puts dual-mode, triple-function performance into a handy, 4.4 pounds. This 5" sander does it all – coarse sanding, fine sanding, and polishing. It's perfect for woodworkers, painters, solid surface fabricators, and anyone who needs to sand in a variety of places and positions. With near-total dust extraction, exceptional ergonomics, and many advanced features, this is a small sander that does a very big job.



Toolless pad change – to change the pad, you just screw it on and off with your hands.

The benefits at a glance

"World's first" capabilities

- The only 5" dual mode sander available.
- The only tool-free pad change on the market.

Rotex versatility

- Dual-mode, triple function for fast stock removal, smooth fine sanding, and polishing.
- Infinitely variable speed for any application.

Better results in less time

- Simple switching from rough to fine sanding.
- Fast coverage of large surfaces, thanks to continuous untiring operation.
- Reduction gear for high torque and fast material removal.
- No unnecessary reworking – the sanding pad brake prevents scratching when placing the sander on a surface or picking it up.

Great handling

- Dust extraction port at the rear and out of the way.
- Low weight and ergonomic design for an easier hold in any position.
- Vibration-Stop balancing reduces vibration and helps you work longer without tiring.
- "StickFix" hook-and-loop abrasive mounting for fast, easy grit changes.

Lower costs

- Initial costs minimized since the Rotex represents three tools in one.
- Patented Jetstream pad design prevents dust buildup on the abrasive, for cleaner work and up to 30% longer abrasive life.
- Sealed bearings for long service life.
- Long-life MPE sanding pad.
- Extreme durability backed by our 3-year warranty.

Sanders

Random orbital sanders – the fine art of sanding



Whether you're working on vertical surfaces or overhead, Festool random orbital sanders are just what you need.



The extremely ergonomic design with integrated extraction channel makes working a pleasure.

Ready for anything

With Festool random orbital sanders, you're ready for anything, with power, performance, and flexibility.

High performance, low weight – the ETS 150 6" sander is a full-featured tool for professionals who need superior results. At just 4 lbs. it is among the lightest sanders in its class, yet packs the power to get the job done fast. The ETS 150 comes with either a 1/8" stroke for fine finishing or 3/16" stroke for intermediate sanding.

Unlike many 6" sanders, this is not just a 5" chassis with a larger pad – the ETS 150 is a purpose-built 6" machine with full-sized performance and a 310 watt motor. It's a balanced, smooth-running tool for tireless working and outstanding finish quality.



The benefits at a glance

Outstanding results

- Super-fine surface finish, thanks to precise guidance and excellent ergonomics.
- Work on all types of materials, thanks to speed control.

Significant time savings

- Untiring, thanks to its low weight.
- No necessary reworking – the sanding pad brake prevents grooves from forming when the sanding pad makes contact with the surface.

Long service life


- MPE sanding pad for extremely long service life.
- Long service life of the abrasives, thanks to the patented Jetstream sanding pad.
- Plug it concept rules out downtime from cord breakage.
- Extreme durability backed by our 3-year warranty.

Health

- Optimum dust extraction provides a clear view and a healthier working environment.
- Less tiring and easier on joints, thanks to the ergonomic handle shape and VS balancing.

6" sanders

Rotex® 6" dual-mode sander



RO 150 E
Includes:
• StickFix sanding pad (150 soft)
• 1 abrasive sheet • Removable handle
• In Systainer 2
Item No. 571 494Price ~~\$420.00~~ **Closeout Price \$350.00**
See page 5 for package savings.

RO 150 E

If you need fast material removal plus smooth fine sanding, but only want to buy one tool, the Rotex is for you. It switches instantly from random orbital sanding motion to the Rotex rotary random orbital motion, to cover rough sanding, fine sanding, and polishing. (Sheepskin, felt, and sponge accessories are available.)

New RO 150 FEQ Coming Summer 2006

- Rough sander, fine sander and polisher in one
- Optimum dust extraction through patented Jetstream principle
- Sanding pad brake prevents scratches when placed on or removed from the workpiece
- Stepless electronic control for all applications
- StickFix system for fast abrasives changing
- MMC electronics with constant and controlled speed for high surface quality: smooth start-up and temperature control protect motor and bearings, and ensure a long service life
- Reduction gearing (2-speed) for high torque
- Very smooth running through VS balancing
- Dust extraction port

Power consumption	500 watts/4.2 amps 120 v AC
Pad diameter	6" (150 mm)
Speed rotary motion	240 - 560 rpm
Speed eccentric motion	2,000 - 5,600 opm
Sanding stroke	3/16" (5mm)
Weight	5 lbs. (2.3 kg)

(Metric dimensions binding)


Rotex® and Dust Extractor Packages

Rotex®

Rotex®, CT 22 E dust extractor with hose
Package price \$769.50
Price up to \$830.00 if purchased separately
Save up to \$85.50
Item No. P2571 494
See page 5 for more package savings.

CT 22 E Dust Extractor

6" random orbital sanders



ETS 150/3 EQ or ETS 150/5 EQ
Each includes:
• StickFix sanding pad (150 soft)
• 1 abrasive sheet • Filter cartridge
• In Systainer 3
ETS 150/3 Item No. 571 540Price \$255.00
ETS 150/5 Item No. 571 541Price \$255.00
See page 5 for package savings.

ETS 150/3 EQ and ETS 150/5 EQ

The right tool for the job. The ETS 150/3 has a short 1/8" stroke for fine finish work. The ETS 150/5 has a 3/16" stroke for intermediate sanding and fast stock removal. Both versions are balanced for their specific stroke, for smooth, low-vibration working.

- Optimum dust extraction through patented Jetstream principle
- Turbo dust extraction
- Sanding pad brake prevents scratches when placed on or removed from the workpiece
- Stepless electronic control for various uses
- StickFix system for fast abrasives changing
- Encapsulated bearing for long service life
- Very smooth running through VS balancing
- Dust extraction port

	ETS 150/3 EQ	ETS 150/5 EQ
Power consumption	310 watts/2.6 amps 120 v AC	310 watts/2.6 amps 120 v AC
Pad diameter	6" (150 mm)	6" (150 mm)
Speed	6,000 - 10,500 opm	6,000 - 10,500 opm
Sanding Stroke	1/8" (3 mm)	3/16" (5 mm)
Weight	4 lbs. (1.8 kg)	4 lbs. (1.8 kg)

(Metric dimensions binding)

Jetstream Principle



With Jetstream



Without Jetstream



Up to 30% longer service life with Jetstream

In the patented Jetstream system, air flowing out through an additional hole in the center of the sanding pad prevents a vacuum from forming between the abrasive and the workpiece. This significantly improves dust extraction, the sanding dust can be removed unhindered, and the abrasive is used more evenly.

Even with fine grits, the Jetstream effect gives up to 30% longer service life of the abrasive.

Superfast changing of abrasives with StickFix

The StickFix system works on the hook-and-loop principle. Mushroom-shaped hooks on sanding pads and hard-wearing velvet fabric on the abrasive material form a secure, non-slip bond which can still be easily released

when desired. Simply lay StickFix abrasives in place, and you're ready to work!

MPE sanding pad: lasts 5 times longer than conventional sanding pads

Only Festool offers you sanding pads of hard wearing MPE. Compared to cold molded foams, MPE (microcellular polyurethane elastomer) has five times the tear resistance – and thus lasts up to five times

longer. This means less wear and lower costs. Furthermore, MPE is produced without CFC's which damage the ozone layer.

More efficient sanding with Jetstream and StickFix

Festool offers a complete solution for faster sanding, lower costs, and better results.



Abrasives last considerably longer if the Festool Jetstream principle is used. Most Festool sanders use this technology.







Abrasives for 6" sanders

StickFix abrasive sheets



StickFix abrasive sheets
dia. 6" (150 mm) / 9 hole
for RO 150 E and ETS 150 EQ




	Grit	Qty	Item No.	Price	Grit	Qty	Item No.	Price
Brilliant 2  For paints and varnishes	P 40	5	492 975	3.00	P 120	100	492 983	34.50
	P 120	5	492 976	3.00	P 150	100	492 984	33.50
	P 180	5	492 977	3.00	P 180	100	492 985	33.50
	P 320	5	492 978	2.00	P 220	100	492 986	33.50
	P 40	50	492 979	24.00	P 240	100	492 987	33.50
	P 60	50	492 980	20.50	P 320	100	492 988	33.50
	P 80	50	492 981	18.50	P 400	100	492 989	33.50
	P 100	100	492 982	34.50				
Rubin  For bare wood	P 50	5	489 482	3.00	P 50	50	486 394	25.00
	P 80	5	484 107	3.00	P 80	50	486 395	20.50
	P 100	5	489 483	3.00	P 100	50	486 396	20.50
	P 120	5	489 484	3.00	P 120	50	486 397	19.50
	P 24	50	486 392	32.50	P 150	50	486 398	19.50
	P 36	50	486 393	29.00	P 180	50	486 399	19.50
Titan 2  For solid surface and automotive	P 40	50	493 663	22.50	P 280	100	492 342	39.00
	P 60	50	493 664	22.50	P 320	100	492 343	39.00
	P 80	50	492 335	22.50	P 360	100	492 344	39.00
	P 100	100	492 336	39.00	P 400	100	492 345	39.00
	P 120	100	492 337	39.00	P 500	100	492 346	39.00
	P 150	100	492 338	39.00	P 800	100	492 347	45.50
	P 180	100	492 339	39.00	P 1200 ¹⁾	100	492 348	46.50
	P 220	100	492 340	39.00	P 1500 ¹⁾	100	492 349	48.50
	P 240	100	492 341	39.00				
Saphir  For heavy duty use	P 24	5	484 105	5.50	P 50	25	486 390	21.50
	P 24	25	486 388	26.00	P 80	25	486 391	18.50
	P 36	25	486 389	25.00				
Vlies  For light sanding and degreasing	A 100 ¹⁾	5	482 778	6.50	A 800 ¹⁾	5	482 780	6.50
	A 280 ¹⁾	5	482 779	6.50				
Platin 2  For superfinish	S 400 ¹⁾	15	492 368	45.50	S 2000 ¹⁾	15	492 371	45.50
	S 500 ¹⁾	15	492 369	45.50	S 4000 ¹⁾	15	492 372	45.50
	S 1000 ¹⁾	15	492 370	45.50				

¹⁾unperforated

Accessories for 6" Festool sanders

Complete from paint care set to filter

Polishing accessories



No.	Description and application	Type	Item No.	Price
PoliStick system with StickFix				
1	Polishing pad to accept polishing accessories	STF 150/M8-P	485 748	17.50
2	Coarse sponge for polishing heavily weathered surfaces (preparation for painting)	STF D 150 coarse sponge		
		1 piece 20 mm high	488 345	10.50
		5 pieces 20 mm high	488 346	42.00
		5 pieces 30 mm high	489 404	49.50
3	Fine sponge for polishing lightly weathered paint (paint maintenance)	STF D 150 fine sponge		
		1 piece 20 mm high	488 343	10.50
		5 pieces 20 mm high	488 344	41.00
		5 pieces 30 mm high	489 403	41.00
		Fine sponge, honeycombed		
		5 pieces 20 mm high	489 115	41.00
		5 pieces 30 mm high	489 405	43.00
4	Soft felt for pre-polishing new paints and plastics	STF D 150 soft felt		
		1 piece	485 972	6.50
		5 pieces	488 347	22.50
5	Hard felt for polishing new paints and plastics	STF D 150 hard felt		
		1 piece	485 970	6.50
		5 pieces	488 348	24.00
6	Sheepskin for high-gloss polishing	STF D 150 sheepskin	484 131	10.50
7	Paint maintenance set (not shown) 1 polishing pad 1 fine sponge	STF D 150 set PT-STF-D 150-178 PT-STF-D 150-20F	485 981 485 748 488 343	25.00 17.50 10.50


Accessories



No.	Description and application	Type	Item No.	Price
8	Turbo dust bags Paper dust bags for turbo dust extraction pack of 5 pack of 25	TF II-ET/RS TF II-ET/RS/25	487 779 487 871	5.50 25.00
9	Turbo dust bag set Paper dust bags for turbo dust extraction and one plastic holder	TFS-ES 150	489 631	15.00
10	Additional hand grip (Rotex RO 150 and RAS 115)	ZG-RO	487 865	5.50
11	Plug-it power cord, 13' (replacement)	SJO 2 x 18 AWG	490 649	29.00

Accessories for 6" sanders

StickFix sanding pads



No.	Description and application	Type	Item No.	Price
1	StickFix sanding pad dia. 6" (150 mm)/9 supersoft	STF D 150/M8 sw ZB STF D 150/M8 w ZB STF D 150/M8 h ZB STF D 150/M8 w HT	486 382	31.50
2	dia. 6" (150 mm)/9 soft		486 381	31.50
3	dia. 6" (150 mm)/9 hard		484 850	31.50
4	dia. 6" (150 mm)/9 soft, Longlife		491 935	31.50
5	Interface pad for superfine abrasive dia. 5 11/16" (145 mm)/9 soft clamping element between abrasive and sanding pad		492 212	14.50

5" sanders

5" Rotex® dual mode sander



Rotex® RO 125 FEQ

Includes:

- 1 StickFix sanding pad (125mm soft)
- 1 Abrasive sheet
- Plug-it cable
- In Systainer 2

Item No. 571 536Price \$350.00

See page 5 for package savings.

Rotex® RO 125 FEQ

If you need fast material removal plus smooth fine sanding, but only want to buy one small tool, the new Rotex RO 125 is for you. It switches instantly from random orbital sanding motion to the Rotex rotary random orbital motion, to cover rough sanding, fine sanding, and polishing. And, it only weighs 4.4 lbs.


- Rough sander, fine sander and polisher in one

- Toolless pad change – change pads in an instant using only your hands
- Optimum dust extraction through patented Jetstream principle
- Sanding pad brake prevents scratches when placed on or removed from the workpiece
- Stepless electronic control for all applications
- StickFix system for fast abrasives changing
- MMC electronics with constant and controlled speed for high surface quality: smooth start-up and temperature control protect motor and bearings, and ensure a long service life
- Reduction gearing (2-speed) for high torque
- Very smooth running through VS balancing
- Dust extraction port
- Plug-it cord for easy replacement

Power consumption	500 watts/4.2 amps 120 v AC
Pad diameter	5" (125 mm)
Speed, rotary motion	300 - 600 rpm
Speed, eccentric motion	3000 - 6000 rpm
Sanding stroke	9/64" (3.6 mm)
Weight	4.4 lbs. (2 kg)

(Metric dimensions binding)

5" random orbital sander



ES 125 EQ

Includes:

- 1 StickFix sanding pad (125mm soft)
- 1 Abrasive sheet
- Filter cartridge
- In Systainer 2

Item No. 571 568.....Price \$165.00

See page 5 for package savings.

ES 125 EQ

- Circular pad, small, lightweight, and handy for single-handed operation for continuous work on vertical and horizontal surfaces.
- Optimum dust extraction through patented Jetstream principle, abrasives last up to 30% longer
- Turbo dust extraction
- Sanding pad brake prevents scratches when the tool is placed on or removed from the workpiece
- Stepless electronic speed control for various uses
- StickFix system for fast change of abrasives
- Encapsulated bearing for long service life
- Very smooth running through VS balancing
- Edge protection prevents damage to workpiece
- Dust extraction port

Power consumption	220 watts/2 amps 120 v AC
Pad diameter	5" (125 mm)
Speed	6,000 - 13,000 opm
Sanding stroke	3/32" (2.5 mm)
Weight	2.4 lbs. (1.1 kg)

(Metric dimensions binding)

Abrasives for 5" sanders

StickFix abrasive sheets



StickFix abrasive sheets
dia. 5" (125 mm) for RO 125 FEQ
and ES 125 EQ




	Grit	Qty	Item No.	Price	Grit	Qty	Item No.	Price
Brilliant 2  For paints and varnishes	P 120	5	492 953	2.00	P 150	100	492 948	30.00
	P 180	5	492 954	2.00	P 180	100	492 949	30.00
	P 320	5	492 955	2.00	P 220	100	492 950	30.00
	P 40	50	493 657	17.50	P 320	100	492 951	30.00
	P 60	50	492 944	17.50	P 400	100	492 952	30.00
	P 80	50	492 945	17.50				
	P 100	100	492 946	30.00				
	P 120	100	492 947	30.00				
Rubin  For bare wood	P 50	5	493 120	3.00	P 100	50	493 116	17.50
	P 80	5	493 121	3.00	P 120	50	493 117	17.50
	P 100	5	493 122	3.00	P 150	50	493 118	17.50
	P 120	5	493 123	3.00	P 180	50	493 119	17.50
	P 50	50	493 114	21.50				
	P 80	50	493 115	18.50				
Titan 2  For solid surface and automotive	P 80	50	492 966	19.50	P 320	100	492 972	35.50
	P 120	100	492 967	35.50	P 360	100	492 973	35.50
	P 150	100	492 968	35.50	P 400	100	492 974	35.50
	P 180	100	492 969	35.50	P 1200 ¹⁾	100	492 363	35.50
	P 220	100	492 970	35.50	P 1500 ¹⁾	100	492 364	38.00
	P 240	100	492 971	35.50	P 3000 ¹⁾	100	492 365	38.00
Saphir  For heavy duty use	P 24	25	493 124	24.00	P 36	25	493 125	22.50
	P 50	25	493 126	18.50	P 80	25	493 127	16.00
Vlies  For light sanding and degreasing	A 120 ¹⁾	5	488 107	8.50				
	A 280 ¹⁾	5	488 108	8.50				
Platin 2  For superfinish	S 400 ¹⁾	15	492 373	38.00	S 2000 ¹⁾	15	492 376	38.00
	S 500 ¹⁾	15	492 374	38.00	S 4000 ¹⁾	15	492 377	38.00
	S 1000 ¹⁾	15	492 375	38.00				


¹⁾ unperforated

Accessories for 5" Festool sanders

Pads



No.	Description and application	RO 125	ES 125	Type	Item No.	Price
FastFix® sanding pad						
1	Hard (1 per pack)	•		D 125, hard	492 127	24.00
2	Soft (1 per pack)	•		D 125, soft (HT)	492 125	24.00
3	Extra soft (1 per pack)	•		D 125, extra soft	492 126	24.00
4	FastFix® polishing pad (1 per pack)	•		D 125, FX-RO125	492 128	23.00
Stickfix sanding pad (not shown)						
5	Soft (1 per pack)		•	STF-ES 125 SW-HT	492 280	24.00
6	Extra soft (1 per pack)		•	STF-ES 125 SW	492 282	24.00
Felt polishing pad						
7	Hard (5 per pack)	•	•	D 125, hard	493 078	24.00
8	Soft (5 per pack)	•	•	D 125, soft	493 077	23.00
9	Sheepskin (not shown) (5 per pack)	•	•	D 125	493 079	58.00
Polishing sponge (not shown)						
	Course (5 per pack)	•	•	D 125, course	493 082	42.00
	Fine (5 per pack)	•	•	D 125, fine	493 081	33.50
	Fine, waffled (5 per pack)	•	•	D 125, fine, waffled	493 080	34.50
11	Interface pad (1 per pack)	•	•	D 120/90/8	492 271	14.50

Accessories		No. Description and application	Type	Item No.	Price
	1	Turbo dust bags Paper dust bags for turbo dust extraction pack of 5 pack of 25	TF-RS 400/5 TF-RS 400/25	489 128 489 127	5.50 25.00
	2	Turbo dust bag set Paper dust bags for turbo dust extraction and one plastic holder	TFS-ES 150	489 631	15.00
	3	Plug-it power cord, 13' (replacement)	SJO 2 x 18 AWG	490 649	30.50

Sanders

RAS 115 E rotary sander for stripping coatings

Strip it down


The RAS 115 is a light, easily-managed tool, specially designed for stripping coatings fast. Gear reduction gives it high torque and a speed range of 1500-4000 rpm, ideal for fast, controlled stock removal. The lower speed prevents abrasive discs from overheating and clogging, an important consideration for stripping old varnishes and paint layers.



All controls are positioned for easy use. The RAS 115 is well-balanced and easy to hold, with a handle under 2 1/2" thick. It comes with an attachable side handle for vertical use, and weighs only 5 lbs. You can swivel the dust extraction hood as desired by just twisting the side handle, for a good view and optimum dust extraction. A spindle lock permits fast toolless backing pad changes.

Rotary sander

RAS 115.04 E



RAS 115.04 E

Includes:

- Dust extraction hood
- Stickfix sanding pad, soft 4 1/2" (115 mm) dia.
- 8 StickFix abrasive disks
- Extra hand grip • Wrench
- In Systainer 2

Item No. 570 738Price \$295.00

See page 5 for package savings.

The benefits at a glance

Fast stock removal

- High torque to power through material.
- Moderate speed prevents abrasive clogging.

Great controllability

- Light, and handle just 2 1/2" thick for an easy hold.
- Electronic speed control for constant speed, even under load.
- Electronic starting control for jolt-free starts.
- Electronic temperature monitor prevents overheating.

Easy handling

- Dust extraction port at the rear and out of the way.
- Dust extraction hood swivels to catch dust without impeding your view of the workpiece.
- Vibration-Stop balancing reduces vibration for untiring working.
- "StickFix" hook-and-loop abrasive attachment for fast, easy grit changes.
- Spindle lock for toolless backing pad exchange.

Lower costs

- Sealed bearings for longer life.
- Long-life MPE sanding pad.
- Extreme durability backed by our 3-year warranty.

RAS 115.04 E

If you strip coatings and prep surfaces regularly, this is the tool for you. The speed range and torque are ideal for the task, and the extremely efficient dust extraction helps keep the air and the area clean. A swiveling hood enhances dust extraction, while giving you a clear view of the workpiece.

- Optimized for stripping coatings and prepping surfaces
- High torque, moderate speed
- Optimum dust extraction through rear dust extraction port
- Swivelling dust extraction hood for unobstructed view of workpiece
- Electronic speed control for constant speed under load
- VS balancing for smooth running
- StickFix system for fast abrasives changing

Power consumption	500 watts
Rotary speed	1500 - 4000 rpm
Pad diameter	4 1/2" (115 mm)
Shaft thread	M 14
Dust extraction port	Uses Festool D27 suction hose
Weight	5 lbs. (2.3 kg)

(Metric dimensions binding)




Abrasives for RAS 115 E rotary sander

StickFix abrasive sheets




StickFix abrasive sheets
dia. 4 1/2" (115 mm) / 9 hole
for RAS 115.04 E



	Grit	Qty	Item No.	Price	Grit	Qty	Item No.	Price
Saphir 	24	25	484 151	17.50				
	36	25	484 152	16.00				
	50	25	485 245	16.00				
	80	25	485 246	13.00				
For heavy duty use								
Rubin 	24	50	485 914	18.50	120	50	484 161	15.00
	36	50	485 915	18.50	150	50	484 162	15.00
	50	50	484 158	17.50	180	50	484 413	15.00
	80	50	484 159	15.00				
	100	50	484 160	15.00				
For bare wood								
Vlies 	A 80	10	484 165	25.00				
	A 180	10	484 166	27.50				
For light sanding and degreasing								

Accessories for RAS 115 E rotary sander

StickFix sanding pad



No.	Description and application	Type	Item No.	Price
1	FiberFix sanding pad for fiber discs and Longlife fiber discs D 115	2F D115/M14	485 298	21.00
2	StickFix sanding pad, hard hard, high edge strength, for flat surfaces and narrow edges dia. 115 mm, Connecting thread M14	STF D115/M14 H	484 172	18.00
3	StickFix sanding pad, soft	STF D115/M14 W	484 173	18.00
4	Brush insert for RAS 115 with plastic bristles (2 per pack)	AHP-RAS D115/2	484 727	12.00
5	with metal bristles (1 per pack)	AHM-RAS D115	484 728	12.00
6	Additional hand grip	ZG-RO	487 865	5.50

Linear sander

DUPLEX – the new dimension in sanding



Surface finishing can be the most tedious part of a job, but also one of the most important. Power tools speed the task on flat surfaces, but up until now tongue and groove joints, rebates, and profiles have

often left even the best-equipped craftsman with no alternative but a sanding block and elbow grease – and hours of tiring work.

Not any more!

Festool introduces a revolutionary new power tool that makes detail sanding faster, easier, and cleaner. The new linear sander is designed for professional use with the quality and reliability you expect from Festool.

Don't sweat the details.

Rebates, edges, and profiles can only be sanded by a linear motion – not side to side, not circular, not oscillating. Up until now, the only truly professional portable that could do that was your hand. But the linear sander now powers through detail sanding up to three times faster. As common as these jobs are, this means major savings in time – and effort.

LS 130 EQ Linear Sander Duplex



LS 130 EQ

Includes:

- 1 Standard StickFix sanding pad 3 5/32" x 5 1/4" (80 x 133 mm)
- 1 – 90° sanding pad • 2 Abrasive sheets
- Plug it cable • In Systainer 1

Item No. 567 777Price \$290.00

See page 5 for package savings.

LS 130 EQ

- Outstanding results and economic labor saver on rebates and profiles with a working stroke of 5/32" (4 mm) and a sanding surface of 3" x 5"
- The variety of sanding bases and abrasive materials for specific applications ensures a wide range of uses
- Straight linear motion with no impacts against sides of rebates
- Faster than manual sanding – up to three times faster
- Cleaner than manual sanding, with dust extraction port
- Quick, easy and toolless sanding base change using the ingenious FastFix system

Power consumption	260 watts/2.2 amps 120 v AC
Speed	4,000 - 6,000 opm
Sanding stroke	5/32" (4 mm)
Replaceable sanding pad	3 5/32" x 5 1/4" (80 x 133 mm)
Dust extractor connection	1" (27 mm)
Weight	3.94 lbs. (1.7 kg)

(Metric dimensions binding)

Abrasives for LS 130 EQ linear sander

StickFix abrasive sheets



For Linear sander LS 130 EQ
3 5/32" x 5 1/4" (80 x 133 mm)



	Grit	Qty	Item No.	Price	Grit	Qty	Item No.	Price
Brilliant 2 	P 40	10	492 859	3.00	P 120	100	492 852	20.50
	P 80	10	492 860	3.00	P 150	100	492 853	20.50
	P 120	10	492 861	3.00	P 180	100	492 854	20.50
	P 180	10	492 862	3.00	P 220	100	492 855	20.50
	P 40	50	492 848	14.00	P 240	100	492 856	20.50
	P 60	50	492 849	12.00	P 320	100	492 857	20.50
	P 80	50	492 850	11.00	P 400	100	492 858	20.50
	P 100	100	492 851	20.50				
Rubin 	P 50	10	490 393	3.00	P 80	50	490 388	12.00
	P 80	10	490 394	3.00	P100	50	490 389	12.00
	P 100	10	490 395	3.00	P 120	50	490 390	12.00
	P 120	10	490 396	3.00	P 150	50	490 391	12.00
	P 50	50	490 387	14.00	P 180	50	490 392	12.00

For bare wood


Accessories for LS 130 EQ linear sander

LS 130 EQ profile pads



No.	Description and application	Type	Item No.	Price
1	Flat sanding pad standard design	STF-LS130-STD	490 161	23.00
2	90° pad for sanding inside corners	STF-LS130-90	490 162	23.00
3	Radius 6 pad for sanding outside edges	STF-LS130-R6KV	490 163	23.00
4	Radius 10 pad for sanding outside edges	STF-LS130-R10KV	491 197	23.00
5	Radius 18 concave pad for sanding curves	STF-LS130-R18KV	490 164	23.00
6	Radius 25 concave pad for sanding curves	STF-LS130-R25KV	490 165	23.00
7	Radius 10 convex pad for sanding v-grooves with inside radius of 25/64" (10 mm)	STF-LS130-V10	490 166	23.00
8	Radius 25 convex pad for sanding inside radius of 1" (25 mm)	STF-LS130-R25KX	490 167	23.00
9	88° pad for sanding inside corners with a radius of 25/64" (10 mm) (example back-splashes)	STF-LS130-R10KX	491 198	23.00
10	Flat sanding pad long for sanding fittings Dimensions: 3 9/64" x 7 43/64" (80 x 195mm)	SSH-STF-LS130-LL195	491 861	14.50
11	Flat sanding pad wide for sanding lamella on both sides Dimensions: 6 59/64" x 5 7/64" (158 x 130mm)	SSH-STF-LS130-LL130	491 862	19.00
12	Do-It-Yourself kit for creating your own sanding pad to match your custom profiles	STF-LS130-KIT	490 780	37.00
13	Interface pad (not shown)	STF-LS130-8	490 160	11.50

LS 130 EQ scraper



No.	Description and application	Type	Item No.	Price
14	Scraper for stripping carpet, wallpaper, etc.	SSH-LS130-B100	491 199	18.00

Sanders

Direct drive orbital sanders – the precision specialists



The RS 400 EQ is particularly light and handy.

The details make the difference

Festool orbital sanders with direct drive units are used by professional tradesmen who need a good surface finish, especially for light sanding of wood or varnished surfaces. The shape of the sanding pad helps you to get right into the corners, thereby saving on manual finishing.

Festool offers a complete set of orbital sanders with direct drive units. These tools can be used for a wide variety of uses, on both small and large surfaces, for a fine, even sanded surface.



The benefits at a glance

Outstanding results

- The high speed and the direct drive ensure very precise sanding.
- The even sanding surface and the ability to sand close to the edges on three sides means that no reworking is required.
- Infinitely variable speed for a wide range of uses.

Significant time savings

- Fine abrasion and edge protection against damage help to eliminate reworking of corners and other difficult to reach areas.
- Short changeover times, thanks to the StickFix design.

Long service life


- The dustproof encapsulated bearing and the hard wearing MPE sanding pad ensure a long service life, for maximum long-term value.
- Extreme durability backed by our 3-year warranty.

Health

- Very smooth running through Vibration-Stop design — easier on your joints.
- Optimum dust extraction provides a clear view and a healthier working environment.


Orbital sanders

Orbital delta sander



DS 400 EQ
Includes:
• 1 StickFix 4" x 6" (100 x 150 mm) sanding pad
• 1 Abrasive sheet
• Filter cartridge • In Systainer 1
Item No. 567 566Price \$190.00
See page 5 for package savings.

Orbital sander



Includes: RS 400 EQ
• 1 StickFix 3 5/32" x 5 1/4" (80 x 133 mm) sanding pad
• 1 Abrasive sheet • Filter cartridge
• In Systainer 1
Item No. 567 567Price \$190.00
See page 5 for package savings.

Orbital sander



RS 2 E
Includes:
• 1 StickFix 4 1/2" x 9" (115 x 228 mm) sanding pad • 1 Abrasive sheet
• Filter cartridge • In Systainer 2
Item No. 567 669Price \$295.00
See page 5 for package savings.

DS 400 EQ

- Small, light, and handy, ideal for work on vertical surfaces
- Effective on surfaces and in corners
- Encapsulated bearing for long service life
- The specialist for hard-to-reach points such as beads and corners
- Smooth running through VS balancing, easy on joints
- Stepless electronic control for many applications
- Replaceable filter bags
- Dust extraction port

Note: Pads not interchangeable with RS400EQ

Power consumption	200 watts/1.67 amps 120 v AC
Pad size	4" x 6" (100 x 150 mm)
Speed	6,000 - 13,000 opm
Sanding stroke	5/64" (2 mm)
Weight	2.4 lbs. (1.1 kg)

(Metric dimensions binding)

RS 400 EQ

- Small, light, eccentric sander ideal for work on vertical surfaces
- Rectangular sanding pad
- High power on surfaces, in rebates, and on edges
- Encapsulated bearing for long service life
- Sand close to edges for efficient working
- Smooth running through VS balancing, easy on wrists
- Stepless electronic speed control for many applications
- Replaceable filter bags
- Dust extraction port

Note: Pads not interchangeable with DS400EQ

Power consumption	200 watts/1.67 amps 120 v AC
Pad size	3 5/32" x 5 1/4" (80 x 133 mm)
Speed	6,000 - 13,000 opm
Sanding stroke	5/64" (2 mm)
Weight	2.4 lbs. (1.1 kg)

(Metric dimensions binding)

RS 2 E

- The RS 2 E is an economical sander for large areas. Precision fine sanding on large surfaces with the RS 2 E gives high surface quality. Typical applications include intermediate sanding of varnished doors. An ergonomic extra handgrip permits easy guidance with little force to avoid premature fatigue during long sessions.
- Powerful, efficient through fast material removal
 - Extra hand grip for excellent tool guidance and even application
 - Large MPE sanding pad, hard wearing for long service life
 - StickFix system for fast abrasives changes
 - Very smooth running through VS balancing, easy on joints
 - Sand right up to the edge on 3 sides for full area sanding with no finishing work
 - Stepless electronic speed control for many applications

Power consumption	330 watts/2.75 amps 120 v AC
Pad size	4 1/2" x 9" (115 x 228 mm)
Speed	4,000 - 10,000 opm
Sanding stroke	3/32" (2.5 mm)
Weight	5.5 lbs. (2.5 kg)

(Metric dimensions binding)

Abrasives for orbital sanders

StickFix abrasive sheets



For DS 400 EQ delta sander
4" x 6" (100 mm x 150 mm)



	Grit	Qty	Item No.	Price		Grit	Qty	Item No.	Price
Brilliant 2 For paints and varnishes	P 40	10	492 804	4.50		P 120	100	492 797	26.00
	P 80	10	492 805	3.00		P 150	100	492 798	25.00
	P 120	10	492 806	3.00		P 180	100	492 799	25.00
	P 180	10	492 807	3.00		P 220	100	492 800	25.00
	P 40	50	492 793	17.50		P 240	100	492 801	25.00
	P 60	50	492 794	15.00		P 320	100	492 802	25.00
	P 80	50	492 795	14.00		P 400	100	492 803	25.00
	P 100	100	492 796	26.00					
Rubin For bare wood	P 50	10	489 478	4.50		P 100	50	489 041	15.00
	P 80	10	489 479	4.50		P 120	50	489 042	15.00
	P 100	10	489 480	3.00		P 150	50	489 043	15.00
	P 120	10	489 481	3.00		P 180	50	489 044	15.00
	P 50	50	489 039	17.50					
	P 80	50	489 040	15.00					
Vlies For light sanding and degreasing	A 120	10	489 045	18.50		S 800	10	489 047	15.00
	A 280	10	489 046	18.50					

StickFix abrasive sheets



For RS 400 EQ orbital sander
3 5/32" x 5 1/4" (80 x 133 mm)



	Grit	Qty	Item No.	Price		Grit	Qty	Item No.	Price
Brilliant 2 For paints and varnishes	P 40	10	492 859	3.00		P 120	100	492 852	20.50
	P 80	10	492 860	3.00		P 150	100	492 853	20.50
	P 120	10	492 861	3.00		P 180	100	492 854	20.50
	P 180	10	492 862	3.00		P 220	100	492 855	20.50
	P 40	50	492 848	14.00		P 240	100	492 856	20.50
	P 60	50	492 849	12.00		P 320	100	492 857	20.50
	P 80	50	492 850	11.00		P 400	100	492 858	20.50
	P 100	100	492 851	20.50					
Rubin For bare wood	P 50	10	490 393	3.00		P 80	50	490 388	12.00
	P 80	10	490 394	3.00		P100	50	490 389	12.00
	P 100	10	490 395	3.00		P 120	50	490 390	12.00
	P 120	10	490 396	3.00		P 150	50	490 391	12.00
	P 50	50	490 387	14.00		P 180	50	490 392	12.00
Titan* For solid surface and automotive	P 80	50	488 242	8.00		P 150	100	488 245	15.00
	P 100	100	488 243	15.00		P 180	100	488 246	15.00
	P 120	100	488 244	15.00		P 220	100	488 247	15.00
Vlies For light sanding and degreasing	A 100	5	483 580	5.50					
	A 280	5	483 581	5.50					
	S 800	5	483 582	5.50					

*This will be discontinued; only available while supplies last.





Abrasives for orbital sanders

StickFix abrasive sheets



For RS 2 E, RS 2 orbital sanders
4 1/2" x 9" (115 x 228 mm)




	Grit	Qty	Item No.	Price		Grit	Qty	Item No.	Price
Brilliant 2  For paints and varnishes	P 40	10	492 818	5.50		P 120	100	492 826	38.00
	P 80	10	492 819	4.50		P 150	100	492 827	36.50
	P 120	10	492 820	4.50		P 180	100	492 828	36.50
	P 180	10	492 821	4.50		P 220	100	492 829	35.50
	P 40	50	492 822	26.00		P 240	100	492 830	35.50
	P 60	50	492 823	22.50		P 320	100	492 831	35.50
	P 80	50	492 824	20.50		P 400	100	492 832	35.50
	P 100	100	492 825	38.00					
Rubin  For bare wood	P 50	10	489 474	5.50		P 100	50	484 406	22.50
	P 80	10	489 475	5.50		P 120	50	484 407	21.50
	P 100	10	489 476	5.50		P 150	50	484 408	21.50
	P 120	10	489 477	5.50		P 180	50	484 409	21.50
	P 50	50	484 404	27.00					
	P 80	50	484 405	22.50					
Titan  For solid surface and automotive	P 80	50	488 249	21.00		P 150	100	488 252	37.00
	P 100	100	488 250	37.00		P 180	100	488 253	37.00
	P 120	100	488 251	37.00		P 220	100	488 254	37.00
Vlies  For light sanding and degreasing	A 100	5	483 586	6.50					
	A 280	5	483 587	6.50					
	S 800	5	483 588	6.50					

Accessories for the DS 400 EQ sander

Purpose-designed for top results

Delta sander accessories



No.	Description and application	Type	Item No.	Price
1	StickFix sanding pad for use with StickFix abrasives	STF Delta 100 x 150	489 126	18.50
2	Turbo dust bag Paper dust bag for turbo dust extraction Pack of 5 Pack of 25	TF-RS 400/5 TF-RS 400/25	489 128 489 127	5.50 25.00
3	Turbo dust bag set Paper dust bag for turbo dust extraction with plastic holder	TFS-RS 400	489 129	14.00
4	Plug-it power cord, 13' (replacement)	SJO 2 x 18 AWG	490 649	30.50




*Lightweight and efficient.
The RS 400 EQ.*



*Small and handy.
The DS 400 EQ.*


Sanding pads and accessories for RS orbital sanders

Sanding pads accessories



No.	Description and application	Type	Item No.	Price
1	StickFix sanding pads for use in conjunction with StickFix abrasives RS 400 RS 2 RS 2	STF 80 x 130 mm STF 115 x 225 mm STF 115 x 225 mm-KS ¹⁾	489 252 483 679 485 648	19.00 28.50 30.50
2	MPE sanding pads for use in conjunction with clamped abrasives RS 2 (not shown) RS 2 (not shown)	115 x 225 mm 115 x 225 mm-KS ¹⁾	484 538 485 647	15.00 28.50
3	Hole punch to perforate standard abrasives for clamping fitting RS 2	10 holes, 115 x 225 mm	481 523	19.00

Turbo filter bags



No.	Description and application	Type	Item No.	Price
1	Turbo dust bags Paper dust bags for turbo dust extraction (packs of 5) a) RS 400 b) RS 2 Pack of 25 a) RS 400 b) RS 2	TF-RS 400 TF-II-ET/RS TF-RS 400/25 TF-II-ET/RS/25	489 128 487 779 489 127 487 871	5.00 5.00 23.00 24.00
2	Turbo dust bag set Paper dust bag for turbo dust extraction Version with plastic holder RS 400 RS 2 ETS 150	TFS-RS 400 TFS-II-ET/RS TFS-ES 150	489 129 487 780 489 631	14.00 19.00 15.00

¹⁾ with side edge protection

Deltex sander DX 93 E

Hard on the material – not on you

Festool gear-driven sanders are designed for strong abrasion through reduction gearing.

This means that they are ideal for stripping off old, thick, and stubborn coatings.

Festool gear-drive sanders are both powerful and economic to run. The DX 93 E gives excellent and complete abrasion in corners.



DX 93 E

A handy sander for difficult and hard-to-reach spots, the Deltex provides perfect sanding results in even the tightest of corners. The Deltex triangular sanding pad means you can power sand using the full area of the pad right into the tightest corner, saving labor and eliminating time-consuming manual sanding in problem areas.

Deltex is the ideal tool for sanding edges, surfaces, and corners in a single operation; for example, wooden staircases, parquet floors, etc. With a housing diameter of only 2 1/4" in the grip area, Deltex rests comfortably in your hand for fatigue-free work.

- Full-area sanding into every corner through orbital sanding motion
- Sanding stroke of 2.5 mm guarantees above average material removal
- Integrated dust extractor port
- Stepless electronic speed control for various uses
- StickFix sanding system for fast replacement of sanding pad and abrasives

Deltex



DX 93 E

Includes:


- Plate
- StickFix 93 V sanding pad (soft), 3 11/16" (93 mm)
- 1 Abrasive sheet
- Flat sanding pad
- In Systainer 1

Item No. 567 738Price \$260.00

See page 5 for package savings.

Power consumption	150 watts/1.3 amps 120 v AC
Pad size	3 11/16" (93 mm)
Speed	5,000 - 9,500 opm
Sanding stroke	3/32" (2.5 mm)
Weight	3.3 lbs. (1.5 kg)

(Metric dimensions binding)

Pads for Deltex sander		No. Description and application	Type	Item No.	Price
	1	StickFix sanding pad soft (pack of 2)	STF 93 V-W (snap stud)	488 715	11.50
	2	StickFix sanding pad hard (pack of 2)	STF 93 V-H (snap stud)	488 716	11.50
	3	Flat sanding pad (1 per pack)	L-STF 93 V	488 036	11.50
	4	Plate Component with StickFix coating onto which sanding pad is secured	TP-DX 2 (snap)	488 717	9.50
	5	Conversion kit DX 93 E Plate 488 717 and sanding pad 488 715, both with snap stud	TP-STF 93-V-W	488 899	17.00

Abrasives for Deltex Sander

StickFix abrasive sheets




For Deltex DX 93 E
3 11/16" (93 mm)



	Grit	Qty	Item No.	Price	Grit	Qty	Item No.	Price
Brilliant 2  For paints and varnishes	P 40	10	492 879	3.00	P 100	100	492 886	17.50
	P 80	10	492 880	3.00	P 120	100	492 887	17.50
	P 120	10	492 881	2.00	P 150	100	492 888	17.50
	P 180	10	492 882	2.00	P 180	100	492 889	17.50
	P 40	50	492 883	11.00	P 220	100	492 890	17.50
	P 60	50	492 884	9.50	P 240	100	492 891	17.50
	P 80	50	492 885	9.50	P 320	100	492 892	17.50
					P 400	100	492 893	17.50
Rubin  For bare wood	P 50	50	486 449	11.00	P 120	50	486 452	9.50
	P 80	50	486 450	9.50	P 150	50	486 453	9.50
	P 100	50	486 451	9.50	P 180	50	486 454	9.50
Saphir  For heavy duty use	P 24	25	487 515	9.50	P 80	25	487 518	7.50
	P 40	25	487 516	8.50	P 100	50	487 519	15.00
	P 60	25	487 517	8.50	P 120	50	487 520	15.00

Hand abrasives

Pocket StickFix



No. Description and application	Grit	Type	Item No.	Price
1 Pocket StickFix Hand sanding block		STF 46 x 178	583 129	9.50
2 StickFix abrasives for Pocket StickFix (pack of 10)	P 40 P 80 P 120 P 180 assorted P40 – P180	STF 46 x 178	492 843 492 844 492 845 492 846 492 847	3.00 3.00 3.00 3.00 3.00

Festool air tools



The LEX 150 6" air sander

Who Should Use Air Tools?

If you sand 3 or more hours a day every day, the economics of air tools catch up and make them the better option.

- Because air tools need a compressed-air supply, they are tied to a shop (less theft).
- Last up to five times longer than electrical power tools
- Much lighter and easier to use for extended periods
- Don't heat up in operation
- Notably quiet
- Reduced risk of electric sparks at the workpiece

The Tools

So, what makes Festool air tools stand out from the rest? In addition to these inherent advantages, Festool air tools offer important benefits of their own:

- Unique 3-in-1 air hose, combining air supply, exhaust, and dust extraction in a single conduit.

- Superior ergonomics light enough for easy one-hand use on the big areas, large enough for a steady two-hand hold on the details.
- Minimum vibration for easier all-day use with fewer breaks.
- Jetstream sanding pad design for longer abrasive life and more efficient sanding. Saves time, and saves money on abrasives.
- Sanders have a pad brake to prevent oversanding and marring when the tool is set down.
- Exhaust air goes out the 3-in-1 hose and away from you. No freezing tool, and no annoying wind in the work area.
- Long life
- Low maintenance
- Low noise, about 73 dB(A) at idle




Air tools for woodworking



Air tools for solid surface



Air tools for boating/marine work



Our CT mobile dust extractor easily converts for use with air tools.

The Dust Extractor

Dust extraction is essential for good working results and for operator health and safety. All of our air sanders incorporate dust extraction as a central design feature, and work with a central dust extraction system with standard 2" fittings, as well as with our CT mobile dust extractors. For your extra protection, HEPA filters are now available.

Our CT 33 Mobile Dust Extractor works with both air tools and electrical tools, and offers a host of operational benefits. The interior dimensions allow use of the full bag capacity, for less frequent refills. It's tool-triggered, so it comes on automatically when you start the tool. Adjustable speed control lets the operator set the right suction for the job. And extremely quiet operation makes it easy to live with over the entire course of a day. We understand that shop space is always at a premium, so we designed our dust extractors with flat tops for tool set-down or storage. You can even latch on a Festool Systainer box.

NOTE: Festool CT mobile dust extractors are electrically operated, and should not be used in explosive environments.




The Hose

At the heart of our air tool system is the unique IAS 2 three-in-one hose. This combines air supply, air exhaust, and dust extraction in a single conduit. That means no tangles, no twisted hoses, and less to trip over. And since there is only one hose attached to the tool, there is less hose drag so it takes less effort to move it around. A rotator connection at the tool end keeps the hose from twisting and kinking, and a bayonet coupling makes tool connects and disconnects a breeze, such as for switching from a coarse sander to a finishing sander.

Many compressed air sanders release the exhaust air at the machine, but not Festool. Our air tools send the exhaust air back through the 3-in-1 hose to a silencer at the far end. This brings the important benefits of quieter operation and no oily air blowing around in the workpiece area.

Naturally the IAS 2 is antistatic, so dust extraction can't build up a static charge. It connects via an adapter directly to our CT dust extractors, so you can work clean.




Sanders

Sanders	No. Description and application	Type	Item No.	Price
	<p>All Festool air sanders feature ergonomic softgrip housing cap, deadman switch, eccentric stroke marked on switch, sanding pad brake, jetstream pad design, MPE pad, hook-and-loop abrasive mounting, vibration stop, antistatic design and variable speed control</p>			
	<p>1 7" Sander Ideal for coarse and intermediate sanding of large surfaces LEX 2 185/7 87 psi flow pressure, 16000 max. strokes per minute, 9/32" sanding stroke, 14 CFM air consumption at rated load, 7 1/4" sanding pad diameter, 3.5 lbs</p>	LEX 2 185/7	691 124	370.00
	<p>6" Sanders Ideal for coarse and intermediate sanding of large surfaces</p>			
	<p>2 LEX 2 150/7 87 psi flow pressure, 16000 max. strokes per minute, 9/32" sanding stroke, 14 CFM air consumption at rated load, 2.9 lbs</p>	LEX 2 150/7	691 125	315.00
	<p>3 LEX 2 150/3 87 psi flow pressure, 16000 max. strokes per minute, 1/8" sanding stroke, 14 CFM air consumption at rated load 6" sanding pad diameter, 2.9 lbs</p>	LEX 2 150/3	691 126	315.00



Abrasives for 7" sander

StickFix abrasive sheets
 <p>StickFix abrasive sheets dia. 7" (185 mm)</p>




(see page 61 for 6" abrasives)

	Grit	Qty	Item No.	Price	Grit	Qty	Item No.	Price
Brilliant  For paints and varnishes	P 40	50	491 482	32.00				
	P 60	50	490 582	27.00				
	P 80	50	490 583	24.00				
	P 100	100	491 488	45.00				
Titan 2  For solid surface and automotive	P 80	50	490 584	27.00	P 240	100	490 588	47.00
	P 100	100	491 358	47.00	P 280	100	490 589	47.00
	P 120	100	490 585	47.00	P 320	100	490 590	47.00
	P 150	100	490 586	47.00	P 360	100	491 489	47.00
	P 180	100	490 587	47.00				
Saphir  For heavy duty use	P 24	25	491 484	26.00				
	P 36	25	491 483	29.00				


Accessories for 7" air sander

Sanding pads	No. Description and application	Type	Item No.	Price
	<p>Sanding and interface pads  </p>			
	1 dia. 7" (185 mm)/Sanding pad soft		490 514	45.00
	2 dia. 7" (185 mm)/Interface pad		491 491	28.00
	3 dia. 7" (185 mm)/Sanding pad supersoft		490 526	45.00

Accessories for 6" air sanders (see page 61 for 6" abrasives)

Sanding pads	No. Description and application	Type	Item No.	Price
	<p>Sanding and interface pads  </p>			
	1 dia. 6" (150 mm)/Sanding pad soft		486 382	31.50
	2 dia. 6" (150 mm)/Interface pad		486 381	31.50
	3 dia. 6" (150 mm)/Sanding pad supersoft		484 850	31.50
	4 dia. 6" (150 mm)/Interface pad (superfine abrasive)		492 212	14.50

Dust extractor & accessories for air tools

Dust extractor & accessories	No. Description and application	Type	Item No.	Price
	1 Mobile Dust Extractor Very quiet, highly effective and efficient. Fully adjustable power. Full use of collection bag capacity for fewer refills. Flat top for convenient tool storage, or latch on one or more Systainers for a rolling tool cabinet. 8.7 gal/7.9 gal capacity (vac/bag), 24"x15"x22", 72 dB noise level, 350-1200 W power, 134 CFM max suction cap., 90" static water lift (23000 Pa) max vacuum, 32 lbs	CT 33 E	583 368	490.00
	2 Antistatic Hoses Combines air supply, exhaust air, and dust extraction in a single hose. Tool-side rotator connector to prevent twisting. Extremely flexible, tough, non-marring. IAS-2-3500 AS Length: 11.5 ft. IAS-2-5000 AS Length: 16.4 ft. IAS-2-7000 AS Length: 22.9 ft.	IAS-2-3500 AS IAS-2-5000 AS IAS-2-7000 AS	487 901 488 176 488 131	190.00 228.00 279.00
	Filter Bags/Longlife Filter Bag Filter Bags in packs of 5, Longlife Filter Bag sold singly.	FIS-CT 33 FIS-CT 33	452 971 456 738	29.00 184.00
	3 FIS-CT 33 paper 4 FIS-CT 33 longlife	FIS-CT 33 FIS-CT 33	452 971 456 738	29.00 184.00
	5 Handle Attaches to CT 33. Provides mounting space for service unit.	SB-CT	452 921	62.00
	6 Service Unit For standard CT dust extractors. Has filter with condensate drain, pressure regulator, oiler, additional oil-free air outlet with quick coupling, prefitted on holding bracket. Includes attachment hardware and air hose.	VE-CT	452 797	349.00
	7 Compressed Air Module Converts standard CT dust extractor to compressed air auto-start version.	DLM-CT	452 829	121.00
	8 IAS 2 Adapter For connecting the CT dust extractors with IAS 2 air tools using IAS 2 air hoses. Antistatic design. Fits all standard 2" central dust extraction systems.	IAS 2-A-ASA/CT	454 757	102.00
	9 Adapter Prevents damage to tools and hose that may result if the IAS 2 hose is used for dust extraction without this adapter. (not shown)	AD-IAS 2/D36	488 418	63.00
	10 IAS 2 Double Adapter To run 2 air tools on 1 CT (also requires IAS 2 Adapter).	IAS 2-DA-CT	454 758	152.00
	11 3/8" Adapter To convert 3/8" ISO thread to 3/8" NPT. (not shown)	AD 3/8 - 3/8 NPT	9397	6.00
	12 Suction Hose Holder Keeps hose off floor for a neater, safer workplace.	SH-CT/SR	487 072	28.50

Package A – All-in



LEX 2 150/3

+



CT 33

LEX 2 150/3
Package price \$1187.00

Save \$425

Item No. PA3691 126



LEX 2 150/7

+



CT 33

LEX 2 150/7
Package price \$1187.00

Save \$425

Item No. PA3691 125



LEX 2 185/7

+



CT 33

LEX 2 185/7
Package price \$1242.00

Save \$425

Item No. PA3691 124

Upgrade from 11.5 to 16.4 ft. hose U488 176 add \$36.00
Upgrade from 11.5 to 22.9 ft. hose U488 131 add \$85.00

If you're just getting started, this is the way to go

Get the LEX 2 150/3 or LEX 2 150/7 (6" air sanders), or LEX 2 185/7 (7" air sander) together with the following: Dust Extractor, Handle, Service Unit, Compressed Air Module, 3/8" Adapter, IAS 2 Adapter, Suction Hose Holder, IAS 2 Hose (antistatic) 11.5 ft.

Packages

System Requirements for all packages:

- Compressor
- Minimum 3/8" air line and couplings recommended
- Supplied air pressure must be regulated to 116 psi = 8 bar
- Tool flow pressure: 87 psi = 6 bar
- Dynamic pressure: 102 psi = 7 bar
- Minimum 14 CFM

Package B – Adding to the Festool System

If you already have an air supply plus our CT 33 E Dust Extractor, this is for you. Get the LEX 2 150/3 or LEX 2 150/7 (6" air sanders), or LEX 2 185/7 (7" air sander) together with the following: Handle, Service Unit, Compressed Air Module, 3/8" Adapter, IAS 2 Adapter, Suction Hose Holder, IAS 2 Hose (antistatic) 11.5 ft.

LEX 2 150/3
Package price \$795

Save \$337

Item No. PB3691 126




LEX 2 150/3

LEX 2 150/7
Package price \$795

Save \$337

Item No. PB3691 125



LEX 2 150/7

LEX 2 185/7
Package price \$850

Save \$337

Item No. PB3691 124



LEX 2 185/7

Upgrade from 11.5 to 16.4 ft. hose U488 176 add \$36.00
Upgrade from 11.5 to 22.9 ft. hose U488 131 add \$85.00

Package C – Just the tools

If you already have an air supply, central dust extraction system (high speed turbine type), and local regulator and air filter, you can still save with this package. Get the LEX 2 150/3 or LEX 2 150/7 (6" air sanders), or LEX 2 185/7 (7" air sander) together with the following: IAS 2 Adapter, IAS 2 Hose (antistatic) 11.5 ft.

LEX 2 150/3
Package price \$416

Save \$177

Item No. PC3691 126




LEX 2 150/3

LEX 2 150/7
Package price \$416

Save \$177

Item No. PC3691 125



LEX 2 150/7

LEX 2 185/7
Package price \$471

Save \$177

Item No. PC3691 124



LEX 2 185/7

Upgrade from 11.5 to 16.4 ft. hose U488 176 add \$36.00
Upgrade from 11.5 to 22.9 ft. hose U488 131 add \$85.00

A new dimension in dust extraction



Festool's mobile dust extractors do more than just clean.

Innovative design and versatility are only two of the characteristics of the Festool Cleantec (CT) mobile dust extractors. Offered in three different sizes, the CT units are compact and mobile, with sturdy chassis, extra large wheels, and double casters to easily negotiate obstacles in the shop or on the work site. On sloping ground, the CT 22 and CT 33 can be stabilized with an integrated parking brake.

For added convenience, one or more Systainers can be secured to the top of the unit, or simply use the large flat space as a handy place to lay tools. All will work wet or dry with no complex conversion, and all are remarkably quiet.

Cleantec Mobile Dust Extractors

CT 22 and CT 33 now come standard equipped with HEPA filters. Regular HEPA filtration frees the air of up to 99.97% of all particulate down to .3 microns in size. Developed by the Atomic Energy Commission to remove radioactive dust from industrial exhaust, high efficiency particulate air (HEPA) filters are now the primary filtration systems for the most sensitive manufacturing and healthcare environments. There is no better filtration available on the market today.



With Festool, HEPA filtration improves to 99.99% dust-free.

The benefits at a glance



Easier to use

- Tool-triggered auto-start for convenient use.
- Quieter running for a more pleasant working environment with less distraction.
- On-board storage compartment for an extra bag and accessory items.
- Larger wheels roll easily over most obstacles and give increased stability.



- Parking brake for a stable position.
- Available handle for the CT22 and CT33 improves mobility and ease of handling.



Superior functionality

- Adjustable power for all kinds of jobs.
- Long, flexible, non-kink hose.
- Sys-Dock for latching on a Systainer for easy tool transport and storage.
- Level Stop for wet vacuuming – electronic sensors automatically turn motor off when maximum liquid capacity is reached. No moving parts mean improved reliability and prolonged life.



Better filtration

- Flat filter has a surface area four times greater than regular corrugated filters.
- Integrated flat filter quick cleaning system – cleans the filter with a quick push-pull.
- Interior design makes full use of filter bag capacity.



Mobile dust extractor



CT MINI

Includes:

- 1 fitted filter bag and 1 spare
- 1 antistatic suction hose, 1" x 11.5 ft. (27 mm x 3.5 m)
- Angle adapter
- Delivered in a box

Item No. 583 360.....Price \$285.00

See page 5 for package savings.

CT MINI

- For non-hazardous dusts
- 2.6 gal (10 L) capacity
- Low weight and small size, so you can work clean anywhere, to save cleanup time and extend the life of tools and consumables
- Tool-triggered or manual start

- Locking brake prevents accidental movement
- Quiet running for a more pleasant working environment
- On-board extra bag storage for fast replacement
- Wet vacuum capability

- Long, flexible, non-kink hose
- Flat top and Sys-Dock for latching on a Systainer for easy tool transport and storage
- Antistatic equipment standard
- Wet and dry extraction with no complicated conversion

Container/Filter bag capacity	2.6 gal/2 gal
Depth x Width x Height	17.5" x 13.5" x 16.5" (440 x 340 x 420 mm)
Weight	21 lbs. (9.5 kg)
Noise (sound level)	72 dB (A)
Power consumption	350 - 1200 watts/3 - 10 amps 120 v AC
Max. suction capacity	99 CFM (2800 l/min)
Max. vacuum	80" static water lift (20000 Pa)

(Metric dimensions binding)

Mobile dust extractor



CT 22 E

Includes:

- HEPA filters
- 1 fitted filter bag
- 1 antistatic suction hose, 1" x 11.5 ft. (27 mm x 3.5 m)
- Delivered in a box

Item No. 583 366.....Price \$425.00

See page 5 for package savings.

CT 22 E

- For non-hazardous dusts
- 5.8 gal. (22 L) capacity
- Larger wheels provide stability and ease of movement
- Locking brake on rear wheels means no accidental movement of the dust extractor

- Large flat area for tools or Systainer stacking
- Tool-triggered or manual on-off switch with smooth start-up and shut-off delay
- Replaceable filter bag
- Stepless electronic suction control

- Wet and dry extraction with no complicated conversion
- Integrated cleaning device cleans the filter in the blink of an eye
- Blower port
- Standard antistatic equipment protects against electrostatic charging

Container/Filter bag capacity	5.8 gal/5.3 gal
Depth x Width x Height	24" x 15" x 17" (625 x 380 x 440 mm)
Weight	26.5 lbs. (12 kg)
Noise (sound level)	72 dB (A)
Power consumption	350 - 1200 watts/3 - 10 amps 120 v AC
Max. suction capacity	134 CFM (3800 l/min)
Max. vacuum	90" static water lift (23000 Pa)

(Metric dimensions binding)

Mobile dust extractor



CT 33 E

Includes:

- HEPA filters
- 1 fitted filter bag
- 1 antistatic suction hose, 1" x 11.5 ft. (27 mm x 3.5 m)
- Delivered in a box

Item No. 583 368.....Price \$490.00

See page 5 for package savings.

CT 33 E

- For non-hazardous dusts
- 8.7 gal. (33 L) capacity
- Larger wheels provide stability and ease of movement
- Locking brake on rear wheels means no accidental movement of the dust extractor

- Large flat area for tools or Systainer stacking
- Tool triggered or manual on-off switch with smooth start-up and shut-off delay
- Replaceable filter bag
- Stepless electronic suction control
- Integrated storage compartment

- Wet and dry extraction with no complicated conversion
- Integrated cleaning device cleans the filter in the blink of an eye
- Blower port
- Standard antistatic equipment protects against electrostatic charging


Container/Filter bag capacity	8.7 gal/7.9 gal
Depth x Width x Height	24" x 15" x 22" (625 x 380 x 550 mm)
Weight	32 lbs. (14.5 kg)
Noise (sound level)	72 dB (A)
Power consumption	350 - 1200 watts/3 - 10 amps 120 v AC
Max. suction capacity	134 CFM (3800 l/min)
Max. vacuum	90" static water lift (23000 Pa)

(Metric dimensions binding)

Cleaning sets

The right set for every application

Cleaning sets



No.	Description	Type	Item No.	Price
1	Installer cleaning set in Systainer SYS 4 with deep drawn insert SYS TZE-RS suction hose D 36 x 11.5' (3.5 m) AS curved hand tube D 36 HR-M extension tube D 36 VR-M 3x carpet nozzle D 36 TD crevice nozzle D 36 FD upholstery nozzle D 36 PD suction hose D 36 SP	D 36 HW-RS	454 766	177.00
2	Workshop cleaning set in Systainer SYS 4 with deep drawn insert SYS TZE-RS suction hose D 36 x 11.5' (3.5 m) AS curved hand tube D 36 HR-M extension tube D 36 VR-M 3 x floor nozzle D 36 BD -370	D 36 WB-RS	454 767	203.00
3	Universal cleaning set in Systainer SYS 4 with deep drawn insert SYS TZE-RS suction hose D 36 x 11.5' (3.5 m) curved hand tube D 36 HR-K extension tube D 36 VR-K 3 x floor nozzle D 36 BD 300 crevice nozzle D 36 FD upholstery nozzle D 36 PD suction brush D 36 SP	D 36 DIY-RS	454 769	121.00
4	Compact cleaning set in Systainer SYS 1 extension tube, plastic D 36 VR-K 3x floor nozzle, 4 part D 36 BD 270 upholstery nozzle D 36 PD hand pipe, bent, plastic D 36 HR-K crevice nozzle D 36 FD (suction hose not included)	D27/D36 K-RS	456 736	62.00
5	Industrial cleaning set in cardboard box suction hose D 50 x 8.25' (2.5 m) extension tube D 50 VR-K 2 x floor nozzle D 50 BD 370 square nozzle D 50 QD suction brush D 50 SP crevice nozzle D 50 FD	D 50 GS-RS	454 770	88.50

Accessories for dust extractors

Suction hoses



No. Description and application	Anti-static ²⁾	Type	Item No.	Price
1 Suction hoses Temperature resistant to 70°C (158°F), leakage resistance of antistatic version ³⁾ ≤ 10 ⁶ Ohm. Temperature resistant to 70° C (158°F) with rotating adapter and reducing sleeve (1" x 11.5') with rotating adapter and reducing sleeve (1" x 16.5') with rotating adapter and reducing sleeve (1 7/16" x 11.5') with rotating adapter and reducing sleeve (1 7/16" x 16.5') with rotating adapter and reducing sleeve (1 7/16" x 23') with rotating adapter and reducing sleeve (2" x 8.25') with rotating adapter and reducing sleeve (2" x 13') with rotating adapter and reducing sleeve (1" x 11.5') with rotating adapter and reducing sleeve (1" x 16.5') with rotating adapter and reducing sleeve (1 7/16" x 11.5') with rotating adapter and reducing sleeve (1 7/16" x 16.5') with rotating adapter and reducing sleeve (1 7/16" x 23') with rotating adapter and reducing sleeve (2" x 8.25') with rotating adapter and reducing sleeve (2" x 13')	AS	<ul style="list-style-type: none"> D 27 x 3.5 m-AS D 27 x 5 m-AS D 36 x 3.5 m-AS D 36 x 5 m-AS D 36 x 7 m-AS D 50 x 2.5 m-AS D 50 x 4 m-AS D 27 x 3.5 m D 27 x 5 m D 36 x 3.5 m D 36 x 5 m D 36 x 7 m D 50 x 2.5 m D 50 x 4 m	452 878 452 880 452 882 452 884 452 886 452 888 452 890 452 877 452 879 452 881 452 883 452 885 452 887 452 889	76.50 103.00 105.00 124.00 157.00 89.50 124.00 49.50 56.50 62.00 76.50 89.50 56.50 78.00

³⁾ Antistatic versions are only effective when used with an AS dust extractor.

Hose sleeves



No. Description and application	Anti-static ²⁾	Type	Item No.	Price
2 Rotating adapters hose connector to fit inlet nozzle of dust extractor, external dia. 2 9/32" (58 mm) 2a Antistatic version for D 50 suction hose 2b Antistatic version for D 36 suction hose 2c Antistatic version for D 27 suction hose 2d For D 50 suction hose 2e For D 36 suction hose 2f For D 27 suction hose 3 Reducing sleeve hose connector for electric tool or suction nozzle 3a with rotating adapter for D 27 suction hose 3b antistatic version with rotating adapter for D 36 suction hose	AS	<ul style="list-style-type: none"> D 50 DAG-AS D 36 DAG-AS D 27 DAG-AS D 50 DAG D 36 DAG D 27 DAG <ul style="list-style-type: none"> D 27 DM-AS D 36 DM-AS 	452 896 452 894 452 892 452 895 452 893 452 891 487 071 487 721	18.50 16.00 13.00 16.00 13.00 11.00 12.50 13.00
4 Suction adapter for reducing from D50 to D36 hose 5 Angle adapter for CT MINI 6 Connector sleeve³⁾ (antistatic) with corresponding rotating adapter to connect suction hoses D 50/D 36/D 27 7 Y-piece with blanking plug⁴⁾ to connect two suction hoses D 27/D 36/D 50 8 Blanking plug for retrofitting on CT 11/22/33, to seal off inlet during transportation.		D 50/D 36 D 27/DAG/90-AS D 50/36/27-CT D 50 SV-AS/D 50V D 50 V	452 897 456 806 493 047 452 898 452 899	9.50 18.00 11.00 24.00 7.50


²⁾ Antistatic versions are only effective when used with an AS dust extractor.

⁴⁾ For simultaneous connection of two electric tools with dust extraction.

³⁾ With D 36/D 27 hoses the reducing sleeve for the hose must be replaced by a D 36/D 27 rotating adapter.

Accessories for dust extractors

Tubes




No.	Description and application	Type	Item No.	Price
Curved hand tube				
1a	Stainless steel	D 36 HR-M	452 900	35.50
Curved hand tube				
1b	Polypropylene (PP) with air regulating slide to adjust suction power	D 36 HR-K	452 901	13.00
Extension tube				
2a	Stainless steel, 3 piece, 37 1/2" (950 mm)	D 36 VR-M 3 x	452 902	40.00
2b	Polypropylene (PP), 3 piece, 37 1/2" (L= 950 mm)	D 36 VR-K 3 x	452 903	16.00
3a	One-piece anodized aluminum, 43 1/2" (L= 1100 mm)	D 50 VR-M	447 599	100.00
3b	Plastic, 2-piece, 38" (L= 970 mm)	D 50 VR-K 2 x	440 412	24.00

Floor nozzles



No.	Description and application	Type	Item No.	Price
4a	Floor nozzle high quality industrial design, aluminum, width 14 5/8" (370 mm), 2 casters, 2 brush inserts	D 36 BD 370	452 908	95.00
4b	Replaceable wearing parts: brush insert, casters		452 934	16.00
4c	Retrofit kit: water extraction: rubber lips and casters		452 936	17.00
4d	Floor nozzle high quality industrial design, aluminum, width 17 11/16" (450 mm), 2 casters, 2 brush inserts	D 50 BD 450	452 910	108.00
4e	Replaceable wearing parts: brush insert, casters		452 935	19.00
4f	Retrofit kit: water extraction: rubber lips and casters		452 937	21.00
5a	Floor nozzle plastic, width 11 13/16" (300 mm) 2 casters, 2 brush inserts	D 36 BD 300	452 907	25.00
5b	Floor nozzle , plastic, width 14 5/8" (370 mm), 2 casters, 2 brush inserts	D 50 BD 370	452 909	41.00
6	Floor nozzle, 4-piece, plastic , with 3 replaceable inserts (brushes, rubber lips, carpet)	D 36 BD 270	452 906	21.50
7	Carpet nozzle , with sliding base for changeover from carpet to smooth floor	D 36 TD	452 911	38.00
8	Turbo combination suction brush for textile and linoleum floors with 4 casters, width 10 5/8" (270 mm), brush rollers driven by intake air, requires 36 mm hose	D 36 TKB	450 644	83.00

Special nozzles/brushes



No.	Description and application	Type	Item No.	Price
9a	Crevice nozzle Plastic length 14 5/8" (370 mm)	D 36 FD	452 904	5.50
9b	Crevice nozzle Plastic length 14 5/8" (370 mm)	D 50 FD	452 912	13.00
10	Suction brush Plastic, dia. 2 13/16" (70 mm)	D 36 SP	440 404	8.50
11	Upholstery brush Plastic, with brush insert width 4 11/16" (120 mm)	D 36 PD	440 406	6.50
12	Universal brush nozzle Plastic, brush ring 4 11/16" x 1 5/8" (120 x 40 mm)	D 36 UBD	440 403	10.50
13	Bevel ended nozzle Rubber, length 7 1/2" (190 mm), outside dia. 1 5/8" (40 mm)	D 36 SRD	411 810	19.00


Accessories for dust extractors

Other accessories




No.	Description	CT MINI	CT 11E	CT 22E	CT 33E	Type	Item No.	Price
1	Spark trap For use when sanding materials which generate sparks			•	•	D 50 FL	484 733	94.00
2	Handle			•	•	SB-CT	452 921	62.00
3	Hose hook		•	•	•	SH-CT	452 998	27.50
4	Suction hose holder Eliminates the tripping hazard of hoses on the floor		•	•	•	SH-CT/SR	487 072	28.50
5	Dirt trap Collects wet coarse dirt			•	•	SBH-CT 22 SBH-CT 33	452 925 452 926	82.00 95.50
6	CT adapter plug replacement (not shown)	•	•	•	•		493 232	8.00
7	Boom arm Keeps cord and hose out of the way (must use with handle above)			•	•		492 753	159.00

CT filters and filter bags



No.	Description	CT MINI	CT 11E	CT 22E	CT 33E	Type	Item No.	Price
8	Filter element Main filter, 2 pieces 1 piece	•	•	•	•	HF-CT HF-CT	452 923 456 790	25.00 13.00
9	Wet Filter element Wet filter, 2 pieces 1 piece	•	•	•	•	NF-CT NF-CT	452 924 456 805	11.50 12.50
10	Longlife filter element Main filter, 2 pieces (not shown)		•	•	•	HF-CT	454 869	50.50
11	Filter bag 5 pieces	•	•	•	•	FIS-CT MINI FIS-CT 11 FIS-CT 22 FIS-CT 33	456 772 452 974 452 970 452 971	16.00 24.00 26.00 29.00
12	HEPA filter element		•	•	•		493 334	52.00
13	Longlife filter bag re-usable bag			•	•	FIS-CT 22 FIS-CT 33	456 737 456 738	177.00 184.00

SR-filters



No.	Description	SR 201	Type	Item No.	Price
14	Absolute Filters, BIA-approved	•	AB-FI/U (3150)	485 808	31.50
15	Filter bag, SR series vacuums 5 pieces 20 pieces (not shown)	• •	FIS-SR 200 FIS-SR 200	487 070 487 874	47.50 113.00



- a) Suction hose holder mounted on CT mobile extractor, hose extended
- b) Suction hose holder mounted on CT mobile extractor, hose coiled

Guide system for precision sawing

Absolutely straight, precise, splinter-free


Absolutely straight, safe and precise

Festool FS guide rails are available in ten different lengths from 32" to 197", providing the right rail for every application.

Simply lay the guide rail on the workpiece and line up the splinter guard flush with the scribe line. Now place your Festool circular saw on the guide rail. The guide rib on the rail engages in the guide slot on the tool. You save laborious measurements and obtain perfectly straight and accurate cuts.



The guide rail




Gentle on surfaces

The soft, non-slip coating prevents damage to the workpiece and holds the guide rail securely in place without clamping or taping. This protects sensitive, high quality materials and saves time-consuming reworking. The saw slides smoothly on the guide rail, so that you can guide the saw easily with a precision that will remain constant over years of use.

Patented splinter guard

Festool guide rails are equipped with a splinter guard. A rubber lip pressing onto the workpiece along the scribe line ensures splinter-free cut edges.



Zero lateral play adjustment for perfect results

The guide slot can be adjusted precisely to the dimensions of the guide rib. All guide rails will thus fit any Festool saw. This adjustment ensures maximum cutting precision and easy handling. You save time and avoid spoiling workpieces.



Guided cuts at any bevel angle

With Festool, the scribe line is always the cutting edge—even on angles between 45° and 90°.



Precise angle cuts up to 45° on both sides

With the FSW angle unit and a guide rail you can quickly set angles of 0° to 45° to either side. This allows you to cut boards and panels to any size at any desired angle, fast, safely, and accurately.

Guide system for precision routing

Guided routing to a scribe mark

To rout out grooves, simply align the guide rail to the scribe mark and fix it in place with Festool clamps. It is now absolutely impossible for the router to wander. This makes routing work easier and faster and at the same time safer and more precise.



Routing at any desired angle

The Festool guide system is also an ideal solution for routing work at an angle on the outer edge of workpieces. The guide cannot slip if secured with FSZ clamps. This avoids reworking and spoiled workpieces.



For ultra-precise guidance

A guide rail fixed into place with the special Festool FSZ clamps, and a guide stop adjusted to be free of backlash, provide the basis for ultra-precise work. For example, use it for dovetail joints produced in several steps. Even when routing against the grain, the router cannot deviate from the desired path, giving perfect results.

Drilling extremely accurate rows of holes


The FS-LR 32 hole drilling system makes it easy to produce rows of holes in furnituremaking, for dowels, shelf supports, etc. The router is positioned precisely by an indexing pin. Recesses for hardware fittings can also be routed precisely between the holes on a 32 mm grid pattern (Euro-holes). This method is highly economical for the production of single pieces or short runs.



Guide rail FS/2

Intelligent technology for precise working

Guide rails



No.	Description and application	Type	Item No.	Price
Guide rail <ul style="list-style-type: none"> • Hard-anodized surface • Soft, non-slip coating • Hard rubber splinter guard • Mounting slot for: FSW angle unit FSV connectors FSZ clamps FS-AW Deflector 				
1	Length 32" (800 mm)	FS/2 800/2	491 499	49.50
2	Length 42" (1080 mm)	FS/2 1080/2	491 504	63.00
3	Length 55" (1400 mm)	FS/2 1400/2	491 498	74.50
4	Length 75" (1900 mm)	FS/2 1900/2	491 503	132.00
5	Length 95" (2400 mm)	FS/2 2400/2	491 502	190.00
6	Length 106" (2700 mm)	FS/2 2700/2	491 937	202.00
7	Length 118" (3000 mm)	FS/2 3000/2	491 501	227.00
8	Length 197" (5000 mm)	FS/2 5000/2	491 500	375.00
9	Length 42" for hole series (1080 mm)	FS/2 1080/2-LR 32	491 621	66.00
10	Length 95" for hole series (2424 mm)	FS/2 2424/2-LR 32	491 622	215.00

Accessories for guide system FS, FS/2

Intelligent technology for precise working

Accessories for guide rails




No.	Description and application	Type	Item No.	Price
1	Angle unit with scale for attachments to FS/2 guide rail	FS-KS	491 588	65.00
2	Clamps For securing guide rails Pack of 2, clamping width 4 11/16" (120 mm) or clamping width 11 13/16" (300 mm)	FSZ 120 FSZ 300	489 570 489 571	31.50 37.00
3	Connector Connects two guide rails for long workpieces - quantity 1 (2 are needed)	FSV	482 107	11.50
4	Deflector Prevents suction hoses and cables from catching on the end of the guide rail	FS-AW	489 022	12.00
5	Limit stop Provides front and rear stop position on guide rail	FS-FB	485 827	19.00
6	Guide rail tote bag For FS 1400/2 and shorter. A convenient way to take a guide rail with you.	FSB 1400	466 357	72.50
7	Gecko For lifting and carrying big and awkward loads that are difficult to handle.		492 617	48.50
8	Gecko Set		493 507	56.00
9	Gecko Pad (replacement)		493 307	11.00
10	Gecko Adapter (not shown)		492 616	14.50

Accessories for guide rails



No.	Description and application	Type	Item No.	Price
11	Guide rail accessory kit • Angle unit • Return/limit stop • Extra splinter guard • Deflector • 2 connectors • 2 steel clamps	FS-SYS/2	492 396	158.00

Replacement parts for guide rails



No.	Description and application	Type	Item No.	Price
12	Splinter guard replacement splinter guard for guide rails	FS-SP 800 (32") FS-SP 1400 (55") FS-SP 3000 (118")	488 468 483 164 488 467	6.50 9.50 14.50
13	Adhesive strip replacement adhesive strips for guide rails, in 32.8 ft. (10 m) rolls	FS-HU 10 M	485 724	17.00
14	Tool glide strip replacement adhesive PTE plastic strip for FS/2 guide rails, in 32.8 ft. (10 m) rolls	FS-GB 10 M	491 741	24.00

Portable multifunction table



To the table – with a saw, planer, and cutter

The MFT multifunction table unites sawing and routing functionality and economic efficiency in one portable work table.

The large support area, in conjunction with the guide rail and large angle stop, guarantees a precise and secure grip on the workpieces. This means that even short strips can be beveled, for example.

One more tip – when working on small, narrow workpieces, place another workpiece of equivalent height underneath them. This will be safer and more accurate.



The benefits at a glance

Outstanding results

- Large support area and versatile range of applications for economic working.
- Two different table sizes and versatile range of accessories for optimal operating conditions.
- Foldaway legs for portability, to give you a shop-steady work surface anywhere.

Significant time savings


- Easy clamping using perforated plate and special accessories.
- Quick to use, all-around angle stop.

Lower costs

- Guide rail with adjustable height for safer sawing, even on small workpieces, and fewer spoiled workpieces.

*Example of universal
clamping of workpieces
on the multifunction table.*

Multifunction table



MFT 800 Table

Includes:

- Table with perforated top & foldaway legs
- Swivel unit
- End stop
- Deflector
- Angle stop
- Guide rail FS 800

Item No. 492 651\$320.00

MFT 800 Basic (table only)

Item No. 493 932\$220.00

MFT 800 Hardware Kit

Item No. 494 070\$135.00

MFT 1080 Table

Includes:

- Table with perforated top & foldaway legs
- Swivel unit
- End stop
- Deflector
- Angle stop
- Guide rail FS 1080

Item No. 492 652Price \$440.00

MFT 1080 Basic (table only)

Item No. 493 933\$340.00

MFT 1080 Hardware Kit

Item No. 494 071\$150.00

MFT 800/MFT 1080

A strong, sturdy, portable worktable for clean cuts and precise angles. Enables a Festool plunge saw to function as a chop saw, radial arm saw, and miter box. When used with the Festool router and Festool saws, exact repeat operations are performed with ease.

- Large support area for safe processing of large and small workpieces
- Quick and easy setup and breakdown, thanks to foldaway legs
- Height-adjustable guide rail, lowers onto workpiece for safe sawing of small and narrow workpieces


- Angle stop can be used in any position on the table
- Clamping element accessories are available for secure work hold down
- Length stop accessory for registering repeat cuts in production applications
- MFT 1080 has double-sized work area (not shown)

Table dimensions	MFT 800	23" x 28" (590 x 725 mm)
	MFT 1080	28" x 45" (725 x 1165 mm)
Working height (folded down)		32" (820 mm) 8" (205 mm)
Max. workpiece thickness		3 1/2" (90 mm)
Max. working width	MFT 800	20" (510 mm)
	MFT 1080	28" (725 mm)
Max. working width longitudinal	MFT 800	24" (625 mm)
	MFT 1080	42 1/2" (1085 mm)
Weight	MFT 800	44 lbs. (20 kg)
	MFT 1080	73 lbs. (33 kg)

(Metric dimensions binding)

See page 5 for package savings.

FS rapid clamp and accessories



No.	Description and application	Type	Item No.	Price
1	FS-Rapid clamp and fixed jaws For clamping and positioning with Festool guide rails Includes fixed jaws and clamping jaws Quantity in pack: 1	FS-RAPID/1	489 790	33.50
2	Clamping profiles For use with the FS-RAPID clamps Length 32" (800 mm) Length 55" (1400 mm)	SPR 800 SPR 1400	490 189 490 190	19.50 28.00
3	Quick Clamp Easily locked and quickly released. For use with MFT and guide rails. Quantity in pack: 1	FS-HZ 160	491 594	32.50

Accessories



No.	Description and application	Type	Item No.	Price
4	Longitudinal stop Adjustable stop for use on all sides of MFT 800 and MFT 1080	MFT-LA	488 564	33.50
5	Clamping elements For safe and exact fixing of workpiece (sawing, sanding, routing, drilling etc.) Pack of 2	MFT-SP	488 030	80.00
6	Table profile, long Build your own bigger MFT Length: 79" (2000 mm) Pack of 2	MFT-TP 2000	488 555	156.00
7	Perforated plate For MFT 800, 23" x 28" (590 x 725 mm) For MFT 1080, 28" x 45" (725 x 1165 mm)	MFT-LP 800 MFT-LP 1080	488 565 489 396	44.00 82.00
8	Angle stop Replacement for MFT	MFT-WA	488 563	79.00
9	Table extension 10 3/4" x 27 1/4"	VL 700/MFT	489 575	124.00
10	Adjustable stop	MFT-AR	490 555	23.00
11	MFT Connector For connecting 2 MFT tables	VS-V650	484 455	10.50

Systainer® – the ultimate system for easier transport, storage and packaging

A tidy workshop, a good impression on customers, clean storage, safe tool transport to job sites – the advantages of the Systainer are as varied as its details are clever.

Quality: one hundred percent reliability

The Systainer copes with knocks and jolts just as easily as heat, cold, or wetness. It's made of tough, thermally stable ABS, and it's built strong, sturdy, and compact.

Versatility: open for anything

The Festool Systainer is not just the ideal storage system for tools and accessories. It can also be used for innumerable other purposes. You'll be amazed by its versatility. The more Systainers you have, the more you benefit from them. They come in several heights and versions, that all work together as a system.



Systainer – never better

The latching system – simple but ingenious

The lid latches of the Systainer also latch one Systainer to another. This Festool patent has a great practical benefit – you can latch several Systainers together and carry them as a single unit. This means fewer trips back and forth to your vehicle, saving time and hassle.



Perfect stacking

All Systainers have the same base dimensions, matched to Europallets. This means that Systainers fit together flush, even when units of different heights are stacked together, for the most efficient use of space in transit and storage.



The storage system: everything in its place

Everything has its place in the Systainer. You can find everything instantly, even if you have a lot of accessories.

Safety: there isn't a catch

All locks and handles are recessed. There are no projecting parts to catch on anything, so you won't be surprised by an open container.



Systainer® – the unique transport, storage and packaging system

Systainers without inserts



No.	Type	Height inches	Weight pounds	Item No.	Price
1	SYS 1 dimensions (L x W x H) 15 5/8" x 11 5/8" x 4"	4	3.1	445 433	45.00
2	SYS 2 dimensions (L x W x H) 15 5/8" x 11 5/8" x 6"	6	3.5	445 434	48.50
3	SYS 3 dimensions (L x W x H) 15 5/8" x 11 5/8" x 8"	8	4.2	445 596	53.50
4	SYS 4 dimensions (L x W x H) 15 5/8" x 11 5/8" x 12"	12	5.3	445 597	56.50
5	SYS 5 dimensions (L x W x H) 15 5/8" x 11 5/8" x 16" (not shown)	16	6.0	493 283	62.00
6	Maxisystainer Can be coupled with SYS 1, SYS 2, SYS 3, SYS 4 dimensions (L x W x H) 23 1/4" x 15 11/32" x 8 1/4"	8.27	8.8	490 701	79.00
7	Minisystainer Can be coupled only with other Minisystainers dimensions (L x W x H) 10 13/32" x 6 11/16" x 2 3/4"	2.76	0.9	460 853	21.00

Systainers with inserts for abrasives



No.	Type	Systainer-size	Item No.	Price
8	FYS-ST5 D115 For RAS 115 abrasives	SYS 1	487 432	50.50
9	SYS-STF D 125 For 5" abrasives	SYS 1	489 463	50.50
10	SYS-STF 80 x 133 For LS 130/RS 400 abrasives	SYS 1	487 435	50.50
11	SYS-STF 93 V For Deltex abrasives	SYS 1	487 633	50.50
12	SYS-STF 115 x 228 For RS 2E, RS 2 abrasives	SYS 2	487 433	54.50
13	SYS-STF Delta 100 x 150 For DS 400 abrasives	SYS 1	489 464	50.50
14	SYS-STF D 150 For 6" abrasives	SYS 3	487 431	63.00

Systainer® – the unique transport, storage and packaging system

Systainers with universal inserts




No.	Type	Size	Item No.	Price
1	SYS 1 Vari (not shown) with single diced foam insert to produce an aperture of any desired shape	SYS 1	487 410	48.50
2	SYS 2 Vari as SYS 1 Vari, but with double diced foam insert to produce an aperture of any desired shape	SYS 2	487 485	54.50
3	SYS 1 Uni with universal insert	SYS 1	487 194	49.50
4	SYS-OF D8/D12 for safe storage and carrying of up to 40 D8/D12 router bits, removable insert	SYS 1	487 925	58.00
5	SYS 1 Box with individual removable plastic compartments	SYS 1	487 552	53.50
6	Plastic compartments for SYS 1 Box Red, 12 pieces (54 x 54 x 63 mm) Yellow, 6 pieces (108 x 54 x 63 mm) Blue, 3 pieces (108 x 108 x 63 mm) Green, 2 pieces (162 x 108 x 63 mm)		487 657 487 658 487 659 487 660	10.50 7.50 5.50 5.50

Systainers with insert/application



No.	Description	Type	Item No.	Price
7	Hole drilling set complete accessories for drilling rows of Euro-holes for shelves and furniture fittings in a 32 mm grid pattern with the OF 1010 E router	LR 32-SYS	489 270	369.00
8	Tool organizer Wooden insert keeps hand tools organized and easy to get to. No more digging around. (Tools not included.) Insert comes in Systainer 4.	SYS-HWZ	491 301	103.00

Foam inserts for Systainers




No.	Description	Type	Item No.	Price
9	Foam insert set Dimpled insert (for lid) 1 base insert and 1 diced insert	SYS-Vari SE	487 427	16.00
10	Foam insert For SYS-Maxi For lid (not shown) For bottom (not shown)	SYS-Maxi SYS-Maxi	491 633 491 632	10.00 8.00
11	Foam insert for lid (not shown) For SYS-Mini	SYS-Mini	491 638	4.00
12	Diced foam insert Diced sections can be pushed out to produce any desired shape. 2 inserts in set	SYS-Vari RM	487 428	11.50
13	Foam insert for lid (not shown) For SYS 1 - SYS 5	SYS 1-5	491 640	4.00
14	Foam insert for bottom (not shown) For SYS 1 - SYS 5	SYS 1-5	491 642	4.00

Systainer® accessories


Individual – for every application

Foam inserts for application Systainers




No.	Description	Type	Item No.	Price
1	Systainer insert for hole drilling set accessories	SE-LR 32-SYS	489 432	27.50

Other accessories



No.	Description	Type	Item No.	Price
2	Toolie Tool Keys to fit all fasteners used in Festool tools	TOOLIE/1 TOOLIE/10	490 833 490 155	19.00 169.00
3	Locking latch (replacement) green gray	SVG-SYS/green SVG-SYS/gray	455 015 491 837	3.00 3.00



4	Systainer Port Secure, space saving, accessible storage of Systainers (Systainer Boxes not included) with 5 Systainer telescopic drawers, with casters	SYS-PORT 1000/2	491 922	480.00
5	Telescopic drawer replacement	SYS-PORT/TA/2 SYS-PORT/TA	491 923 487 802	80.00 76.00
6	Systainer cart mobile platform for Systainers max. load 110 lbs., comes with 4 locking straps	SYS-CART	492 388	67.00
7	Set of casters (replacement) for mobile use of the Systainer Port	SYS-PORT/RS	491 932	61.00

How many Systainers fit in a Systainer Port? Organizational/Configuration possibilities:

Configurations	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27
	For Sysport 1000/2*																										
Systainer size	No. of Systainers																										
Sys 1	8	6	6	5	5	4	4	3	3	3	3	2	2	2	2	2	1	1	1	-	-	-	-	-	-	-	-
Sys 2	-	1	-	2	-	1	-	1	2	3	-	1	2	4	-	-	2	3	-	1	1	2	3	4	5	-	-
Sys 3	-	-	1	-	-	1	2	-	1	-	1	2	-	-	3	-	2	1	2	-	3	1	-	1	-	4	1
Sys 4	-	-	-	-	1	-	-	1	-	-	1	-	1	-	-	2	-	-	1	2	-	1	1	-	-	-	2
Number of telescopic drawers needed*	8	7	7	7	6	6	6	5	6	6	5	5	5	6	5	4	5	5	4	3	4	4	4	5	5	4	3

* The Sysport 1000 is delivered with 5 telescopic drawers.

Sortainers



Keep small parts sorted and organized. These handy drawer sets latch onto Systainers and CT dust extractors. Same dimensions as a Systainer 3 – 15 5/8" L x 11 5/8" W x 8" H.

Sortainers open up endless possibilities. For example, by latching a tool Systainer to the top of a Sortainer, you have a self-contained carrying case complete with a tool and its consumables and accessories. Or latch two or more Sortainers together for a complete small-parts storage unit that you can break down and reconfigure as needed. Or latch a Sortainer and Systainer to a CT dust extractor for a rolling work unit – especially useful when you're working at a customer's site.

Sortainers



Description	Item No.	Price
1 4 drawer Sortainer	491 522	98.50
2 6 drawer Sortainer	491 984	98.50
3 9 drawer Sortainer	491 985	98.50
4 12 drawer Sortainer	491 986	102.00
5 Drawer latches pkg of 4 (not shown)	492 511	4.50
6 Locking latches pkg of 4 (not shown)	491 838	8.00

Festool Gear



Description	Item No.	Price
T-shirt Navy blue 100% preshrunk cotton		
Small	TSSM-o6	\$18.00
Medium	TSME-o6	\$18.00
Large	TSLG-o6	\$18.00
X-Large	TSXL-o6	\$18.00
XX-Large	TSXXL-o6	\$18.00



Cap Navy blue		
Low profile (relaxed structure)	CAPLP-o6	\$14.00
Mid profile (slightly reinforced structure)	CAPMP-o6	\$14.00



Festool Duffel Bag	M56990	\$25.00
Festool Thermos	M56991	\$18.00

Terms and conditions for purchases

Sales - We have a growing network of Festool dealers located throughout the U.S. Our factory trained dealers will provide demonstrations, answer any questions and take orders. A large number of our dealers have stores, where they stock a selection of Festool power tools, accessories and consumables.

For the most up-to-date listing of a Festool dealer nearest you, check our web site at www.festoolusa.com or call us toll-free at (888) 337-8600.

Easy Ordering

By phone - Call (888) 337-8600 toll free or (805) 685-3757 8AM - 5PM PST Monday through Friday.

Online - at www.festoolusa.com - Order online 24 hours a day, 7 days a week.

By Fax or Mail - Mail your order form to Festool USA, 140 Los Carneros Way, Goleta, CA 93117, or fax it to us at (888) 550-6425.

Pricing - Prices and availability of products in this catalog are subject to change without notice. Price information in this catalog supercedes all earlier catalogs. Festool reserves the right to discontinue any item.

Minimum Order Required - A minimum of \$10.00 is required for all orders. Orders below the minimum amount will be charged an order-processing fee equal to the difference between the actual dollar amount ordered and the specified minimum.

Payment Options

Credit Cards - We accept Visa, MasterCard, American Express, and Discover cards. Be sure to include account number, expiration date, signature and address of cardholder if different from mailing address. State and local taxes may apply, plus shipping & handling.

Check - For mail orders, pay by personal check, postal money order, and certified check or bank cashier's check, payable to Festool USA. Personal checks are subject to processing delays. Starter checks or checks without pre-printed name and address information may delay processing of your order as much as 3 weeks. All checks are subject to verification.

C.O.D. - Please add \$7.50 per box. C.O.D. orders are collect on delivery and available on orders up to \$500. Orders exceeding \$500 must be paid by certified check or money order, or be pre-approved by faxing in a copy of your check to (888) 550-6425 or (805) 685-5927. C.O.D. is available in the 48 contiguous states on UPS Ground shipping only.

Customer Service - For help with any questions you may have, to check the status of an order, or to request a catalog for yourself or a friend. Call 8AM - 5PM PST (888) 337-8600 Monday through Friday.

Shipping Policy

Orders shipping within the continental United States and placed directly with FESTOOL USA will be assessed a \$10 handling fee, regardless of order value. (Alaska, Hawaii, Puerto Rico & APO - additional shipping charges apply)

All orders are shipped UPS ground* - For Next Day, Second Day & Three day express shipping rates, please visit www.festoolusa.com or call our sales office at 1-888-337-8600.

*Orders in excess of 150 lbs and/or including any of the following items will be shipped via Common Carrier: item # 492652 - MFT 1080 Table; item #493933 - MFT 1080 Basic table; item #491922 - Systainer Port 1000 /2; item #491500 - FS 5000 /2 Guide rail; item #491501 - FS 3000 /2 Guide rail.

Additionally, orders shipped via Common Carrier require that the customer be present to inspect and sign for deliveries. Once the shipment has reached the destination terminal, the Carrier company will attempt to contact the customer in order to arrange a delivery time. If a delivery time cannot be scheduled within 3 business days, storage fees will begin to accrue at the rate of \$70 per day. Orders deemed undeliverable will be returned to our warehouse and subject to appropriate return freight charges.

Festool USA does not ship to Canada. Canadian residents should contact the Festool distributor in Canada: Hafele Canada; 5323 John Lucas Drive, Burlington, Ontario, L7L 6A8; toll-free 800-423-3531; phone 905-336-6608; fax 905-319-4445.

Warranty

30-Day Money Back Guarantee - We are so confident that you will thoroughly enjoy our tools, that we offer a 30-day money back guarantee. If you are not completely satisfied, we will refund the full purchase price, excluding all freight charges; simply call for a return authorization. No returns of any kind will be accepted without prior authorization. Call (888) 337-8600 for authorization. Items must be returned in original, unmarked packaging or will be subject to a 10% restocking fee.

1+2 Warranty - Festool offers a 3-year warranty, one of the longest in the industry. This warranty is valid on the pre-condition that the tool is used and operated in compliance with the Festool operating instructions. Festool warrants, only to the original purchaser, that the specified tool will be free from defects in materials and workmanship for a term of 3 years from the date of purchase.

Conditions of 1 + 2 warranty - You are entitled to a free extended warranty (1 year + 2 years = 3 years) for your Festool power tool. Festool is responsible for all shipping costs during the first year of the warranty. During the second and third year of the warranty the customer is responsible for shipping the tool to Festool. Festool will pay for return shipping to the customer using UPS Ground Service. All warranty service is valid 3 years from the date of purchase on your receipt or invoice.

Festool makes no other warranty, express or implied, for Festool portable power tools. No agent, representative, distributor, dealer, or employee of Festool has the authority to increase or otherwise change the obligations or limitations of this warranty. The obligations of Festool in its sole discretion under this warranty shall be limited to the repair or replacement of any Festool portable power tool that is found to be defective as packaged with the User Manual.

Excluded from the coverage under this warranty are: normal wear and tear; damages caused by misuse, abuse, or neglect; damage caused by anything other than defects in material and workmanship. This warranty does not apply to accessory items such as circular saw blades, drill bits, router bits, jigsaw blades, sanding belts, and grinding wheels. Also excluded are "wearing parts," such as carbon brushes, lamellas of air tools, rubber collars and seals, sanding discs and pads, and batteries.

Festool portable power tools requiring replacement or repair are to be returned to Festool. Call (800) 554-8741 for address details. In no event shall Festool be liable for any consequential or incidental damages for breach of this or any other warranty, express or implied whatsoever. All warranties implied by state law, including the implied warranties of merchantability and fitness for a particular purpose are hereby limited to the duration of three years.

Some states in the U.S. do not allow the limitations on how long an implied warranty lasts, so the above limitation may not apply to you. With the exception of any warranties implied by state or province law as hereby limited, the foregoing express limited warranty is exclusive and in lieu of all other warranties, guarantees, agreements, and similar obligations of Festool.

This warranty gives you specific legal rights and you may also have other rights that vary from state to state in the U.S.

Repairs - Power tools requiring replacement or repair are to be returned after calling our service department at (800) 554-8741.

Returns - If you need to return your Festool tool for any reason, you must contact our office at (888) 337-8600 for a return authorization. No collect shipments will be accepted.

Limitation of Liability - Festool's total liability to Buyer and Buyer's exclusive remedy for direct damages, regardless of injury, property damage, or schedule delays, shall, at Festool's sole option, be a refund of purchase price paid or replacement of the product. FESTOOL SHALL NOT BE LIABLE TO BUYER FOR ANY CONSEQUENTIAL, INCIDENTAL OR SPECIAL DAMAGES REGARDLESS OF THE THEORY OF LAW ON WHICH THE CLAIM IS BASED.

Warning

This document is a product catalog and is not meant to replace your instruction manual that comes with every tool.

Instruction Manual - For your safety and best optimum tool performance, be sure to read, understand, and follow all the safety and operating instructions in the instruction manual before using the tool. An instruction manual is furnished with every tool. If yours is lost or if you have questions please call (888) 337-8600 for a replacement.

Health - Various dusts created by power sanding, sawing, grinding, drilling, and other construction activities contains chemicals known (to the State of California) to cause cancer, birth defects or other reproductive harm. Some examples of these chemicals are: Lead from lead-based paints; crystalline silica, from bricks and cement and other masonry products; arsenic and chromium from chemically-treated lumber.

Your risk from these exposures varies, depending on how often you do this type of work. To reduce your exposure to these chemicals: work in a well-ventilated area, and work with approved safety equipment, such as dust masks that are specially designed to filter out microscopic particles. Festool recommends to use dust extractors with every power tool.

Disclaimer

Festool reserves the right to make changes or improvements on its products without incurring an additional obligation to make corresponding changes or improvements to products previously manufactured or sold. Festool reserves the right to discontinue products at any time without notice.

All illustrations and photographs displayed in this catalog are the property of Festool and shall not be duplicated or reproduced without the express written consent of Festool.

Festool is not responsible for typographical errors. Prices are subject to change and are only valid for sales shipped within the United States.

Festool dealers

🛠️ stock tools
🛒 stock accessories and consumables

ALASKA

Hardware Specialties 🛠️🛒
424 West 54th Ave
Anchorage, AK 99518
907-563-1312

ALABAMA

Thustool LLC 🛠️
Bo Thuston
BIRMINGHAM, AL 35202
205-999-3203; 800-289-7297

ARKANSAS

David Moppin
6528 South R Street
FORT SMITH, AR 72903
479-484-1099

ARIZONA

Tim Bonham 🛠️
MESA, AZ
480-330-0492
Woodcraft Phoenix 563 🛠️🛒
3002 N Arizona Ave #12
CHANDLER, AZ 85225
480-539-9663; 888-549-9663

Woodcraft Tucson 514 🛠️🛒
6230 N Oracle Road
TUCSON, AZ 85704
520-742-9663; 888-749-9663

Woodworkers Source 🛠️🛒
3441 South Palo Verde
TUCSON, AZ 85713
520-745-8301; 800-952-2123
Woodworkers Source 🛠️🛒
18115 North Black Canyon Hwy
PHOENIX, AZ 85023
602-504-1931

Woodworkers Source 🛠️🛒
5402 South 40th Street
PHOENIX, AZ 85040
602-437-4266; 800-423-2450

CALIFORNIA

Almquist Lumber 🛠️
100 Taylor Way
BLUE LAKE, CA 95525
707-668-5652
Anderson Plywood Sales 🛠️🛒
4020 Sepulveda Blvd
CULVER CITY, CA 90230
310-397-8229

Austin Hardwood Hardware 🛠️
610 N Santiago Street
SANTA ANA, CA 92701
714-953-4000
Battels Hardware & Tool Co 🛠️🛒

13238 E Whittier Blvd
WHITTIER, CA 90602
562-698-3714
Buena Tool 🛠️
433 Laguna Street
SANTA BARBARA, CA 93101
805-963-3885

CB Tool Group 🛠️🛒
90 Karina Ct
SAN JOSE, CA 95131
408-436-0707; 800-662-9858

Eagle Tools 🛠️🛒
3027 Treadwell Street
LOS ANGELES, CA 90065
323-999-2909

Eurosystems Montgomery Inc 🛠️🛒
139 Roosevelt Ave
NATIONAL CITY, CA 91950
619-477-2776; 800-333-2776

Ideal Saw Works 🛠️🛒
351 O Street
FRESNO, CA 93721
559-237-0809

Jacksons Hardware 🛠️🛒
435 Dubois Street
SAN RAFAEL, CA 94901
415-454-3740

The Japan Woodworker 🛠️
1731 Clement Ave
ALAMEDA, CA 94501
510-521-1810; 800-537-7820

MTA Technical Sales
7513 Wystone Ave
RESEDA, CA 91335
818-704-9700; 800-784-5816

Outlet Tool Supply 🛠️
7175 El Camino Real
ATASCADERO, CA 93422
805-461-7120; 877-886-1298

Paramount Saw
16493 Paramount Blvd
PARAMOUNT, CA 90723
562-633-0606; 800-237-7297

Peninsula Power Tool 🛠️🛒
828 Lighthouse Ave
MONTEREY, CA 93940
831-375-4244

Sacramento Machinery 🛠️🛒
729 W Del Paso Road
SACRAMENTO, CA 95834
916-568-7514

Santa Rosa Tool & Supply 🛠️🛒
1651 Piner Road
SANTA ROSA, CA 95403
707-545-6480

The Hardwood & Hardware Co 🛠️🛒
9040 Activity Road Bldg E
SAN DIEGO, CA 92126
858-536-1800

Tooland 🛠️🛒
1369 Industrial Road
SAN CARLOS, CA 94070
650-631-9636

Toolswitch
1302 S Claremont Street
SAN MATEO, CA 94402
650-576-1388

Truitt & White 🛠️🛒
642 Hearst Ave
BERKELEY, CA 94710
510-841-0511

Woodcraft Dublin 521 🛠️🛒
6044 Dougherty Road
DUBLIN, CA 94568
925-875-9988

Woodcraft San Carlos 561 🛠️🛒
1121 B Industrial Road
SAN CARLOS, CA 94070
650-631-9663

Woodcraft Santa Rosa 528 🛠️🛒
3589 Industrial Drive
SANTA ROSA, CA 95403
707-573-8157

Woodcraft Stanton 553 🛠️🛒
12781 Beach Blvd
STANTON, CA 90680
714-899-1422

COLORADO

Advantage Tools 🛠️
4057 Pioneer Road
MONTROSE, CO 81401
970-240-4290

Colorado Fasteners Inc 🛠️🛒
11450 N Cherokee St, Unit B-2
NORTHGLENN, CO 80234
303-450-2833

Colorado Fasteners Inc 🛠️🛒
34510 Hwy 6
EDWARDS, CO 81632
800-332-1514

Minitman Supply 🛠️
7350 Greendale Road
WINDSOR, CO 80550
970-667-8501

Sears Trostel Lumber 🛠️
1500 Riverside Ave
FORT COLLINS, CO 80524
970-482-1928

Woodcraft Co Springs 501 🛠️
5669 North Academy Blvd
COLORADO SPRINGS, CO 80918
719-266-9889

Woodcraft Denver 305 🛠️
4403 S. Tamarac Pkwy
DENVER, CO 80237
303-290-0007

CONNECTICUT

Brians Tool Sales 🛠️🛒
9 Moody Road
ENFIELD, CT 06082
860-763-1730

Coastal Tool & Supply Corp 🛠️🛒
510 New Park Ave
WEST HARTFORD, CT 06110
860-233-8213

Lindell True Value 🛠️🛒
59 Church Street
CANAAAN, CT 06018
800-480-3963

Mamsco, LLC
9 Tipping Drive
BRANFORD, CT 06405
203-481-9833

Woodcraft Manchester 534 🛠️🛒
249 Spencer Street
MANCHESTER, CT 06040
860-647-0303

Woodcraft Orange 546 🛠️🛒
150 Boston Post Road
ORANGE, CT 06477
203-799-7865

WoodWorkers Club 105 🛠️🛒
215 Westport Ave
NORWALK, CT 06851
203-847-9663

DELAWARE

Woodcraft New Castle 551 🛠️
166 S. Dupont Hwy Suite F
NEW CASTLE, DE 19720
302-323-0400

FLORIDA

Blackwater River Tools, Inc. 🛠️
2503 North V Street
PENSACOLA, FL 32505
850-470-9959

Empire Tool & Supply 🛠️🛒
6291 147th Ave North
CLEARWATER, FL 33760
800-535-6749

International Tool 🛠️🛒
2590 Davie Road
DAVIE, FL 33317
954-792-4403 x1

Marine Industry Tool
& Supply 🛠️🛒
3001 SW 3rd Ave, Bay 8
FORT LAUDERDALE, FL 33315
954-525-0199

Presher's 🛠️🛒
785 NE 19th Place Unit B
CAPE CORAL, FL 33909
239-574-2540

Presher's 🛠️🛒
2825 Davis Blvd
NAPLES, FL 34104
239-774-2525

Rugby Tampa 🛠️
7010 Benjamin Road, Ste 100
TAMPA, FL 33634
813-888-6824

Specialty Tools 🛠️
940 Lawhon Drive
JACKSONVILLE, FL 32259
800-669-5519

Woodcraft Clearwater 512 🛠️🛒
18891 US Highway 19 N
CLEARWATER, FL 33764
727-532-6888

Woodcraft Jacksonville 542 🛠️🛒
9280 Arlington Expressway 20A
JACKSONVILLE, FL 32225
904-721-9796

Woodcraft Miami 555 🛠️🛒
1157 South Federal Hwy
POMPANO BEACH, FL 33062
954-785-6321

GEORGIA

Millworks & Supply Inc
24 Mincey Blvd
GARDEN CITY, GA 31408
912-966-0770

Rugby Atlanta 🛠️
400 Indeco Blvd Suite C
ATLANTA, GA 30336
404-691-3402

SDC Sales & Consulting 🛠️
202 Northeast Cove Road
DAWSONVILLE, GA 30534
706-344-3985

HAWAII

Woodcraft Hawaii 526 🛠️🛒
1311 Kalani Street
HONOLULU, HI 96817
808-841-9876

IOWA

Woodsmith Store 🛠️🛒
10320 Hickman Road
CLIVE, IA 50325
800-835-5084

IDAHO

Nobel Woodworking 🛠️
2435 East Iona Road
IDAHO FALLS, ID 83401
208-529-3367

Woodcraft Boise 326 🛠️🛒
6883 W. Overland Road
BOISE, ID 83709
208-338-1190

ILLINOIS

Berlands House of Tools 🛠️🛒
600 Oak Creek Drive
Lombard, IL 60148
630-620-0026

Berlands House of Tools 🛠️🛒
20254 N. Rand Road
PALATINE, IL 60074
847-540-9200

Berlands House of Tools 🛠️🛒
1695 New Lenox Road
JOLIET, IL 60433
815-722-2000

Bruce Adhesives
245 Roosevelt, Bldg 10, Ste 67
WEST CHICAGO, IL 60185
630-293-8674

Woodcraft Palatine 322 🛠️🛒
1280 East Dundee Road, Dock 1
PALATINE, IL 60074
847-776-1184

Woodcraft Woodridge 519 🛠️🛒
7440 Woodward Ave
WOODRIDGE, IL 60517
630-435-9663

Woodworkers Shop - Morris 🛠️
3385 North Route 47
MORRIS, IL 60450
815-942-5865

Woodworkers Shop Inc 🛠️
13587 E Manito Road
PEKIN, IL 61555
309-347-5111

INDIANA

Brands Inc 🛠️🛒
1425 California Street
COLUMBUS, IN 47201
812-379-9566

Legendary Floors
601 S 21st Street
TERRE HAUTE, IN 47803
312-232-3372

Superior Distributing 🛠️
918-922 Ft Wayne Ave
INDIANAPOLIS, IN 46202
317-633-0555

Woodcraft Evansville 527
721 N Green River Road
EVANSVILLE, IN 47715
812-479-9663

Woodcraft Indianapolis 549 🛠️🛒
7330 East 86th Street
INDIANAPOLIS, IN 46256
317-578-3400

KENTUCKY

American Products of Kentucky
1810 Plantside Drive
LOUISVILLE, KY 40299
502-671-0505

LOUISIANA

Builders Best Tools 🛠️🛒
7424 Johnston Street
LAFAYETTE, LA 70503
337-993-2378

MASSACHUSETTS



Alliance Machinery Inc
24 St Martin Drive Bldg 2
MARLBOROUGH, MA 01752
508-303-0600

Beaver Woodworking Supplies 🛠️
1 Brockton Ave
BROCKTON, MA 02302
508-583-4631

Burns Tools Inc 🛠️
350 Mariano S Bishop Blvd
FALL RIVER, MA 02721
800-341-2200


Calvo Studio
186 E Main Street
GLOUCESTER, MA 01930
978-283-0231

Festool dealers


 stock tools
 stock accessories and consumables

Monument Tools



28 Mill Street
ASSONET, MA 02702
508-644-2400

Northeast Tool & Supply 
157 Thornton Drive
HYANNIS, MA 02601
508-778-4552


right-tool.com
3 Bonazolli Ave
HUDSON, MA 01749
978-562-5575
Woodcraft West Springfield
559 
239 A Memorial Ave
WEST SPRINGFIELD, MA 01089
413-827-0244


Woodcraft Woburn 304 
313 Montvale Ave
WOBBURN, MA 01801
781-935-6414

MARYLAND

Cayce Company 
221-B Cockeysville Road
HUNT VALLEY, MD 21030
410-771-0225
Chesapeake Woodworkers
Sales 
7017 ENM Ellwood Road
HURLOCK, MD 21643
410-820-8582


Hard Surface Consulting
2645 Putnam Road
FOREST HILL, MD 21050
443-807-3660

Industrial Finishes 
14622 Southlawn Lane
ROCKVILLE, MD 20850
301-424-3033


Skarie Inc 
707 North Howard Street
BALTIMORE, MD 21201
410-728-6000

MAINE


Advantage Gases-Lewiston 
44 Hammond Street
LEWISTON, ME 04240
207-784-4588


Bath Industrial Sales 
56 New Meadows Road
WEST BATH, ME 04530
207-443-9754

MICHIGAN


Accurate Systems 
172 Garden Court
WHITMORE LAKE, MI 48189
734-891-9375

Electric Tool & Equipment 
3680 S State Street
ANN ARBOR, MI 48108
734-995-1111

Glenn Wing Power Tools 
33656 Woodward Ave
BIRMINGHAM, MI 48009
800-448-1572

Wood Source Inc 
2701 29th Street SE
GRAND RAPIDS, MI 49512
616-285-0600

MINNESOTA

Betterley Industries Inc 
11160 Central Ave NE
BLAINE, MN 55434
763-755-3425

Fabricators Choice LLC

23 Empire Drive
ST PAUL, MN 55103
888-299-8840

Seven Corners Hardware 
216 West 7th Street
SAINT PAUL, MN 55102
800-328-0457


Woodcraft Bloomington
306 
9125 Lyndale Ave South
BLOOMINGTON, MN 55420
952-884-3634

MISSOURI


Ballew Saw & Tool 
325 South Kimbrough Ave
SPRINGFIELD, MO 65806
417-865-7511
BTI Supply 
4029 Gravois Ave
SAINT LOUIS, MO 63116
314-773-5999

Woodcraft St Louis 309
12511 Olive Blvd
CREVE COEUR, MO 63141
314-434-5779

MISSISSIPPI

Ameitech South 
210 Industrial Drive
RIDGELAND, MS 39157
601-853-0830

MONTANA

A&H Turf & Specialties Inc 
468 S Moore Lane
BILLINGS, MT 59101
406-245-8466

NORTH CAROLINA


Eagle Distribution
3031 Bruce Pugh Road
FRANKLINVILLE, NC 27248
336-824-4400

Klingspor - Charlotte 
4728 South Blvd
CHARLOTTE, NC 28217
704-521-8886


Klingspor - Hickory 
856 21st Street Drive SE
HICKORY, NC 28602
828-327-7263


Klingspor - Raleigh 
3141 Capital Blvd
RALEIGH, NC 27604
919-876-0707

Klingspor - Winston Salem 
532 Hanes Mall Blvd
WINSTON SALEM, NC 27103
336-768-9663


Woodcraft Charlotte 507 
1725 Windsor Square Drive
MATTHEWS, NC 28105
704-847-8300


NEBRASKA

Hardwood Heaven, Inc. 
3822 S 14th Street
LINCOLN, NE 68502
402-423-5993


Tighton Fastener & Supply 
6620 "F" Street
OMAHA, NE 68117
402-331-5550

NEW HAMPSHIRE

Brentwood Machinery &
Tools 
313 State Route 125
BRENTWOOD, NH 03833
800-582-7229

Minuteman Tool Repair Inc 
96 Epping Road
EXETER, NH 03833
866-664-6883

National Industrial Supplies
578 West Unity Road
CLAREMONT, NH 03743
603-542-3900


Woodcraft Newington 505 
45 Gosling Road Suite 4
NEWINGTON, NH 03801
603-433-6116

NEW JERSEY

Auxiliary Service Inc
802 Silvia Street
TRENTON, NJ 08628
609-737-0986


Darf Spray Equipment 
5 Mathews Ave
RIVERDALE, NJ 07457
973-283-1068

Force Machinery Co Inc 
2271 Route 22 West
UNION, NJ 07083
908-688-8270

Godwin Tool & Hardware
Supplies 
189 Greenwood Ave
MIDLAND PARK, NJ 07432
201-445-4431


Hoboken Floors
70 Demarest Drive
WAYNE, NJ 07470
973-694-2888 x4147

Home Décor Products
47 Brunswick Ave
EDISON, NJ 08817
888-801-2559

Robert Marino 
14 Inness Place
GLEN RIDGE, NJ 07028
973-896-4388

Ultimate Garage 
235 Kinderkamack Road
EMERSON, NJ 07630
201-262-0412

NEW MEXICO

Woodcraft Albuquerque 547 
4520B Alexander Blvd NE
ALBUQUERQUE, NM 87107
505-342-9663

NEVADA

Apex Saw Works
570 Kietzke Lane
RENO, NV 89502
775-329-3076; 800-960-7297


Woodworkers Emporium 
125 N Gibson Road
HENDERSON, NV 89014
702-567-8223

Woodworkers Emporium 
5461 S Arville Street
LAS VEGAS, NV 89118
702-871-0722

NEW YORK

Ace Tool Repair Inc 
2201 Wantagh Ave
WANTAGH, NY 11793
516-783-8899

Bruce Hall Corporation 
206 Main Street
COOPERSTOWN, NY 13326
607-547-9961

Dynamite Tool Co 
1551 Smithtown Ave
BOHEMIA, NY 11716
631-563-8181


JIT Hardware Supplies, Inc.
13 Jeanne Drive
NEWBURGH, NY 12550
800-480-5543


One Source Tool Supply,
Inc 
341 County Road 39A
SOUTHAMPTON, NY 11968
631-283-8700

Power Tools & Abrasives 
790 Walck Road
NORTH TONAWANDA, NY 14120
888-782-8665


Select Machinery Inc
64-30 Ellwell Crescent
REGO PARK, NY 11374
718-897-3937


Sienna Diamond Products 
1159 Nepperhan Ave
YONKERS, NY 10703
917-553-3314

Tool Factory Outlet 
Route 17 M
GOSHEN, NY 10924
845-294-7900

Trinity Abrasives 
3009 Rt. 17C
TIOGA CENTER, NY 13845
607-330-0279


Warren Cutlery Corp 
3584 Rt. 9-G
RHINEBECK, NY 12572
845-876-3444


Woodcraft Albany 557 
935 New Loudon Road
LATHAM, NY 12110
518-783-3192

Woodcraft Rochester 531 
1100 Jefferson Road
ROCHESTER, NY 14623
585-292-9690

OHIO

Cleveland Tool & Cutter,
Inc. 
14181 Foltz Industrial Parkway
STRONGSVILLE, OH 44149
440-238-5770

Electric Tool & Equipment 
3637 Briarfield Blvd
MAUMEE, OH 43537
419-867-7670


Hartville Hardware, Inc 
940 West Maple Street
HARTVILLE, OH 44632
330-877-3631

Mueller Company Inc 
101 East Benson Street
CINCINNATI, OH 45215
513-761-6777


Ohio Valley Supply Company
3512 Spring Grove Ave
CINCINNATI, OH 45223
800-696-5608

Wood Werks Supply 
1181 Claycraft Road
COLUMBUS, OH 43230
800-860-9375


Woodcraft Dayton 513 
175 East Alex-Bell Road
DAYTON, OH 45459
937-438-1282


Woodcraft Hilliard 508 
4562 Cemetery Road
HILLIARD, OH 43026
614-527-7594

OKLAHOMA


Snyder Tool 
1501 Peachtree Ct
EDMOND, OK 73003
405-844-1044


OREGON

National Builders Hardware
Co 
1019 SE 10th Ave
PORTLAND, OR 97214
503-233-5381

Woodcraft Portland 312 
12020 SW Main Street
TIGARD, OR 97223
503-684-1428; 866-684-1428

PENNSYLVANIA


Hearne Hardwoods 
200 Whiteside Drive
OXFORD, PA 19363
610-932-7400

Kayhart Company 
127 E Pittsburgh Street
GREENSBURG, PA 15601
724-836-8766


Maxwell Products Corp 
425 Industrial Drive
NORTH WALES, PA 19454
215-699-2224


RT Byrnes Co Inc 
600 Hannum Ave
WEST CHESTER, PA 19380
610-692-2770

Saw Sales & Machinery 
5160 N Pioneer Road
GIBSONIA, PA 15044
724-443-3200


Woodcraft Downingtown 537 
417 Boot Road
DOWNINGTOWN, PA 19335
610-873-5660


Woodcraft Harrisburg 523
777 Eisenhower Blvd
HARRISBURG, PA 17111
717-939-6770

Woodcrafters Supply 
7703 Perry Hwy Rt 19
PITTSBURGH, PA 15237
412-367-4330

Woodworkers Haven 
60 James Way Unit # 7
SOUTHAMPTON, PA 18966
215-953-1955


RHODE ISLAND

Jamestown Distributors LLC 
17 Peckham Drive
BRISTOL, RI 02809
401-253-3840

Massasoit Tool Company 
110 Minnesota Ave
WARWICK, RI 02888
401-739-6676

Woodcraft East Greenwich
535 
1000 Division Street
EAST GREENWICH, RI 02818
401-886-1175

SOUTH CAROLINA

Mann Tool and Supply Inc 
802 Chris Drive
WEST COLUMBIA, SC 29169
803-252-7777

The Tool Shed 
901 Poinsett Hwy
GREENVILLE, SC 29609
864-233-6185; 800-233-6185

Festool dealers

🔧 stock tools
🔧 stock accessories and consumables

Woodcraft Charleston 529 🇺🇸
975 Savannah Hwy
CHARLESTON, SC 29407
843-573-8700

TENNESSEE

Webb Fabricators Supply 🇺🇸
603 Joe Joyner Road
ATOKA, TN 38004
901-837-1581

Woodcraft Nashville 552 🇺🇸
209 S Royal Oaks Blvd Ste 164
FRANKLIN, TN 37064
615-599-9638

TEXAS

Cooks Sharpening Service 🇺🇸
1214 Northpoint Drive
SAN MARCOS, TX 78666
512-353-4504

Woodcraft Dallas 317 🇺🇸
14380 Marsh Lane
ADDISON, TX 75001
972-241-0701

UTAH

M & M Tool and Machinery 🇺🇸
1773 S 300 West
SALT LAKE CITY, UT 84115
801-485-8200

Woodcraft Sandy 311 🇺🇸
9891 South 500 West
SANDY, UT 84070
801-566-5652

VIRGINIA

Fries Beall & Sharp Co Inc 🇺🇸
7300-10 Lockport Place
LORTON, VA 22079
703-550-1100

Harper Hardware 🇺🇸
1712 East Broad Street
RICHMOND, VA 23223
804-643-9007

Integrated Marine Supply
9411 Main Street
MANASSAS, VA 20110
877-462-7787

McFeely's Square Drive Screws
3720 Cohen Place
LYNCHBURG, VA 24501
800-443-7937

Woodcraft Leesburg 575 🇺🇸
512 East Market Street
LEESBURG, VA 20176
703-737-7880

Woodcraft Norfolk 556 🇺🇸
5802 E Virginia Beach Blvd 152
NORFOLK, VA 23502
757-466-1166

Woodcraft Springfield 327 🇺🇸
6123B Backlick Road
SPRINGFIELD, VA 22150
703-912-6727

VERMONT

Spooner Specialties 🇺🇸
120 River Street
MONTPELIER, VT 05602
802-229-4800

WASHINGTON

Bills Festool Supply NW 🇺🇸
23002 56th Ave West
MOUNTLAKE TERRACE, WA 98043
(North Seattle) 425-673-7873

Coast Woodworking
Machinery 🇺🇸
17120 Tye Street
MONROE, WA 98272
360-588-1980

Edensaw Seattle 🇺🇸
8032 S 194th Street
KENT, WA 98032
253-216-1150

Edensaw Wood 🇺🇸
211 Seton Road
PORT TOWNSEND, WA 98368
360-385-7878

Hardware Sales 🇺🇸
2034 James Street
BELLINGHAM, WA 98225
360-734-6140

Woodcraft Seattle 307 🇺🇸
5963 Corson Ave South
SEATTLE, WA 98108
206-767-6394

Woodcraft Spokane 573 🇺🇸
212 N Sullivan Rd Unit C
SPOKANE, WA 99037
509-892-9663

WISCONSIN

Blake Stevens Wood Flooring 🇺🇸
636 Commerce Drive
HUDSON, WI 54016
866-360-9663

Blake Stevens Wood Flooring 🇺🇸
3201 Progress Way
KAUKAUNA, WI 54130
866-354-9663

Blake Stevens Wood Flooring 🇺🇸
822 Walsh Road
MADISON, WI 53714
877-804-0588

Blake Stevens Wood Flooring 🇺🇸
N27 W23727 Paul Road
PEWAUKEE, WI 53072
800-322-4088

Woodcraft Appleton 520 🇺🇸
4731 Michaels Drive
APPLETON, WI 53915
920-730-9663

Woodcraft Madison 504 🇺🇸
616 Westgate Mall
MADISON, WI 53711
608-273-8868

Woodcraft Milwaukee 506 🇺🇸
1725 South 108th Street
WEST ALLIS, WI 53214
414-607-6164

WEST VIRGINIA

Woodcraft Corporation 🇺🇸
1177 Rosemar Road
PARKERSBURG, WV 26102
304-422-5412

Festool dealers online

Accurate Systems
<http://www accuratesystems.biz>

Ace Tool Repair Inc
<http://www.acetool.com/festool.htm>

Ballew Saw & Tool
<http://ballewtools.com>

Beaver Woodworking Supplies
<http://www.beaverwoodworking.com>

Bob Marino's Festool Store
<http://festool.safeshopper.com>

BTI Supply; Beaver Tools Inc
<http://www.btisupply.com>

Burns Tools Inc
<http://www.burnstools.com>

Dynamite Tool Co
<http://dynamitetoolco.com>

Force Machinery Company Inc
<http://www.forcemachinery.biz/festool.htm>

Hearne Hardwoods
<http://www.hearnehardwoods.com>

Home Décor Products
<http://www.hechinger.com>

International Tool
<http://www.internationaltool.com>

Jamestown Distributors LLC
<http://www.jamestowndistributors.com>

The Japan Woodworker
<http://www.thejapanwoodworker.com>

Kayhart Company
<http://www.kayhartsupplies.com>

McFeely's Square Drive Screws
<http://www.festools.com>

Minuteman Tool Repair Inc
<http://www.minutemantool.com>

MTA Technical Sales
<http://www.mtasales.com>

Outlet Tool Supply
<http://www.outlettools.com>

Power Tools and Abrasives
<http://www.industrialtool.com>

Right-tool.com
<http://www.right-tool.com>

Seven Corners Hardware
<http://www.7corners.com>

















SpecialtyTools.com
<http://www.specialtytools.com>

Toolbarn.com
<http://www.toolbarn.com/brand/festool>

Tool Factory Outlet
<http://www.toolfactoryoutlet.com>

Toolswitch
<http://www.toolswitch.com>

Festool feature icons

Spir-O-Cut  <p>Single-blade planer head offers advantages: no adjustment of cutting circle diameter after blade replacement.</p>	Patented Jetstream system  <p>Improves dust extraction through an outlet hole in the center of the sanding pad.</p>	StickFix STF  <p>Quick, easy, economical hook-and-loop adhesive fastening. No gluing, no clamping.</p>	Multi-Material Control (MMC) electronics  <p>Modern electronic power control with constant speed under load.</p>
Jigsaw with precision guides  <p>Heat-resistant hard-wearing jaws guide the saw blade directly over the cutting line.</p>	Dust extraction  <p>Standard port or dust extraction to safeguard your health and keep the work area clean.</p>	Vibration-Stop  <p>VS balancing gives smooth running with orbital sanders, Rotex, and eccentric sanders.</p>	Torque shut-off  <p>The right torque for driving fasteners in any material. Prevents screws from snapping or pulling through material.</p>
FastFix  <p>Facilitates the changing of routing, cutting, planing, drilling, and sanding tools.</p>	Turbo Dust extraction  <p>Sander equipped with internal fan – dust can be extracted to attachable dust bag.</p>	MPE High Performance Motor  <p>Highly durable material for all orbital sander and Rotex sander pads.</p>	 <p>Extremely compact, powerful motor for easier handling and more comfortable operation.</p>
Antistatic function  <p>Eliminates static charges and shocks when working with dust extractors and tools.</p>	Plug it  <p>For fast power-cord replacement. Just insert the cord and engage it with a quarter turn. That's all there is to it.</p>	Patented FS guidance system  <p>Precise guidance for saws and routers. Greater safety, higher precision, and more efficiency.</p>	 <p>For your increased safety.</p>

Festool USA
Tooltechnic Systems, LLC
140 Los Carneros Way
Goleta, CA 93117
Tel 888.337.8600
Fax 888.550.6425
www.festoolusa.com



Festool USA Master Catalog 2006
USA \$5 / Replaces all previous catalogs
MC 04/06